

Material Safety Data Sheet



ITW Texwipe® Wipers pre-wetted with 60% - 70 % IPA

1. Product and company identification

Product name	: ITW Texwipe® Wipers pre-wetted with 60% - 70 % IPA
Code	: TX1041, TX1045, TX1065
Material uses	: For use in Cleanroom Environments and Other for various cleaning and Cleanroom Maintenance Operations.
Supplier/Manufacturer	: ITW Texwipe 1210 South Park Drive Kernersville, NC 27284 Tel : 1-(336) 996-7046 (Toll Free : 1-(800) 839-9473) Fax : 1-(336) 996-6563 Website : www.texwipe.com
MSDS authored by	: KMK Regulatory Services Inc.
In case of emergency	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

Emergency overview

Physical state	: Pre-wetted wipers.
Color	: Colorless.
Odor	: Alcohol-like. [Strong]
Signal word	: WARNING!
Hazard statements	: FLAMMABLE SOLID. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Precautionary measures : Keep away from heat, sparks and flame. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation	: Irritating to respiratory system.
Ingestion	: No known significant effects or critical hazards.
Skin	: Irritating to skin.
Eyes	: Irritating to eyes.

Potential chronic health effects

Chronic effects	: Contains material that may cause target organ damage, based on animal data.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: central nervous system (CNS).

Over-exposure signs/symptoms

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.

2. Hazards identification

- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Propan-2-ol	67-63-0	60 - 70

Canada

Name	CAS number	%
Propan-2-ol	67-63-0	60 - 70

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
Propan-2-ol	67-63-0	UN1219	60 - 70	2000 ppm	1	3	0	

Final product is comprised of solid cloth media that is saturated with the above components. Fill volume is controlled to ensure that no free liquid is present in the final product packaging.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention if symptoms occur.
- Inhalation** : Move exposed person to fresh air. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
- Notes to physician** : No specific treatment. Treat symptomatically.

5. Fire-fighting measures

- Flammability of the product** : Flammable.
- Extinguishing media**
- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
 - Not suitable** : Do not use water jet.
- Special exposure hazards** : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions : Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Spill : Place spilled material in an appropriate container for disposal.

7. Handling and storage

Handling : Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Wash thoroughly after handling.

Storage : Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Propan-2-ol	<p>ACGIH TLV (United States, 2/2010). STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s).</p> <p>NIOSH REL (United States, 6/2009). STEL: 1225 mg/m³ 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 980 mg/m³ 10 hour(s). TWA: 400 ppm 10 hour(s).</p> <p>OSHA PEL (United States, 6/2010). TWA: 980 mg/m³ 8 hour(s). TWA: 400 ppm 8 hour(s).</p>

Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	Notations
Propan-2-ol	US ACGIH 2/2010	200	-	-	400	-	-	-	-	-	
	AB 4/2009	200	492	-	400	984	-	-	-	-	
	BC 9/2010	200	-	-	400	-	-	-	-	-	
	ON 7/2010	200	-	-	400	-	-	-	-	-	
	QC 6/2008	400	983	-	500	1230	-	-	-	-	

Mexico

Occupational exposure limits

Ingredient	Exposure limits
Propan-2-ol	<p>NOM-010-STPS (Mexico, 9/2000). LMPE-CT: 1225 mg/m³ 15 minute(s). LMPE-CT: 500 ppm 15 minute(s). LMPE-PPT: 980 mg/m³ 8 hour(s). LMPE-PPT: 400 ppm 8 hour(s).</p>

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

8. Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
- Personal protection**
- Respiratory** : Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure an MSHA/NIOSH-approved respirator or equivalent is used.
- Hands** : Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).
- Eyes** : Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Lab coat.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

- Physical state** : Pre-wetted wipers.
- Flash point** : Closed cup: 20 °C (68 °F) [Tagliabue.]
- Color** : Colorless.
- Odor** : Alcohol-like. [Strong]
- Relative density** : 0.89
- VOC content** : 57.1 % (w/w), 57.7 % (w/w), 58.9 % (w/w)

10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials and alkalis.
- Hazardous decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propan-2-ol	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-

11. Toxicological information

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Propan-2-ol	A4	3	-	-	-	None.

IDLH : Not available.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Propan-2-ol	Acute LC50 1400000 to 1950000 ug/L Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 >1400000 ug/L	Fish - Gambusia affinis - 20 to 30 mm	96 hours

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations





Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

International transport regulations

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	-	ORM-D	-	-		-
TDG Classification	UN3175	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)	4.1	II		Remarks Limited quantity
Mexico Classification	UN3175	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)	4.1	II		Remarks Limited quantity
IMDG Class	UN3175	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)	4.1	II		Remarks Limited quantity
IATA-DGR Class	UN3175	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)	4.1	II		Remarks Limited quantity

PG* : Packing group

Exemption to the above classification may apply.

AERG : 133

15. Regulatory information

United States

HCS Classification : Flammable solid
Irritating material
Target organ effects

U.S. Federal regulations : **TSCA 8(a) IUR Exempt/Partial exemption:** Not determined
United States inventory (TSCA 8b): All components are listed or exempted.
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Propan-2-ol
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
Propan-2-ol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Propan-2-ol	67-63-0	60 - 70
Supplier notification	Propan-2-ol	67-63-0	60 - 70

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Propan-2-ol

New York : None of the components are listed.

New Jersey : The following components are listed: Propan-2-ol

Pennsylvania : The following components are listed: Propan-2-ol

California Prop. 65

No products were found.

Canada

WHMIS (Canada) : Class B-4: Flammable solid.
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Isopropyl alcohol

CEPA Toxic substances : None of the components are listed.


Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

15. Regulatory information

Classification :



International regulations

International lists :

- Australia inventory (AICS):** All components are listed or exempted.
- China inventory (IECSC):** All components are listed or exempted.
- Japan inventory:** All components are listed or exempted.
- Korea inventory:** All components are listed or exempted.
- New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.
- Philippines inventory (PICCS):** All components are listed or exempted.

16. Other information

Label requirements : FLAMMABLE SOLID. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Hazardous Material Information System (U.S.A.) : Health : 1 * Flammability : 3 Physical hazards : 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) : Health : 1 Flammability : 3 Instability : 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Canada

WHMIS (Canada) :



History

Date of issue : 02/28/2011
Date of previous issue : 07/01/2009
Version : 4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.