



HMIS Rating

# MATERIAL SAFETY DATA SHEET

## GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label) YELLOW 77® PLUS Wire Pulling Lubricant	CATALOG NUMBER All "31" Series
MANUFACTURER'S NAME <b>IDEAL INDUSTRIES, INC.</b>	EMERGENCY TELEPHONE NO. <b>(815) 895-5181</b>
ADDRESS (Number, Street, City, State, Zip Code) <b>Becker Place, Sycamore, IL 60178</b>	
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS NO., HAZARD ID NO. (49 CFR 172.101) None	
CHEMICAL DESCRIPTION Water-Wax Emulsion	FORMULA Proprietary

### SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, IARC or OSHA 1910(z) (specify)
7732-18-5	<90	Water	No
64742-43-4	<5	Paraffin Wax	No
8009-03-8	<5	Petrolatum U.S.P	No
8042-47-5	<5	White Mineral Oil U.S.P (See *A)	No
9005-08-7	<5	Poly(oxy-1,2-ethanediy), a-(1-oxo-9-octadecenyl)-w-(1-oxooctadecyl)oxy-	No
61791-44-4	<1	Ethanol, 2,2'-iminobis-,N-tallow alkyl derivs	No
8042-47-5 24838-91-8	<1	Acrylamide Sodium Acrylate Copolymer with Trideceth-6	No
1310-58-3	<2	20% Potassium Hydroxide	No
52-51-7	<0.1	2-Bromo-2-Nitropropane 1,3 Diol	No
5989-27-5	<0.1	Lemon Fragrance	No
6358-31-2	<0.1	Butanamide, 2-[(2-methoxy-4-nitrophenyl)azo]-N-(2-methoxyphenyl)-3-oxo-	No
9002-84-0	<0.1	Polytetrafluoroethylene	No

### SECTION II - PHYSICAL DATA

BOILING POINT 212°F 100°C	SPECIFIC GRAVITY (H <sub>2</sub> O=1) 0.93	PERCENT VOLATILE BY VOLUME (%) <90
SOLUBILITY IN WATER Moderate	pH = 6.5 - 7.5	PERCENT SOLID BY WEIGHT (%) ~15
APPEARANCE AND ODOR Yellow creamy paste, slight odor	IS MATERIAL: LIQUID SOLID GEL GAS <u>PASTE</u>	

### SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT None	method used C.O.C	FLAMMABLE LIMITS	LEL None	UEL None
EXTINGUISHING MEDIA Use extinguishing media suitable for surrounding materials.				
SPECIAL FIRE FIGHTING PROCEDURES Self-contained respiratory protection should be provided for fire fighters. Keep fire exposed containers cool with water.				
UNUSUAL FIRE AND EXPLOSION HAZARDS None				

- None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R. 1910.1200
- A: Oil is severely hydrotreated with a polymorphonuclear content at less than 0.1% and meets OSHA 29 C.F.R. 1910.1200.

**SECTION IV - HEALTH HAZARD INFORMATION**

EFFECTS OF OVEREXPOSURE - Conditions to Avoid	None normally expected. Upon prolonged contact, may cause temporary eye discomfort.
THRESHOLD LIMIT VALUE	None established
PRIMARY ROUTES OF ENTRY Inhalation <input checked="" type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify)	
EMERGENCY FIRST AID PROCEDURES	
SKIN CONTACT:	Wash with soap and water for 15 minutes.
EYE CONTACT:	Flush with water for 15 minutes. Inhalation: Remove to fresh air.
INGESTION:	Administer water or milk. Consult physician or local poison control center.

**SECTION V - REACTIVITY DATA**

STABILITY	UNSTABLE		CONDITIONS TO AVOID	None
	STABLE	X		
INCOMPATIBILITY (materials to avoid)				
Avoid strong oxidizers.				
HAZARDOUS DECOMPOSITION PRODUCTS:				
Excessive heat and burning may release oxides of carbon and nitrogen.				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	Avoid prolonged storage at temperatures above 120 F.
	WILL NOT OCCUR	X		

**SECTION VI - SPILL AND LEAK PROCEDURES**

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	Wipe up, shovel or vacuum spilled material. Clean up spills immediately as can be dangerously slippery.
WASTE DISPOSAL METHOD	Comply with Federal, state and local regulations for solid landfill.
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs)	None Required
RCRA HAZARDOUS WASTE NO. (40CFR 261.33)	None Required
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water)	2.6 gms / ltr
<sup>3</sup> Theoretical _____ lb/gal	N/A
<sup>4</sup> Analytical _____ lb/gal	N/A

**SECTION VII - PERSONAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (specify type)	None normally required.		
VENTILATION	LOCAL EXHAUST (Specify Rate)	None	SPECIAL None
	MECHANICAL (General) (Specify Rate)	Recommended in closed areas.	OTHER None
PROTECTIVE GLOVES (specify type)	None normally needed. -Neoprene if necessary		
EYE PROTECTION (specify type)	Safety glasses or splash goggles.		
OTHER PROTECTIVE EQUIPMENT	Eye fountain in work area is recommended.		

**SECTION VIII - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Store at temperatures between 40 - 120° F.
OTHER PRECAUTIONS	Keep away from children, infants and pets.

**SECTION IX - ADDITIONAL INFORMATION**

If material is used in extreme heat (>120° F), prolonged and repeated exposure could pose a risk of pulmonary disease. Exposure below TLV (5mg/m) appears to be without risk.
---

N/A = Not Applicable, N.E. = None Established

THIS MATERIAL SAFETY DATA SHEET PREPARED BY:

NAME	James R. MacMurdo	SIGNATURE  <i>James R. MacMurdo</i>
TITLE	Director, Corporate Quality Assurance	
DATE	02/11/2009	