

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Address:

8125 Cobb Center Drive
Kennesaw, GA 30152

Product Information: 800-TECH-401
Customer Service: 800-645-5244

Emergency: (Chemtec) 800-424-9300
Revision Date: February 17, 2010

Product Identification

Electro-Wash® MX Pen

Product Code: FW2150, FW2150BLK

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Wt. % Range
Naphtha	64741-66-8	60.0-90.0
Ethanol	64-17-5	1.0-25.0
Ethyl acetate	141-78-6	0.1-10.0
Isopropanol	67-63-0	1.0-20.0

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Clear, colorless liquid with mild hydrocarbon odor. This product is extremely flammable. Liquid may irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product may produce drowsiness and a headache.

Potential Health Effects:

Eyes: Liquid and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Skin: Contact causes skin irritation.

Ingestion: Harmful if swallowed. Irritating to the mouth, throat and stomach. May cause vomiting.

Inhalation: Harmful if inhaled. High concentrations in immediate area can displace oxygen and cause dizziness, unconsciousness and even death, with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

Pre-Existing Medical Conditions Aggravated by Exposure: Heart, lung, skin, eye.

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persist. Wash clothing separately before reuse.

Ingestion: If swallowed, do not induce vomiting. Keep head below knees to minimize chance of aspirating material into the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: 45 F (7C) TCC

LEL/UEL: 0.9/6.2 (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Shut off leak if possible and safe to do so. Wear a self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (i.e. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches that lead to waterways.

Small Spills: Absorb spill with inert material (i.e. dry sand or earth), then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with skin, eyes or clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor. Do not reuse this container. Store in a cool dry place, away from heat, sparks or flames. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL	OTHER
Naphtha	NA	NA	NA	281 ppm (Exxon)
Ethanol	1000 ppm	1000 ppm	NA	
Isopropanol	200 ppm	400 ppm	400ppm	
Ethyl acetate	400 ppm	400 ppm	NA	

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields, goggles and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:	NFPA	HMIS
Health	1	1
Flammability	3	3
Reactivity	1	1
Personal Protection	-	B

