



Revision Number: 003.0

Issue date: 02/22/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 294 Threadlocker Wicking Grade	IDH number: 232774
Product type: Anaerobic Sealant	Item number: 27936
	Region: United States
Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information: Telephone: 860.571.5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Liquid	HEALTH: *2
Color: Green	FLAMMABILITY: 1
Odor: Mild	PHYSICAL HAZARD: 1
	Personal Protection: See MSDS Section 8

HMIS:

WARNING: CAUSES EYE IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
MAY CAUSE SKIN IRRITATION.
HARMFUL IF SWALLOWED OR INHALED.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	May cause respiratory tract irritation. N-Phenylmaleimide is highly toxic by inhalation.
Skin contact:	May cause allergic skin reaction. May cause skin irritation with discomfort or rash.
Eye contact:	Contact with eyes will cause irritation.
Ingestion:	Harmful if swallowed. N-phenylmaleimide is toxic by ingestion.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Triazine ester	Unknown	10 - 30
1H-Pyrrole-2,5-dione, 1-phenyl-	941-69-5	10 - 30
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	24448-20-2	5 - 10
1H-Pyrrole-2,5-dione, 1,1'-[methylenebis(2-ethyl-	105391-33-1	1 - 5
Maleic acid	110-16-7	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Wash with soap and water. Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 93.3 °C (> 199.94 °F) Tagliabue closed cup
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Not available.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours. Toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Storage:	For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Triazine ester	None	None	None	None
1H-Pyrrole-2,5-dione, 1-phenyl-	None	None	None	None
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	None	None	None	None
1H-Pyrrole-2,5-dione, 1,1'-[methylenebis(2-ethyl-	None	None	None	None
Maleic acid	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls:	No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Eye/face protection:	Safety goggles or safety glasses with side shields.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Green
Odor:	Mild
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	0.7 kPa (20 °C (68 °F))
Boiling point/range:	> 149 °C (> 300.2 °F)
Melting point/ range:	Not available.
Specific gravity:	1.1229
Vapor density:	Not available.
Flash point:	> 93.3 °C (> 199.94 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Slight Partition
coefficient (n-octanol/water):	Not available.
VOC content:	< 4 %; < 44.92 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours. Toxic fumes.
Incompatible materials:	Iron. copper Aluminum. Rust. Zinc. Reducing agents. Strong acids and oxidizing agents. Oxygen scavengers. Strong alkalis. Peroxides. Heat, sunlight, or UV light.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Triazine ester	No	No	No
1H-Pyrrole-2,5-dione, 1-phenyl-	No	No	No
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	No	No	No
1H-Pyrrole-2,5-dione, 1,1'-[methylenebis(2-ethyl-	No	No	No
Maleic acid	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate	Irritant, Allergen
Triazine ester	No Target Organs
1H-Pyrrole-2,5-dione, 1-phenyl-	Irritant
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	Irritant, Allergen
1H-Pyrrole-2,5-dione, 1,1'-[methylenebis(2-ethyl-	No Records
Maleic acid	Irritant, Kidney
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Toxic, liquids, organic, n.o.s. (n-Phenylmaleimide)
Hazard class or division: 6.1
Identification number: UN 2810
Packing group: III
Exceptions: (Not more than 4 L), ORM-D, Consumer Commodity

International Air Transportation (ICAO/IATA)

Proper shipping name: Toxic liquid, organic, n.o.s. (n-Phenylmaleimide)
Hazard class or division: 6.1
Identification number: UN 2810
Packing group: III
Exceptions: (Not more than 500 ml), Consumer Commodity, ID 8000, Class 9

Water Transportation (IMO/IMDG)

Proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (n-Phenylmaleimide, Methylphenyl-dimaleimide)
Hazard class or division: 6.1
Identification number: UN 2810
Packing group: III
Marine pollutant: Methylphenyl-dimaleimide

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS:	None above reporting de minimus
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA 313:	None above reporting de minimus
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
WHMIS hazard class:	D.1.B, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Updated Contact Information in Section 1.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.