

SAI Global File # 004008

Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Carbon Conductive Grease SDS Code: 846

Related Part # 846-80G, 846-1P, 846-1G

Recommended Use and Restriction on Use

Use: electrically conductive lubricant for switches

Uses Advised Against: Avoid uses that result in aerosolization

Details of Manufacturer or Importer

Manufacturer

MG Chemicals MG Chemicals (Head Office) 1210 Corporate Drive 9347-193 Street Surrey, British Columbia V4N 4E7 Burlington, Ontario L7L 5R6 CANADA CANADA

A +1-800-340-0772 +1-905-331-1396 FAX +1-800-340-0773 FAX +1-905-331-2682 E-MAIL support@mqchemicals.com **E-MAIL** <u>info@mgchemicals.com</u>

WEB www.mgchemicals.com

E-MAIL (Competent Person): sds@mqchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents

USA or CANADA: Call CHEMTREC ☎: +1-800-424-9300

For emergencies involving dangerous goods; Collect 24/7

CANADA: Call CANUTEC : +1-613-996-6666 or *666 on cellular phones

Date of Creation: 07 April 2015 / Ver. 2.01

SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Section 2: Hazards Identification

Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Carcinogenicity	2	Warning	Health

Note: The degree of severity in a category is ranked from 1 (Highest Severity) to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions.

Other Classifications

HMIS® RATING

HEALTH:	*	1
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H351: Suspected of causing cancer
Prevention	Precautionary Statements
P201 + P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P280	Wear protective gloves/eye protection/face protection.

Section continued on the next page

Page **2** of **13**

Date of Creation: 07 April 2015 / Ver. 2.01



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Continued...

Response	Precautionary Statements
P308 + P313	IF exposed or concerned: Get medical advice/attention.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/national/international regulations.

Other Hazards

Not applicable

Section 3: Hazardous Ingredients

CAS # Chemical Name		Wt%
63148-62-9	dimethylpolysiloxane ^{a)}	80%
1333-86-4	carbon black	20%

a) Non-hazardous component

Section 4: First Aid Measures

Exposure Condition	GHS Code: Precautionary Statement	
IF INHALED	P304 + P340, P308 + P313 (Not a likely route of exposure under normal use)	
Immediate Symptoms	None known or expected	
Response	Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.	
	If exposed or concerned: Get medical advice/attention	
IF IN EYES	P305, P351+ P338, P337+P313	
Immediate Symptoms	mild irritation (discomfort)	
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

IF ON SKIN

Immediate Symptoms *None expected.*

Response Clean with soap and water.

IF SWALLOWED

Immediate Symptoms None known or expected

Response Do NOT induce vomiting.

Get medical advice/attention if feeling unwell.

Section 5: Fire Fighting Measures

Auto-ignition	Not	Flash Point a)	>300 °C	LFL [LEL] b)	Not
Temperature	available		[572 °F]	UFL [UEL]	available

In case of fire	P370 +P378
Response	Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	At temperatures of 150 °C [302 °F] and above, formaldehyde can be generated in the presence of oxygen. Formaldehyde is classified as a human carcinogen, skin sensitizer, respiratory sensitizer, and eye and throat irritant.
	Prevent fire-fighting wash from entering waterway or sewer system.

Combustion Products Produces carbon oxides (CO, CO₂), SiO₂ and formaldehyde **Fire-Fighter** Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

a) Cleveland open cup

b) LF[E]L = Lower Flammability [or Explosion] Limit (in volume %); UF[E]L = Upper Flammability [or Explosion] Limit (in volume %)



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Protection

Precautions for Do not breathe the mist/spray. Remove or keep away all sources of

Response

extreme heat or open flames.

Environmental Precautions

Avoid releasing to the environment.

Containment

Contain the spill and cover drains.

Cleaning

The material presents a slip hazard and must be cleaned thoroughly. Collect liquid in a sealable container. Scoop into the container. Wipe up further residue with paper towel and place dirty towels in container. Wash spill area with steam, solvents, or detergents to remove the last

traces of residue.

Disposal

Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood.

Do not get in eye, on skin, or on clothing.

Handling Wear protective gloves/eye protection.

Storage Store locked up.

RECOMMENDATION: Keep in a dry and clean area, away from

incompatible substances.

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Skin contact, Eye contact, Ingestion, Inhalation



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
Carbon black a)	ACGIH	3.5 mg/m ³	_
	U.S.A. OSHA PEL	3.5 mg/m ³	_
	Canada AB	3.5 mg/m ³	_
	Canada BC	3 mg/m ³	_
	Canada ON	3.5 mg/m ³	_
	Canada QC	3.5 mg/m ³	_

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted.

a) Respirable airborne particles

Engineering Controls

Ventilation

Normal ventilation is generally adequate. The carbon black particles are bound in the grease matrix and are not available as a respiration hazard under normal conditions.

If the product is exposed to extreme heat or combustion conditions, see the advice in the PPE respiratory protection

subsection.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection Wear appropriate protective clothing to prevent skin contact.

Respiratory Protection If exposed to aerosols, wear oil resistant or oil proof

particulate respirators or filter masks.

If the product is exposed to extreme heat or combustion conditions, wear a NIOSH approved self-contained breathing

apparatus (SCBA) or supplied air respirator.

RECOMMENDATION: Consult your local safety supply store to

ensure your respirator or mask.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Section 9: Physical and Chemical Properties				
Physical State	Liquid	Appearance	Black grease	
Odor	None	Odor Threshold	Not applicable	
рН	Not available	Specific Gravity	1.1	
Solubility in Water @ 25 °C	Insoluble	Melting/Freezing Point	Not available	
Boiling Point	>200°C [>392 °F]	Evaporation Rate	<1 (ButAc = 1)	
Flash Point a)	>300°C [572 °F]	Vapor Pressure @ 25 °C	0.13 kPa [1 mmHg]	
Lower Flammability Limit	Not available	Upper Flammability Limit	Not available	
Auto-ignition Temperature	Not available	Decomposition Temperature	Not available	
Viscosity @25 °C	570 000 cSt	Vapor Density	>1 (Air = 1)	
Partition Coefficient	Not available			

a) Cleveland open cup

Section 10: Stability and Reactivity

Reactivity	Not available

Chemical Chemically stable at normal temperatures and pressures

Stability

Ignition sources, excessive heat, and incompatible substances.

Conditions to Avoid

Incompatibilities Strong oxidizing agents, strong acids

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Section 11: Toxicological Information

Routes of Exposure

Eye contact, Inhalation, and Skin contact

Symptoms Summary

Eyes May cause mild eye irritation, redness.

Skin No known significant effects.
 Inhalation No known significant effects.
 Ingestion No known significant effects.
 Chronic No known long term effect.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50	TCLo
	oral	dermal	inhalation	inhalation
dimethylpolysiloxane	>5 000 mg/kg	>10 000 mg/kg	>535 mg/L	Not
	Rat	Rabbit	Rat	available
carbon black	>15 g/kg	>3 g/kg	Not	1.6 mg/m³
	Rat	Rabbit	established	7 h Rat

Note: Representative toxicity data from by RTECS database of the Canadian Centre for Occupational Health and Safety (CCOHS)¹ data from supplier MSDS were also consulted.

Other Toxicological Effects

Skin corrosion/irritation No known effects

Serious eye damage/irritation

May cause mild eye irritation.

Sensitization

Not available

(allergic reactions)



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Carcinogenicity

(risk of cancer)

The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures. Because the carbon black is bound in the highly viscous grease matrix, it is not

expected to be available as an airborne hazard (dust, mist,

or spray) under normal and foreseeable uses.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen

NTP: Not listed

Mutagenicity

(risk of heritable genetic

effects)

Not available

Reproductive Toxicity

(risk to sex functions)

Not available

Teratogenicity (risk of fetus malformation)

Not available

STOT-single exposure

Not available

STOT-repeated exposure

Not available

Aspiration hazard

Not classified as aspiration hazard: the mixture does not contains Class 1 aspiration toxicant and its viscosity is

>20.5 mm²/s at 40 °C

Section 12: Ecological Information

The IMDG Code criteria and the raw-material MSDS along with supporting data for the classification of registered substances from the European Chemical Agency database (http://echa.europa.eu) were used.

The polydimethyl siloxane fluid and carbon black are not classifiable as ecotoxic hazards under GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Chronic Ecotoxicity

Not data available

Biodegradability

Not readily biodegradable

Global Warming Potential

No data available

Other Effects

VOC (Regulated Volatile Organic Content) = 0% [0 g/L]

All components are VOC exempt in Canada and the USA.

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations) and **USA 49CFR Regulations** (Parts 100 to 185).

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Section 15: Regulatory Information

Canada

WHMIS Classification



D2A - Very Toxic Material (Carcinogen IARC: 2B)

Note: The carcinogenic warning applies with respect to dust inhalation. Because the carbon black is inextricably bound in the grease matrix, it is not an expected route of entry during usages and processing of this product.

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

USA

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

N Chemicals

Quality System Certified to ISO 9001:2008

SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any of the listed substances.

Europe

RoHS

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

MSDS Prepared by Michel Hachey

Date of Issue 07 April 2015

Supersedes 04 February 2014

Volatile Organic Content

Reason for Changes: Correction to section 5 and review with respect to WHMIS 2015 regulations.

Reference

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

VOC

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
PPE	Personal Protection Equipment
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average



SAI Global File # 004008 Burlington, Ontario, Canada

CARBON CONDUCTIVE GREASE

846

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only.

M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international

regulations.