

ISOPROPANOL, 99%, (Isopropyl Alcohol 99%)

	<u>SPECIFICATIONS</u>
Specific Gravity, 20°/20°C (D-268)	0.785 - 0.787
Distillation, °C (D-1078)	1.5 range to include 82.3
Acidity, % by wt, as Acetic Acid (D-1613)	0.002 max
Water, % by wt (D-1364)	0.1 max
Nonvolatiles, mg/100 ml (D-1353)	5 max
Color, Pt-Co (D-1209)	5 max
Water Miscibility (D-1722)	passes test
Assay	99.8 min
SHIPPING DATA:	
Pounds per Gallon, 20°C	6.55
Kg per Liter, 20°C	0.79
Flash Point, °F (T.C.C.)	53 (11.7°C)
DOT Label Required	Flammable Liquid
DOT Identification No.	UN 1219

Nexeo Isopropanol 99% sales specifications comply with but are not certified to the following specifications:

- TT-I-735 Isopropyl Alcohol
- ASTM D-770 Isopropyl Alcohol

Code: 20286 (BULK)

C.A.S. No.: 67-63-0

C.A.S. Registry Name: 2-Propanol

() Indicates ASTM Test Method

1407

NOTICE: Nexeo Solutions makes no warranty or representation as to the suitability of the product as specified herein for any particular application. The determination of the suitability of the above specification for any particular use is solely the responsibility of the user.

All precautionary labels and notices should be read and understood by all supervisory personnel and employees before using. Consult Nexeo Solutions and OSHA regulations for additional safety and health information. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product. Special attention should be given to consumer applications. Freedom to use any patent owned by Nexeo Solutions or others is not to be inferred from any statement contained herein.

© 2011, Nexeo Solutions

nexeoTM
solutions