

**RTV627
SILICONE POTTING COMPOUND****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Manufacturer Name: Momentive Performance Materials LLC
260 Hudson River Road
Waterford NY 12188

Revised: 04/04/2013

Prepared by Product Safety Team
CHEMTREC 1-800-424-9300
MSDS Contact 1-888-443-9466
Information 4information@momentive.com

Chemical Family/Use: Silicone Elastomer

Formula: Mixture

HMIS

Health: 1 Flammability: 1 Reactivity: 0

NFPA

Health: 1 Flammability: 1 Reactivity: 0

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

CAUTION! May cause skin, eye, and respiratory tract irritation. Attention: Not for injection into humans.

Form: Liquid

Form: Black

Odor: Faint

POTENTIAL HEALTH EFFECTS**INGESTION**

Not an anticipated route of exposure.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Eye; Dermal

**RTV627
SILICONE POTTING COMPOUND****3. COMPOSITION/INFORMATION ON INGREDIENTS****PRODUCT COMPOSITION****CAS-No.****WGT. %****A. HAZARDOUS****B. NON-HAZARDOUS**

polyvinylsiloxane	68083-19-2	30 - 60 %
QUARTZ	14808-60-7	30 - 60 %
Carbon Black	1333-86-4	1 - 5 %

4. FIRST AID MEASURES**INGESTION**

If swallowed, do NOT induce vomiting. Give a glass of water. Do not give victim anything to drink if he is unconscious. Get medical attention.

SKIN

Wash with soap and water.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:	> 204 °C; 399 °F
IGNITION TEMPERATURE:	Not applicable
FLAMMABLE LIMITS LEL:	No data available.
FLAMMABLE LIMITS UEL:	No data available.

SENSITIVITY TO MECHANICAL IMPACT: No

**RTV627
SILICONE POTTING COMPOUND**

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

FURTHER INFORMATION

Use standard firefighting procedures and consider the hazards of other involved materials.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed. Avoid contact with eyes, skin, and clothing. Keep out of reach of children. May generate formaldehyde at temperatures greater than 150 C(300 F). See Section 8 of the MSDS for Personal Protective Equipment.

STORAGE

Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING CONTROLS**

Eye wash facilities and emergency shower must be available when handling this product.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations

**RTV627
SILICONE POTTING COMPOUND**

(see 29CFR 1910.134).

EYE AND FACE PROTECTION

Safety glasses with side shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS-No.</u>	<u>Source</u>	<u>Value</u>
------------------	----------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°C):	>260 °C; 500 °F
VAPOR PRESSURE (20 C) (MM HG):	Negligible
VAPOR DENSITY (AIR=1):	1.0
FREEZING POINT:	Not applicable
PHYSICAL STATE:	Liquid
ODOR:	Faint
Color:	Black
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY:	ca. 1.4
DENSITY:	ca. 1.4 g/cm3
ACID / ALKALINITY (MEQ/G):	No data available.
pH:	No data available.
SOLUBILITY IN WATER (20 C):	Insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Toluene

10. STABILITY AND REACTIVITY**STABILITY**

Stable

**RTV627
SILICONE POTTING COMPOUND**

HAZARDOUS POLYMERIZATION.

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Silicon dioxide.; Formaldehyde.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBLE MATERIALS

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Remarks: No data available.

CARCINOGENICITY

The National Toxicology Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA Formaldehyde Workplace Standard at 29 CFR 1920.1048 (the "OSHA Standard"). Safe handling and use instructions are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov; <http://monographs.iarc.fr>; <http://ntp-server.niehs.nih.gov>; <http://epa.gov>; <http://www.nap.edu> and other authoritative websites then search on formaldehyde.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

SENSITIZATION

No data available.

**RTV627
SILICONE POTTING COMPOUND**

SKIN IRRITATION.

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

No data available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION**Inventories**

Australia Inventory of Chemical Substances (AICS)	y (positive listing)
EU list of existing chemical substances	y (positive listing)
Japan Inventory of Existing & New	y (positive listing)

**RTV627
SILICONE POTTING COMPOUND**

Chemical Substances (ENCS)

China Inventory of Existing Chemical Substances y (positive listing)

Chemical Substances

Korea Existing Chemicals Inventory (KECI) y (positive listing)

Canada DSL Inventory y (positive listing)

Canada NDSL Inventory n (Negative listing)

Philippines Inventory of Chemicals and Chemical Substances (PICCS) y (positive listing)

TSCA list y (positive listing) On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information**SARA (311,312) HAZARD CLASS**

No SARA Hazards

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Canadian Regulatory Information**WHMIS CLASSIFICATION**

D2A - Very Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit

NEGL = negligible

EST = estimated

NF = none found

NA = not applicable

UNKN = unknown

NE = none established

REC = recommended

ND = none determined

V = recommended by vendor

SKN = skin

TS = trade secret

R = recommended

MST = mist

NT = not tested

STEL = short term exposure limit

ppm = parts per million

ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).



**MATERIAL SAFETY DATA
SHEET**

Version: 1.5
04/04/2013

**RTV627
SILICONE POTTING COMPOUND**
