



MSDS Name **DFense Blok™ Surface Wetting Agent**
 Manufacturer Name ITW Polymers Adhesives, North America
 Stock No.: 11340
 Kit MSDS Revision Date 12/30/2012

Components	
	DFense Blok™ Surface Wetting Agent Hardener
	DFense Blok™ Surface Wetting Agent Resin
ITW Polymers Adhesives, North America Product Code : 11340	

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **DFense Blok™ Surface Wetting Agent Hardener**
 MSDS Manufacturer Number: 0273
 Manufacturer Name: ITW Polymers Adhesives, North America
 Address: 30 Endicott Street
 Danvers, MA 01923
 General Phone Number: (978) 777-1100
 Emergency Phone Number: (800) 424-9300
 CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
 MSDS Creation Date: 2/25/2011
 MSDS Revision Date: 2/5/2013

HMIS	
Health Hazard	3*
Fire Hazard	1
Reactivity	0
Personal Protection	X

* Chronic Health Effects

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Inert material	N/A	5 - 10 by weight
Diethylenetriamine	111-40-0	5 - 10 by weight
1-(2 hydroxypropyl) Imidazole	37788-55-9	30 - 60 by weight
Non-hazardous ingredients.	N/A	30 - 60 by weight
Aminoethylpiperazine	140-31-8	1 - 5 by weight
Triethanolamine	102-71-6	1 - 5 by weight
Titanium Dioxide	13463-67-7	0.1 - 1 by weight

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview: **DANGER!** Corrosive. Potential Sensitizer Irritant.
 Route of Exposure: Eyes, Skin, Inhalation, Ingestion.
 Potential Health Effects:
 Eye: Corrosive. Will cause eye burns, permanent tissue damage, and blindness.
 Skin: Contact causes severe skin irritation and possible burns. may cause permanent skin damage. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
 Inhalation: May cause severe respiratory system irritation. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
 Ingestion: Harmful if swallowed. Corrosive to the gastrointestinal tract.
 Chronic Health Effects: Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.
 Signs/Symptoms: Depending on solution concentration, material may be corrosive to skin, mucous membranes and eyes. Vapors may cause respiratory irritation.
 Target Organs: Eyes, Skin, Respiratory system, Digestive system.
 Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Class III B.
Flash Point:	>200°F (93.3°C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO ₂) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Corrosive. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes and skin. Do not reuse containers without proper cleaning or reconditioning.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in reactive metal containers. Keep away from acids, oxidizers.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Diethylenetriamine:

Guideline ACGIH: 1 ppm
Skin: Yes
TLV-TWA: 1 ppm

Titanium Dioxide:

Guideline ACGIH: 10 mg/m³
TLV-TWA: 10 mg/m³

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.
Color: Amber.
Odor: Ammonia like fishy.
Boiling Point: >212°F (100°C)
Melting Point: Not determined.
Specific Gravity: 0.99
Solubility: >30%
Vapor Density: >1 (air = 1)
Vapor Pressure: <21 mmHg @70°F
Percent Volatile: Not determined.
Evaporation Rate: <1 (butyl acetate = 1)
pH: alkaline
Molecular Formula: Mixture
Molecular Weight: Mixture
Flash Point: >200°F (93.3°C)
Flash Point Method: Estimated.
Auto Ignition Temperature: Not determined.
VOC Content: Not determined.
Percent Solids by Weight: Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.
Hazardous Polymerization: Not reported.
Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Product may slowly corrode copper, aluminum, zinc and galvanized surfaces.
Incompatible Materials: Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

SECTION 11 : TOXICOLOGICAL INFORMATION

Diethylenetriamine:

RTECS Number: IE1225000
Skin: Administration onto the skin - Rabbit : 1090 mg/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Guinea pig : 170 uL/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Rabbit : 500 mg
Administration onto the skin - Rabbit : 500 mg
Ingestion: Oral - Rat LD50: 1080 mg/kg [Behavioral - Convulsions or effect on seizure threshold]

Aminoethylpiperazine:

RTECS Number: TK8050000
Eye: Eye - Rabbit Standard Draize test.: 20 mg/24H [Moderate]
Skin: Administration onto the skin - Rabbit LD50 : 880 uL/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Rabbit Open irritation test: 100 ug/24H
Administration onto the skin - Rabbit Standard Draize test.: 5 mg/24H [severe]
Ingestion: Oral - Rat LD50 : 2140 uL/kg [Details of toxic effects not reported other than lethal dose value]

Triethanolamine:

RTECS Number: KL9275000
Eye: Eye - Rabbit Standard Draize test.: 20 mg
Eye - Rabbit Standard Draize test.: 10 mg
Skin: Administration onto the skin - Rat : >16 mL/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Rabbit : >20 mL/kg [Details of toxic effects not reported other than lethal dose value]

[Kidney/Ureter/Bladder - Changes in kidney weight Skin and Appendages - Dermatitis, other (After systemic exposure) Nutritional and Gross Metabolic - Weight loss or decreased weight gain]
Administration onto the skin - Mouse : 260 gm/kg/13W (Intermittent)
[Liver - Changes in liver weight Kidney/Ureter/Bladder - Changes in kidney weight Skin and Appendages - Dermatitis, other (After systemic exposure)]
Administration onto the skin - Guinea pig : 32 gm/kg/4D (Intermittent)
[Related to Chronic Data - death]
Administration onto the skin - Rat : 22750 mg/kg/13W (Intermittent)
[Behavioral - Irritability Skin and Appendages - Primary irritation (After topical exposure)]
Administration onto the skin - Mouse : 182000 mg/kg/13W (Intermittent) [Behavioral - Irritability Skin and Appendages - Primary irritation (After topical exposure)]
Administration onto the skin - Rat : 45990 mg/kg/2Y (Intermittent)
[Kidney/Ureter/Bladder - Tumors Skin and Appendages - Primary irritation (After topical exposure) Tumorigenic - Increased incidence of tumors in susceptible strains]
Administration onto the skin - Rat : 45990 mg/kg/2Y (Intermittent)
[Behavioral - Irritability Skin and Appendages - Primary irritation (After topical exposure)]
Administration onto the skin - Mouse : 459900 mg/kg/2Y (Intermittent)
[Vascular - Tumors Skin and Appendages - Primary irritation (After topical exposure) Tumorigenic - Increased incidence of tumors in susceptible strains]
Administration onto the skin - Mouse : 730000 mg/kg/2Y (Intermittent)
[Liver - Tumors Skin and Appendages - Primary irritation (After topical exposure) Tumorigenic - Increased incidence of tumors in susceptible strains]
Administration onto the skin - Mouse : 2000 mg/kg/17W (Continuous)
[Nutritional and Gross Metabolic - Weight loss or decreased weight gain]
Administration onto the skin - Mouse : 100 mg/kg/104W (Continuous)
[Liver - Tumors Skin and Appendages - Corrosive (After topical exposure)]
Administration onto the skin - Mouse : 100 mg/kg/104W (Continuous)
[Liver - Other changes Liver - Tumors]
Administration onto the skin - Mouse : 630 mg/kg/104W (Continuous)
[Liver - Angiosarcoma]
Administration onto the skin - Human : 15 mg/3D (Intermittent)
Administration onto the skin - Rabbit : 560 mg/24H
Administration onto the skin - Mouse : 50 %
Administration onto the skin - Rat : 129 gm/kg/2Y (Intermittent)
[Tumorigenic - equivocal Tumorigenic agent by RTECS criteria Kidney/Ureter/Bladder - Tumors]
Administration onto the skin - Rat : 90125 mg/kg/103W (Intermittent)
[Tumorigenic - equivocal Tumorigenic agent by RTECS criteria Kidney/Ureter/Bladder - Kidney tumors]
Oral - Rat LD50: 4920 uL/kg [Sense Organs and Special Senses (Eye) - Lacrimation Gastrointestinal - Hypermotility, diarrhea Skin and Appendages - Hair]
Oral - Mouse LD50: 5846 mg/kg [Behavioral - Convulsions or effect on seizure threshold Gastrointestinal - Hypermotility, diarrhea Kidney/Ureter/Bladder - Other changes]

Ingestion:

Titanium Dioxide:

RTECS Number: XR2275000
Skin: Administration onto the skin - Human : 300 ug/3D (Intermittent)
Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.
Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Refer to Bill of Lading
DOT UN Number: Refer to Bill of Lading

SECTION 15 : REGULATORY INFORMATION

Diethylenetriamine :

TSCA Inventory Status: Listed
Massachusetts: Listed
Pennsylvania: Listed
Canada DSL: Listed

1-(2 hydroxypropyl) Imidazole :

TSCA Inventory Status: Listed

TSCA Inventory Status: Listed
 Massachusetts: Listed: Massachusetts Oil and Hazardous List
 Pennsylvania: Listed
 Canada DSL: Listed
Triethanolamine:
 TSCA Inventory Status: Listed
 Massachusetts: Listed: Massachusetts Oil and Hazardous List
 Pennsylvania: Listed
 Canada DSL: Listed
Titanium Dioxide:
 TSCA Inventory Status: Listed
 Massachusetts: Listed
 Pennsylvania: Listed
 Canada DSL: Listed
 Canadian Regulations: WHMIS Hazard Class(es): E; D2B
 All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms



SECTION 16 : ADDITIONAL INFORMATION

HMIS Fire Hazard: 1
 HMIS Health Hazard: 3*
 HMIS Reactivity: 0
 HMIS Personal Protection: X
 MSDS Creation Date: 2/25/2011
 MSDS Revision Date: 2/5/2013
 MSDS Author: Actio Corporation

Copyright © 1996-2011 Actio Software Corporation. All Rights Reserved.

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **DFense Blok™ Surface Wetting Agent Resin**
 MSDS Manufacturer Number: 0773
 Manufacturer Name: ITW Polymers Adhesives, North America
 Address: 30 Endicott Street
 Danvers, MA 01923
 General Phone Number: (978) 777-1100
 Emergency Phone Number: (800) 424-9300
 CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
 MSDS Creation Date: 2/25/2011
 MSDS Revision Date: 12/30/2012

HMIS	
Health Hazard	2*
Fire Hazard	1
Reactivity	1
Personal Protection	X

* Chronic Health Effects

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Elastomer Modified Diglycidyl Ether	68909-14-8	10 - 30 by weight
Inert material	N/A	5 - 10 by weight
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	30 - 60 by weight
Neopentyl glycol diglycidyl ether	17557-23-2	1 - 5 by weight
Reaction Product of Epichlorohydrin & Bisphenol A	25085-99-8	10 - 30 by weight
Bisphenol A diglycidyl ether resin	25068-38-6	10 - 30 by weight
Butadiene-Acrylic Copolymer	Proprietary	5 - 10 by weight

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Potential Sensitizer Irritant.
 Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
 Potential Health Effects:

Skin:	Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion:	Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects:	Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms:	Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point:	>200°F (93.3°C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization. Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

	levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Viscous. Liquid.
Odor:	mild.
Boiling Point:	Not determined.
Melting Point:	Not determined.
Specific Gravity:	> 1
Solubility:	Not determined.
Vapor Density:	>1 (air = 1)
Vapor Pressure:	Not determined.
Percent Volatile:	0
Evaporation Rate:	Not determined.
pH:	Neutral.
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	>200°F (93.3°C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
Percent Solids by Weight	100

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300 F in the presence of air may cause slow oxidative decomposition.
Incompatible Materials:	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

SECTION 11 : TOXICOLOGICAL INFORMATION

Neopentyl glycol diglycidyl ether:

RTECS Number:	TX3760000
Skin:	Administration onto the skin - Mouse TDLo : 9393 mg/kg/2Y-I [Tumorigenic - Equivocal tumorigenic agent by RTECS criteria Skin and Appendages - Tumors] Administration onto the skin - Mouse TD : 11 gm/kg/3Y-I [Tumorigenic - Equivocal tumorigenic agent by RTECS criteria Skin and Appendages - Tumors] Administration onto the skin - Mouse TD : 17 gm/kg/2Y-I [Tumorigenic - Equivocal tumorigenic agent by RTECS criteria Skin and Appendages - Tumors] Administration onto the skin - Mouse TD : 25 gm/kg/3Y-I [Tumorigenic - Equivocal tumorigenic agent by RTECS criteria Skin and Appendages - Tumors]
Ingestion:	Oral - Rat LD50 : 4500 mg/kg [Details of toxic effects not reported other than lethal dose value]

Reaction Product of Epichlorohydrin & Bisphenol A:

Ingestion:	Oral - Rat LD50: 11300 uL/kg [Details of toxic effects not reported other than lethal dose value]
------------	---

Bisphenol A diglycidyl ether resin:

RTECS Number:	SL6480000
Skin:	Administration onto the skin - Rat LD : >2 gm/kg [Nutritional and Gross Metabolic - Other changes]

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.
Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number: Not determined.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.
DOT UN Number: Not applicable.
DOT Hazard Class: Not applicable.
DOT Packing Group: Not applicable.

SECTION 15 : REGULATORY INFORMATION**Elastomer Modified Diglycidyl Ether :**

TSCA Inventory Status: Listed
Canada DSL: Listed

Phenol, polymer with formaldehyde, glycidyl ether :

TSCA Inventory Status: Listed
Canada DSL: Listed

Neopentyl glycol diglycidyl ether :

TSCA Inventory Status: Listed
Canada DSL: Listed

Reaction Product of Epichlorohydrin & Bisphenol A :

TSCA Inventory Status: Listed
Canada DSL: Listed

Bisphenol A diglycidyl ether resin :

TSCA Inventory Status: Listed
Canada DSL: Listed
Canadian Regulations. WHMIS Hazard Class(es): D2B

WHMIS Pictograms**SECTION 16 : ADDITIONAL INFORMATION**

HMIS Fire Hazard: 1
HMIS Health Hazard: 2*
HMIS Reactivity: 1
HMIS Personal Protection: X
MSDS Creation Date: 2/25/2011
MSDS Revision Date: 12/30/2012
MSDS Author: Actio Corporation

Copyright © 1996-2011 Actio Software Corporation. All Rights Reserved.