



SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **CLEANER BLEND 300**
Stock No.: 19510
Manufacturer Name: ITW Polymers Adhesives, North America
Address: 30 Endicott Street
Danvers, MA 01923
General Phone Number: (978) 777-1100
Emergency Phone Number: (800) 424-9300
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
MSDS Revision Date: December 30, 2012
(M)SDS Format:

HMIS	
Health Hazard	2*
Fire Hazard	2
Reactivity	1
Personal Protection	X

* Chronic Health Effects

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
1-methoxy-2-propanol acetate	108-65-6	10 - 30 by weight
2-methoxy-1-propanol	1589-47-5	1 - 5 by weight
d-Limonene	5989-27-5	5 - 10 by weight
Non-hazardous ingredients.	N/A	10 - 30 by weight
Propylene glycol monomethyl ether	107-98-2	30 - 60 by weight

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Flammable. Irritant.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:
Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.
Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.
Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.
Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs: Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Flammable.
Flash Point:	104°F (40°C)
Flash Point Method:	Tag closed cup (TCC)
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	3.0%
Upper Flammable/Explosive Limit:	12%
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Flammable, eliminate ignition sources. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Ventilate area. Use proper personal protective equipment as listed in section 8.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures. Do not reuse containers without proper cleaning or reconditioning.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use.
Special Handling Procedures:	Hazardous liquid or vapor residue may remain in emptied container. Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES**Propylene glycol monomethyl ether :**

Guideline ACGIH: 100 ppm
 TLV-STEL: 150 ppm
 TLV-TWA: 100 ppm

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.
 Color: Pale Amber.
 Odor: Ethereal.
 Boiling Point: 212°F (100°C) initial
 Melting Point: Not determined.
 Specific Gravity: 0.95
 Solubility: Appreciable.
 Vapor Density: >1 (air = 1)
 Vapor Pressure: 12 mmHg @68°F
 Percent Volatile: 100
 Evaporation Rate: <1 (butyl acetate = 1)
 pH: Not determined.
 Molecular Formula: Mixture
 Molecular Weight: Mixture
 Flash Point: 104°F (40°C)
 Flash Point Method: Tag closed cup (TCC)
 Auto Ignition Temperature: Not determined.
 VOC Content: 840 g/L
 Percent Solids by Weight 0

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.
 Hazardous Polymerization: Not reported.
 Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.
 Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11 : TOXICOLOGICAL INFORMATION**1-methoxy-2-propanol acetate :**

RTECS Number: AI8925000
 Skin: Administration onto the skin - Rabbit : >5 gm/kg [Details of toxic effects not reported other than lethal dose value]
 Ingestion: Oral - Rat LD50: 8532 mg/kg [Details of toxic effects not reported other than lethal dose value]

2-methoxy-1-propanol :

RTECS Number: UB7645000

d-Limonene :

RTECS Number: GW6360000
 Skin: Administration onto the skin - : >5 gm/kg [Details of toxic effects not reported other than lethal dose value]
 Administration onto the skin - Rabbit : >5000 mg/kg [Details of toxic effects not reported other than lethal dose value]
 Administration onto the skin - Rabbit : 10 %/24H
 Administration onto the skin - Rat : 100 %/1H
 Ingestion: Oral - Rat LD50: 4400 mg/kg [Behavioral - Changes in motor activity (specific assay) Lungs, Thorax, or Respiration - Respiratory depression Skin and Appendages - Hair]
 Oral - Mouse LD50: 5600 mg/kg [Behavioral - Changes in motor activity (specific assay) Lungs, Thorax, or Respiration - Respiratory depression Skin and Appendages - Hair]

Propylene glycol monomethyl ether :

RTECS Number: UB7700000

effects not reported other than lethal dose value]
Administration onto the skin - Rabbit : 455 mL/kg/13W (Intermittent)
[Behavioral - General anesthetic Nutritional and Gross Metabolic -
Weight loss or decreased weight gain Related to Chronic Data - death]
Administration onto the skin - Rabbit : 900 mL/kg/90D (Intermittent)
[Related to Chronic Data - death]
Administration onto the skin - Rabbit : 500 mg

Inhalation: Inhalation - Rat LC50: 10000 ppm/5H [Details of toxic effects not reported other than lethal dose value]

Ingestion: Oral - Mouse LD50: 11700 mg/kg [Behavioral - Convulsions or effect on seizure threshold Behavioral - Ataxia Lungs, Thorax, or Respiration - Dyspnea]
Oral - Rat LD50: 6600 mg/kg [Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lungs, Thorax, or Respiration - Dyspnea]

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

RCRA Number: D001

Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Refer to Bill of Lading

DOT UN Number: Refer to Bill of Lading

IATA Shipping Name: Refer to Bill of Lading

IATA UN Number: Refer to Bill of Lading

SECTION 15 : REGULATORY INFORMATION

1-methoxy-2-propanol acetate :

TSCA Inventory Status: Listed

Canada DSL: Listed

2-methoxy-1-propanol:

TSCA Inventory Status: Listed

Canada DSL: Listed

d-Limonene:

TSCA Inventory Status: Listed

Canada DSL: Listed

Propylene glycol monomethyl ether:

TSCA Inventory Status: Listed

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed

Canada DSL: Listed

Canadian Regulations. WHMIS Hazard Class(es): B3; D2B
All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:



SECTION 16 : ADDITIONAL INFORMATION

