Material Safety Data Sheet





Revision Number: 004.0 Issue date: 11/21/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Quickstix(TM) 248(TM) Threadlocker Product name:

Medium Strength

Product type: Anaerobic Sealant

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 826034

37684PR Item number: Region: **United States**

Contact information:

Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

*2 Physical state: Wax **HEALTH:** Color: FLAMMABILITY: Blue 1 Odor: Mild **PHYSICAL HAZARD:**

Personal Protection: See MSDS Section 8

MAY CAUSE ALLERGIC SKIN REACTION. WARNING:

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause allergic skin reaction. May cause skin irritation.

Eye contact: May cause irritation.

Not expected to be harmful by ingestion. Ingestion:

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	60 - 100
Thixotropic agent	Unknown	10 - 30
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Polyglycol dioctanoate	18268-70-7	1 - 5
Saccharin	81-07-2	1 - 5
Ethylene glycol	107-21-1	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
Cumene	98-82-8	0.1 - 1

IDH number: 826034 Product name: Quickstix(TM) 248(TM) Threadlocker Medium Strength Page 1 of 6

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water. If

symptoms develop and persist, get medical attention. Wash clothing before

reuse.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion: Keep individual calm. Do not induce vomiting. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: Product is a solid. Burn Rate: Greater than 7 cms (2.8 inches)

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: None

Unusual fire or explosion hazards: None

IDH number: 826034

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic

vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Ventilate area. Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

Storage: For safe storage, store at or below 38 ℃ (100.4 ℉)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Thixotropic agent	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Polyglycol dioctanoate	None	None	None	None
Saccharin	None	None	None	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
Cumene hydroperoxide	None	None	(SKIN) 1 ppm (6 mg/m3) TWA	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Wax
Color: Blue
Odor: Mild

Odor threshold: Not available. pH: Not applicable

Vapor pressure: $< 5 \text{ mm hg} (27 \text{ $\mathbb{C}} (80.6 \text{ $\mathbb{F}}))$ Boiling point/range: $> 149 \text{ $\mathbb{C}} (> 300.2 \text{ $\mathbb{F}})$ Melting point/ range:Not available.

Specific gravity: 1.1097 Vapor density: 1.097 Not available.

IDH number: 826034

Flash point: Product is a solid. Burn Rate: Greater than 7 cms (2.8 inches)

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
Not available.
Solubility in water:
Not available.
Not available.

VOC content: 2.90 %; 31.9 g/l California SCAQMD Method 316B

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 826034

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 5,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Thixotropic agent	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Polyglycol dioctanoate	No	No	No
Saccharin	No	No	No
Ethylene glycol	No	No	No
Cumene hydroperoxide	No	No	No
Cumene	No	Group 2B	No

Hazardous components	Health Effects/Target Organs		
Polyglycol dimethacrylate	Allergen, Irritant		
Thixotropic agent	No Data		
Silica, amorphous, fumed, crystal-free	Nuisance dust		
Polyglycol dioctanoate	Irritant		
Saccharin	No Target Organs		
Ethylene glycol	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic		
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen		
Cumene	Central nervous system, Irritant, Lung		

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Environmentally hazardous substances, solid, n.o.s.

Hazard class or division: 9 Identification number: UN 3077

Ш **DOT Reportable quantity:** alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, solid, n.o.s.

Hazard class or division: Identification number: UN 3077 Packing group: Ш

Water Transportation (IMO/IMDG)

Packing group:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. Proper shipping name:

Hazard class or division:

Identification number: UN 3077 Packing group: Ш

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 826034

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 9 and 16

Prepared by: Diane Annis, Sr. Regulatory Affairs Specialist

Product name: Quickstix(TM) 248(TM) Threadlocker Medium Strength

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 826034