

Bevco Built-In Values

- Meets ANSI/BIFMA* standards
- Passes California fire code 117
- Proven Bevco quality
- 12-year guarantee

BEVCO°

5000 Series

Outstanding Ergonomic Value



5000 Series from Bevco

The 5000 Series is BEVCO'S best in ergonomic industrial seating for the toughest workplace environment. Made in America, these durable "intensive use" chairs offer ergonomic features that improve productivity while reducing worker injury and fatigue.

Each model features heavy-duty construction, comfortable seat with waterfall edge, resilient high density foam, easy-to-use pneumatic seat height adjustment, 360 degree swivel, a fully adjustable back and sturdy five legged base with mushroom glides. Casters are optional. Models 5001, 5201, 5301,5501, and 5601 also come standard with an articulating seat and back tilt control for maximum ergonomic benefit.



Models 5000, 5300, 5301, 5001, 5500, and 5501 feature a five star reinforced plastic base. The 5500 and 5501 come standard with a 10" pneumatic cylinder and 18" diameter adjustable chrome footring. Models 5200,5201, 5600 and 5601 feature a black painted, tubular steel base with sturdy 19" diameter welded chrome footring.

BEVCO's reputation for outstanding value in ergonomic seating is backed by 50 years of manufacturing. All products carry BEVCO's superior "intensive use" guarantee. It's not prorated, applies to a 24 hour day, and covers defects in material and workmanship for a full 12 years!**

- ANSI: American National Standards Institute, Inc. BIFMA: Business and Institutional Furniture Manufacturers Association. ANSI/BIFMA standards include safety, durability and structural adequacy evaluations.
- ** Pneumatic cylinders have a lifetime guarantee in the chair originally installed.

•

Important Standard Features – All Models

- Sturdy five legged base with mushroom glides •
- Easy-to-use pneumatic seat height adjustment with "lifetime" cylinder quarantee
- Ergonomic waterfall seat for improved circulation
- Contoured back with durable scuff resistant back pan

<u>5200, 5201, 5600, 5601</u>

- Heavy 16 gauge tubular steel base with top grade, scratch resistant, baked enamel finish
- 19" welded chrome footring to reduce pressure on thighs and promote better circulation
- Optional rubber cushioned metal glides for long wear on cement floors (Reduces seat height range by 1-1/2")

<u>Upholstery</u>

- BIFMA Class 1 rated Olefin fabric resists fading, pilling, punctures and moisture
- Meets flame retardant standards of California Technical **Bulletin 117**
- Standard colors are black, gray, burgundy, royal blue, medium blue, navy or green
- Optional all vinyl upholstery in black or blue

Additional Options

- Dual wheel hard floor, carpet or interval braking casters
- "02" Control with separate levers for seat and back tilt. (Specify model with "02" option, ie: 5502)
- Additional lumbar back support (LBS)
- Ergonomic adjustable armrests with polyurethane armpads.
- Larger 20" diameter adjustable chrome footring for models 5300, 5301,5500 and 5501
- Larger ergonomic seat (20"W, 18"D, 3" Thick)
- Larger ergonomic seat available on models with reinforced plastic base.
- Larger backrest (17 1/2"W, 19"H, 4" Thick)
- **Customized options available**

| | Height Adjustment | Height Adj. W/Casters | Vertical Back Adj. | Horizontal Back Adj. | Tilt | | | Base | Weight |
|-------|----------------------|--------------------------|-----------------------|-------------------------|---------------------------|----------------------------|----------------------|---------------------------|--------|
| Model | | | | | Seat | Back | Footring | Туре | (lbs.) |
| 5000 | 17" - 22" | 18" - 23" | 3" Range | 1½" Range | - | - | No | Reinforced Plastic | 23 |
| 5001 | 17" - 22" | 18" - 23" | 6" Range | Tilt | 6° Rearward 5° Forward | 20° Inward 21° Backward | No | Reinforced Plastic | 27 |
| 5200 | 20" - 25" | 21" - 26" | 3" Range | 1½" Range | - | - | Welded Chrome | 16 Gauge Tubular Steel | 26 |
| 5201 | 20" - 25" | 21" - 26" | 6" Range | Tilt | 6° Rearward 5° Forward | 20° Inward 21° Backward | Welded Chrome | 16 Gauge Tubular Steel | 30 |
| 5300 | 20½" - 28" | 21½" - 29" | 3" Range | 1½" Range | - | - | Adjustable Chrome | Reinforced Plastic | 30 |
| 5301 | 20½" - 28" | 21½" - 29" | 6" Range | Tilt | 6° Rearward 5° Forward | 20° Inward 21° Backward | Adjustable Chrome | Reinforced Plastic | 32 |
| 5500 | 23" - 33" | 24" - 34" | 3" Range | 1½" Range | - | - | Adjustable Chrome | Reinforced Plastic | 28 |
| 5501 | 23" - 33" | 24" - 34" | 6" Range | Tilt | 6° Rearward 5° Forward | 20° Inward 21° Backward | Adjustable Chrome | Reinforced Plastic | 32 |
| 5600 | 25" - 30" | 26" - 31" | 3" Range | 1½" Range | - | - | Welded Chrome | 16 Gauge Tubular Steel | 27 |
| 5601 | 25" - 30" | 26" - 31" | 6" Range | Tilt | 6° Rearward 5° Forward | 20° Inward 21° Backward | Welded Chrome | 16 Gauge Tubular Steel | 31 |



Model 5001

EV/EO

Standard Dimensions: Seat: 18"W x 17"D x 2-3/4" Thick. Back: 16"W x 10"H x 2" Thick. Seat Foam Density: 2..5 lb., 55 IFD.