
Product: SDPU
Dissipative Soft
Typical Physical Properties

Physical Property	Value	Test Method
Color	Black	
Density (lbs / ft ³)	1.7-1.9	ASTM D-3574-01
Indent Force Deflection@25%	45-55	ASTM D-3574-01
Surface Resistivity(Ohms/sq)	10 ⁷ - 10 ¹⁰	ASTM D257
Ohms (point to point)	10 ⁷ - 10 ¹⁰	
Volume Resistance(Ohm-CM)	10 ⁷ - 10 ¹⁰	ASTM D257
Static Decay Time(in seconds)	.01 max	
Flame Resistance	NA	

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, CCI does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

3/7/07

www.corstat.com

WARNING: URETHANE FOAM IS FLAMMABLE!
*Urethane Foam should not be exposed to open flame or other ignition sources.
Urethanes burn rapidly with great heat and release gases which are extremely hazardous.*

Distributed by:
All-Spec Industries
Wilmington, NC

Ph: 800-537-0351
Fx: 800-379-9903

Web: www.all-spec.com
Email: sales@all-spec.com