

Technical Specifications

Connectors

MICROMAPPER main unit: RJ45 jack

Remote Identifier: RJ 45 jack

Pairs tested

1-2, 3-6, 4-5, 7-8, and shield

LED Display

Horizontal: 5 green LEDs for pairs and shield display
(1 - 2, 3 - 6, 4 - 5, 7 - 8, and SHIELD)

Vertical: 6 red LEDs (TONER, SHORT, REVERSED, MISWIRE, SPLIT PAIRS, and LOW BATTERY)

Cables test limit

Minimum: 15.75" (40cm); Maximum: 656' (200 m)

Power

IEC 86-1 (1996-07) --- Primary Batteries - General

IEC 60086-2 (1997-07) --- Primary Batteries - Specification Sheets

MICROMAPPER: requires four 1.5 AAA batteries. IEC : LR03; Others : AAA, E92, 4003; JIS : AM 4 ; ANSI : 24A; 1.5 Volt (nominal)

Remote Identifier: No battery required

Dimensions

MICROMAPPER: 4.92" x 2.05" x 1.54" 1
125 mm x 52 mm x 39 mm

Remote Identifier: 1.87" x 1.12" x 0.87"
47mm x 28mm x 22mm

Weight

MICROMAPPER with Remote Identifier: 125 g

Distributed by: **All-Spec Industries**

5228 US Hwy 421 N
Wilmington, NC 28401

www.all-spec.com
sales@all-spec.com

PH: 800-537-0351
FX: 800-379-9903