

Security.

MetroMax Q Security Units 14.01

Protects valuable materials and sensitive items from loss or pilferage.

- Ready view of contents: Heavy gauge open wire construction keep contents visible at all times, making it easy to check inventory.
- Microban antimicrobial product protection is built into the enclosures, doors, handles, and shelves to keep the product "cleaner between cleanings."
- Optional intermediate shelves: MetroMax Q quick adjust shelves or corrosion proof MetroMax i.
- Double door with ergonomic ¼-turn handle: Each door opens 270 degrees and can be secured along the sides of the unit.
- Shipped knocked down to save on freight costs. Assembles in minutes.



MQSEC53VE with optional intermediate shelves

MetroMax Q Stationary Units– 66-3/16" (1681mm) High

Actual Outside Dimensions
(Including Handle)

	Width		Length		Fits Shelf		Approx. Pkd. Wt.		Cat. No.
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	
26-15/16	685	685	38-7/8	987	24x36	610x914	148	67	MQSEC53E
26-15/16	685	685	50-7/8	1292	24x48	610x1219	156	71	MQSEC55E
26-15/16	685	685	62-7/8	1597	24x60	610x1524	161	73	MQSEC56E

Note: Leveling foot on post can be adjusted up to 1" (25mm) to compensate for uneven floors.

MetroMax Q Stem Caster Mobile Units– 67-13/16" (1723mm) High

Actual Outside Dimensions
(Including Bumpers and Handle)

	Width		Length		Fits Shelf		Approx. Pkd. Wt.		Includes (4) 5"	Includes (4) 5"
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	(127mm) Diameter Swivel Casters Cat. No.	(127mm) Diameter Swivel Casters Cat. No.
27-13/16	707	707	40-3/4	1035	24x36	610x914	166	75	MQSEC53DE	MQSEC53VE
27-13/16	707	707	52-3/4	1340	24x48	610x1219	176	80	MQSEC55DE	MQSEC55VE
27-13/16	707	707	64-3/4	1645	24x60	610x1524	179	81	MQSEC56DE	MQSEC56VE

Note: DE models use four 5MP casters.

Note: VE models use two 5PCX and two 5PCBX casters.

MetroMax Q Heavy-Duty Mobile Units– 68-1/2" (1740mm) High

Mounted on an aluminum dolly with 5" (127mm) plate casters and wraparound bumpers.

Actual Outside Dimensions
(Including Handle)

	Width		Length		Fits Shelf		Approx. Pkd. Wt.		Cat. No.
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	
28-1/16	713	713	39-1/8	994	24x36	610x914	166	75	MQSEC53LE
28-1/16	713	713	51-1/8	1299	24x48	610x1219	176	80	MQSEC55LE
28-1/16	713	713	63-1/8	1603	24x60	610x1524	179	81	MQSEC56LE

Note: The aluminum dollies used on the LE models have two B5P and two B5PB plate casters.



Ergonomic–
1/4 turn door handle

Intermediate Shelves

	Width		Length		i	i	Q
	(in)	(mm)	(in)	(mm)	Shelf with Grid Mat Cat. No.	Shelf with Solid Mat Cat. No.	Shelf with Grid Mat Cat. No.
24	610	610	36	914	MX2436G	MX2436F	MQ2436G
24	610	610	48	1220	MX2448G	MX2448F	MQ2448G
24	610	610	60	1524	MX2460G	MX2460F	MQ2460G

Distributed by:
All-Spec Industries
www.all-spec.com
sales@all-spec.com
PH: 800-537-0351
FX: 800-379-9903