



Ecoheat® Heat Gun & Heat Gun Kit

Economical, lightweight, multi-use heat gun



- Two heat settings: 500°F or 1000°F (260°C or 538°C)
- Two fan speeds - Low & High (7 or 9 CFM)
- Resettable thermostat - Automatically protects element against overheating
- Lightweight - 1 lb. - Easy to hold at any angle for long periods of time, eliminates operator fatigue
- Built-in hand guard - Protects hand and fingers. Recessed switch guards against knocks and bumps
- 3-wire grounded cord set, a positive grounding system for user safety
- Thermoplastic housing - for high impact durability
- Built-in Stand - Very stable, allows user to set heat gun down in an upright position for hands free use
- Use to bend and form plastics, dry body fillers, remove decals, spot dry paint, shrink tubing, packaging and more

MODEL NO.	DESCRIPTION
EC-100	500°F or 1000°F 260°C or 538°C 7 or 9 CFM 120V 50/60 Hz 10A 656 or 1200W 
EC-100K	500°F or 1000°F 260°C or 538°C 7 or 9 CFM 120V 50/60 Hz 10A 656 or 1200W  Kit consists of EC-100 Heat Gun, 7/8" reducer attachment, 1-1/4" shrink tubing reflector, 1-15/16" and 3-1/8" spreader attachments packed in a durable storage & carrying case
35225	Attachment kit contains 7/8" reducer attachment, 1-1/4" shrink tubing reflector, 1-15/16" and 3-1/8" spreader attachments
35215	Durable storage & carrying case



Kit includes storage case and four specialized nozzle attachments shown left to right: 7/8" reducer, shrink tubing reflector, 1-15/16" spreader and 3-1/8" spreader

Specifications

- Air Volume: 7 and 9 CFM
- Air Velocity: 720 and 1100 FPM
- Motor: Permanent Magnet
- Nozzle Opening: 1.2" I.D., 1.35" O.D.
- Cordset: 6 ft., 3-wire grounded
- Dimensions: 8.5" L x 3.2" W x 7.7" H
- Tool Net Weight: 2 lbs.
- Shipping Weight Tool: 3 lbs.
- Shipping Weight Kit: 5 lbs.

NOTE: Users should independently evaluate the suitability of the product for their application.