

High visibility gloves – protection that you can see



FEATURES AND BENEFITS:

Visibility in Low Light

Bright orange color allows hands to be visible in low light situations and at greater distances, resulting in increased safety conditions for a variety of work environments.

Chemical Splash Resistance

Resists a variety of industrial chemicals for longer periods than other nitrile disposable gloves.

Wrist and Forearm Protection

Extended cuff offers an increased level of protection in an exam grade glove in the highly sensitive wrist and forearm areas.

Secure and Confident Grip

Textured fingers ensure a strong grip and maximum worker protection.

Protection from Type 1 Allergies

Powder-free and not made with natural rubber latex, to help protect from Type 1 skin allergies, skin irritation and dryness.

Industries

- Chemical
- Fire Safety
- Food Processing
- Healthcare
- Laboratory
- Manufacturing
- Mining
- Printing

Applications

- Assembly and inspection
- Crime scene analysis
- Emergency services
- Exploration, drilling & blasting
- Laboratory analysis and testing
- Maintaining equipment & instruments
- Maintenance & clean-up
- Paint and spray shops
- Patient examination
- Protection from blood and other bodily fluids
- Re-fueling
- Warehousing

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	BLAZE®
Material	Nitrile
Color	High Visibility Orange
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	US QSR/FDA 510(K), US NFPA
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XL	ASTM D3767/EN 420
Length (mm)	270	270	270	270	270	
Average Palm Width (mm)	85	95	105	115	125	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.13) / (mil : 5.1)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	33 Mpa		37 Mpa			ASTM D 412-06a
Elongation at Break (%)	> 500		> 400			ASTM D 412-06a
Force at break (N)	16		17			EN 455-2

ORDERING INFORMATION:

	SIZE	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XL
BLAZE®	REORDER NO.	N481	N482	N483	N484	N485

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell (Hong Kong) Limited
Unit 3102-3103, 31/F
Manhattan Place
23 Wang Tai Road
Kowloon Bay, Hong Kong
+852 2185 0600
+852 2856 2155

North America
Ansell Protective Products Inc.
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

