

Provides sturdy coverage
for demanding applications



Nitrile



Multi-Purpose



FEATURES AND BENEFITS:

Exceptional Protection

The Microflex Supreno® SE offers an advanced barrier protection against contaminants due to its lower acceptable pinhole rates. Its 0.65 Acceptance Quality Limit for pinholes help set a new standard for protection.

Increased Productivity

Non-stick properties are built into the glove formulation to create a resistance to tape or adhesives, and to assist workers with improved efficiency and speed.

Secure and Confident Grip

Textured fingers ensure strong, efficient grip and maximum worker protection.

Effortless Donning and Doffing

Polymer coating assures easy donning to help protect workers in fast-paced environments.

Protection from Type 1 Allergies

Constructed without natural rubber latex materials or powder, to help protect from allergies, skin irritation and dryness.

Industries

- Automotive
- Chemical
- Healthcare
- Laboratory
- Law Enforcement
- Manufacturing

Applications

- Crime scene evaluation
- Patient examinations
- Analytical testing
- Assembly and inspection
- Electronics
- Food processing
- Glass manufacturing
- Laboratory analysis and testing
- Light assembly tasks
- Maintaining equipment & instruments
- Paint and spray shops
- Patient examinations
- Pharmaceutical manufacturing
- Preparing pharmaceutical products
- Printing industry
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	SUPRENO® SE
Material	Nitrile
Color	Blue
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Polymer Coated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	MDD 93/42/EEC, PPED 89/686/EEC CATEGORY III, COMPLEX DESIGN, EN 455 1,2 AND 3, EN374-3, EN374-2 LEVEL 3 AQL .65, ASTM D6319, EN420 (SIZING FOR SPECIAL PURPOSES), REACH COMPLIANT, TGA, US QSR/FDA 510(K)
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	
Length (mm)	245	245	245	245	245	ASTM D3767/EN 420
Average Palm Width (mm)	75	86	98	108	115	
Freedom from Holes (Inspection level I)	0.65 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.11) / (mil : 4.3)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	30 Mpa		30 Mpa		ASTM D 412-06a	
Elongation at Break (%)	> 500		> 400		ASTM D 412-06a	
Force at break (N)	10		11		EN 455-2	

ORDERING INFORMATION:

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
SUPRENO® SE	REORDER NO.	SU-690-XS	SU-690-S	SU-690-M	SU-690-L	SU-690-XL

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell (Hong Kong) Limited
Unit 3102-3103, 31/F
Manhattan Place
23 Wang Tai Road
Kowloon Bay, Hong Kong
+852 2185 0600
+852 2856 2155

North America
Ansell Protective Products Inc.
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16



EN 374

EN 374

