

# Super Lube®



## SUPER LUBE® GREASE

**SUPER LUBE® MULTI-PURPOSE GREASE**

**Super Lube® Grease** is a patented synthetic NLGI grade 2 heavy-duty, multipurpose lubricant with PTFE. Synthetic base fluids and the addition of PTFE micro powders combine to form a premium lubricant that provides longer life protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

**Super Lube® Grease** is a USDA listed Food Grade lubricant, rated H-1 for incidental food contact.

**Super Lube® Grease** will not run or drip, does not evaporate or form gummy deposits and will not melt or separate.

**Super Lube® Grease** is a synthetic, heavy-duty lubricant that is compatible with most other lubricants.


**Super Lube® Grease** outlasts conventional greases 50-100% and has excellent adhesion.



### NLGI Grade 2:

#### Part No. Description

21006	6 cc Syringe
21010	½ oz Tube
21030	3 oz Tube
21036	3 oz Cartridge
41150	400 gr Cartridge
41160	400 gr Jar
41050	5 lb Pail
41030	30 lb Pail
41120	120 lb Keg
41140	400 lb Drum
82340	1 cc Packet



### Also available in NLGI-1, 0, 00 or 000

#### Part No. Part No. Part No. Part

41150/1		41150/0	
	41150/00	41150/000	
41050/1		41050/0	
	41050/00	41050/000	
41030/1		41030/0	
	41030/00	41030/000	
41120/1		41120/0	
	41120/00	41120/000	
41140/1		41140/0	
	41140/00	41140/000	

Synco Chemical Corporation - Super Lube®  
24 Da Vinci Drive, Bohemia, NY 11716  
Tel: (631) 567-5300 / Fax: (631) 567-5399  
Email: [info@super-lube.com](mailto:info@super-lube.com) / [www.super-lube.com](http://www.super-lube.com)

June 26, 2003 / Copyright ©





## SUPER LUBE® GREASE

SUPER LUBE® GREASE

### **Super Lube® Grease** **Typical Applications:**

- ▶ Plain, anti-friction, ball, roller, wheel bearings
- ▶ Cams, slides, valves, conveyors, chains
- ▶ Food processing equipment
- ▶ Caliper assembly and bearing grease
- ▶ Hubs, axles, chassis, shocks, springs
- ▶ Seat regulators and tracks
- ▶ Fifth wheels
- ▶ Parts lubricant
- ▶ Winches, pulleys, snaps
- ▶ Trailer and buddy bearings
- ▶ Dielectric grease, battery protector
- ▶ Campers, trailers, bicycles, guns, fishing gear, motorcycles, hunting gear
- ▶ Weight and fitness equipment

- ▶ Linkages, hinges and locks
- ▶ Lawn movers, garage doors, snow blowers, sewing machines
- ▶ Faucets and pool pumps
- ▶ Garden and farm equipment

### **Benefits:**

- ▶ Clean, non-toxic, non-staining
- ▶ Dielectric
- ▶ USDA Rating H-1
- ▶ Will not drip, run or evaporate
- ▶ Impervious to salt water, safe in potable water
- ▶ Long lasting
- ▶ Prevents rust and corrosion while reducing friction
- ▶ Wide Temperature Range -45° to 450 °F



Synco Chemical Corporation - Super Lube®  
24 DaVinci Drive, Bohemia, NY 11716  
Tel: (631) 567-5300 / Fax: (631) 567-5359  
Email: [info@super-lube.com](mailto:info@super-lube.com) / [www.super-lube.com](http://www.super-lube.com)



**Super  
Lube®**



## SUPER LUBE® GREASE

---

**SUPER LUBE® GREASE**

Typical Properties		
Test	Test Method	Rating
Color		Translucent White
NLGI Grade	ASTM D217	2
Dropping Point	ASTM D566	>500°F (260°C)
<b>Four Ball test:</b>	ASTM D2783	
Load wear index		81.73 kg
Weld Point		400 kg
Oxidation Stability 100 hrs	ASTM D942	0 psi
Wheel bearing Leakage	ASTM D1263	0.2 g
Copper Corrosion 24 hrs @ 100°C	ASTM D4048	1B, shiny
Warranty		24 months

While the information contained herein is believed to be reliable, Synco Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.



Synco Chemical Corporation - Super Lube®  
24 DaVinci Drive, Bohemia, NY 11716  
Tel: (631) 567-5300 / Fax: (631) 567-5359  
Email: [info@super-lube.com](mailto:info@super-lube.com) / [www.super-lube.com](http://www.super-lube.com)

