

shield

Static Dissipative Products

STATIC DISSIPATIVE FLOOR CLEANER FC-4500

Safety Information

Product contains a low odor, safe solvent and surfactant system.

See full safety data sheet.

Does not contain:

Formaldehyde	CAS #	50-00-0
Dibutyl Phthalate	CAS #	87-74-2
Free Ammonia		None
Free Alkali		None
Free acid		None
Phosphates		None
Abrasives		None

Health	1
Flammability	0
Reactivity	0
Personal Protection	B



Directions

INITIAL APPLICATION - Read full product information sheet.

1. Before application, dry mop area to be cleaned.
2. Dilute FC-4500 10 parts water 1 part FC-4500
3. Thoroughly mix the concentrate. Use rayon mop. Do not flood rinse the floor. Wring out excess cleaner. Allow floor to dry.
4. Check the resistivity. If needed apply 2 coats of AF-5500 Floor Finish or AF-6000.
5. Allow to dry for 1 hour before walking on floor.
6. Do not damp mop with plain water, high alkaline or high residue cleaners. This will damage a floors' static dissipative properties.
7. Heavy to moderate traffic areas should be cleaned once a week.
8. Light traffic areas should be cleaned 2-3 times a month.
9. Cleaning of black marks can be easily removed with a hand-pad mop.
10. Apply 1-2 Coats AF-5500 or AF-6000 Floor Finish as needed.
11. Dry mop daily.

Warranty: Static Solutions, Inc. expressly warrants that for a period of (1) one year from the date of purchase any Static Solutions, Inc. product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions, Inc.'s option with no cost to the customer as long as Static Solutions, Inc. receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions, Inc.'s customer service at 800-450-0700 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly disclaimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions, Inc. or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on tort, contract, or the use of or inability to use, the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions, Inc.'s warranty obligations will be the customer's exclusive remedy and Static Solutions, Inc. and seller's limit of liability for any breach of warranty or otherwise.

DISTRIBUTED BY:

All-Spec Industries

www.all-spec.com

sales@all-spec.com

PH: 800-537-0351

FX: 800-379-9903

Specifications

Active Ingredients:	Proprietary Static Dissipative compounds	
Surface Resistance (RTT)	10 ⁹ -10 ⁹	OHM @ 100 volts
Electrostatic Decay Time	EIA 541	0.1 Seconds
% Solids	25	
pH	6.5 - 7.5	
Color	Yellow	
Odor	Mild Lemon	
Solubility in Water	100%	
Freeze/Thaw Stability	Minimum 3 cycles	
Shelf Life	1 year	
Flash Point	None	
Weight Per Gallon	8.5 lbs./gallon	
Biodegradable	Yes	
Soil Suspension	Very good	

For additional OHM-SHIELD product literature, call or fax the Static Solutions, Inc. sales department.

Static Solutions, Inc.

Ohm-Shield is a trademark of Static Solutions, Inc. ©1998 Static Solutions, Inc.
All specifications subject to change without notice. Printed in USA 12/98