



E-Line IPA

1610 Aerosol

99.8% pure anhydrous (containing the least water possible and no denaturant) isopropyl alcohol is excellent for tape head cleaning, defluxing, stencil cleaning, other light cleaning, and as a flux thinner. Avoid "bargain" alcohols for critical electronic cleaning. Cheap alcohols contain much more water, which slows drying and can cause oxidation, while "denatured" alcohols leave residues.



99.8% IPA in convenient aerosol package

Introducing E-LINE IPA – Isopropyl Alcohol (IPA) in new, convenient aerosol packaging. 99.8% pure anhydrous (minimal water) IPA is excellent for defluxing, fiber optics maintenance, stencil cleaning, tool cleaning, tape-head cleaning and other light-duty cleaning.

- 99.8% pure IPA
- Ideal for defluxing, stencil cleaning & fiber optics
- Plastic safe
- Low toxicity
- Non-ozone depleting
- Compliant with SCAQMD rule 1171

Product Packaging

1610-12S
E-Line IPA
12 oz
12 units/case



Instructions

Make sure opening of sprayhead is pointing toward surface to be cleaned. Hold can 15-20 cm away. Direct spray to saturate soiled surface. A TechBrush® (2000 Series) may be utilized to help in the removal of heavy soils. When used as a general cleaner, start at top of area to be cleaned using a sweeping motion, and spray the area slowly, working towards the bottom. To clean in hard to reach areas, insert extension tube in sprayhead to direct spray. Allow components to dry completely before applying current. For flat surface cleaning, saturate a lint-free TechClean® Twillwipe (2357) or Purwipe™ (2355) and wipe surface with cloth. Rotate the cleaning side of the wipe periodically and re-saturate.

Chemical & Physical Properties

Appearance	Clear, colorless liquid
Odor	Alcohol odor



Techspray - US office, P.O. Box 949,
Amarillo, TX 79105-0949,
Tel. 806-372-8523, Toll-free 800-858-4043
Fax 806-372-8750, tsales@techspray.com

Distributed by: All-Spec Industries
PH: 800-537-0351 sales@all-spec.com
FX: 800-379-9903 www.all-spec.com



Flash Point	11.7°C (53°F) TAG CC
VOC (EPA)	75%
VOC (CARB)	75%
Boiling Point	82°C (180°F)
Density	

Chemical Composition

CHEMICAL NAME	CAS #
2-Propanol	67-63-0

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe

ITW Contamination Control BV
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Techspray - US office, P.O. Box 949,
Amarillo, TX 79105-0949,
Tel. 806-372-8523, Toll-free 800-858-4043
Fax 806-372-8750, tsales@techspray.com

Distributed by: All-Spec Industries
PH: 800-537-0351 sales@all-spec.com
FX: 800-379-9903 www.all-spec.com