

Nitrile Powder-Free 12" Glove

Part Number: VTGNPFB12

Part of the

 MicroTek
 product family



Description: Glove Powder-Free Nitrile White, Ambidextrous Shape, Beaded Cuff, Finger tip textured, 12" Length. Good ESD attributes, Lot Control Quality Tested

Application: Nitrile gloves offer improved fit and performance over other materials. Consistent quality and performance. Good ESD characteristics for electronic applications. Commonly used as the preferred glove in semiconductor and pharmaceutical applications. Standard cuff length for less critical applications. Class 100 & above.

Test Methods: Product conforms to the following test standards:

IES-RP-CC-005	Recommended Practice for Cleanroom Gloves
ASTM D3578	Standard Specifications for Rubber Examination Gloves
ASTM D412	Tensile Properties of Vulcanized Rubbers
ASTM D573	Accelerated Aging for Latex (at 70°C for 166 hr.)
ASTM D5151	Standard Test for Detection of Holes in Medical Gloves

Quality Sampling Plan: MIL-STD-105E, Inspection Levels S-2, and S-4

Parameter AQL	Inspection	Level
Watertight	1.5	S-4
Dimensions	2.5	S-2
Physical Properties	2.5	S-2
Visual Defects		S-4
Major 1.5		
Minor 2.5		

Visual Defects: AQL 1.5 Major - Tears, visible holes, sticking pleats (> 10mm), embedded particles (> 5mm), large lumps, non-removable dirt, torn beads/cuffs, excessively thin spots, tackiness, wrong size.

Description: AQL 2.5 Minor - Stains and discoloration, sticking pleats (< 10mm), embedded particles (< 5mm), small lumps, loose dirt, or defective beads.



USA/Canada
 Valutek
 1005 N 50th St
 Phoenix, AZ 85008
 p 602.256.0540
 f 602.252.1972
 info@valutek.com

Latin America
 Valutek Latin America
 S.A. de C.V.
 Avenida de la Raza 5385
 Loc. 205
 Col. Los Nogales chihuahua
 Cd. Juarez, Chihuahua 3235
 latam@valutek.com

Asia
 Valutek Asia Sdn. Bhd.
 5029 Jalan Raja Uda
 12300 Butterworth,
 Palau Pinang, Malaysia
 p 604.310.6111/113/110
 f 604.310.6112
 asia@valutek.com

Nitrile Powder-Free 12" Glove

Part Number: VTGNPFB12

Part of the

 MicroTek
 product family

Dimensions and Tolerances :

Dimensions Parameter	Size Small	Medium	Large	X-Large	Tolerance mm
Width (mm)	85	95	105	115	+/- 5
Length (mm)	240 min. for all sizes				

Minimum Thickness	(mm)	(mils)
Finger	0.10- 0.20	3.44-7.87
Palm	0.10 - 0.15	3.94-5.91
Cuff	0.08 0.12	3.15-4.72

Weight*	5.3	5.7	6.2	7.1
---------	-----	-----	-----	-----

*Average weight based on standard shipping ratios not to exceed 6.5 grams.

Physical Properties:

Before Aging		After Aging	
Tensile Strength	Ultimate Elongation	Tensile Strength	Ultimate Elongation
14 MPa min.	500% min.	14 MPa min.	400% min.
ESD Specification @ 50-60% Humidity			

Physical Characteristics:

Particle Counts: Current Particle data available on request.
 Extractables: Current Extractable data available on request.
 Chemical Compatibility: Contact Manufacturer for Chemical
 Compatibility information.

Packaging and Markings:

Bagged - 100 pieces per bag, which are unidirectional
 packed & labeled with size, lot/batch
 number, product description, and country of origin. 10
 bags per carton

Shelf Life and Storage:

All product delivered will have a minimum shelf life of 12
 months. All product is stored and shipped
 in an environment appropriate for the materials, and the
 use.



USA/Canada
 Valutek
 1005 N 50th St
 Phoenix, AZ 85008
 p 602.256.0540
 f 602.252.1972
 info@valutek.com

Latin America
 Valutek Latin America
 S.A. de C.V.
 Avenida de la Raza 5385
 Loc. 205
 Col. Los Nogales chihuahua
 Cd. Juarez, Chihuahua 3235
 latam@valutek.com

Asia
 Valutek Asia Sdn. Bhd.
 5029 Jalan Raja Uda
 12300 Butterworth,
 Palau Pinang, Malaysia
 p 604.310.6111/113/110
 f 604.310.6112
 asia@valutek.com