

# The Diamond-Plate Family





## **Performance: ULTIMATE**

If you want to be a hero to your employees, buy **UltraSoft Diamond-Plate!**It provides **unparalleled comfort**, resulting in enhanced employee productivity and morale. UltraSoft's long-term performance and exceptional feel are due to its double-thick Nitricell® Sponge base. Nitricell® is a unique composite loaded with Nitrile rubber for exceptional rebound and resilience. Designed for heavy-use areas, the popular, high-tech diamond-plate surface resists abrasion and most chemical spills, and is available with colored borders for maximum safety awareness. All edges are safety beveled.

## **Performance: BEST**


**Diamond-Plate SpongeCote** is the **original Diamond-Plate** anti-fatigue mat and definitely sets the standard for comfort in the industry. It is, without a doubt, one of the most popular anti-fatigue mats on the market today because it offers the complete package of comfort, enhanced productivity, long-term performance and an industrial image. It is identical to UltraSoft Diamond-Plate with one exception. Its Nitricell® Sponge base is a standard 3/8" thick.




As an added bonus, both versions can be customized in virtually any width or dimension to fit even the most unique work area.





#### UltraSoft Diamond-Plate No. 414





## Diamond-Plate SpongeCote® No. 415







No. 414 No. 415

| Stock Sizes                       | 15/16" Thick | Non-Stock Sizes   |               | Stock Sizes   | 9/16" Thick | Non-Stock Sizes               |          |
|-----------------------------------|--------------|-------------------|---------------|---|-------------|-------------------------------|----------|
| Part Number                       | Size         | Part Number       | Size          | Part Number   | Size        | Part Number                   | Size     |
| 414.1516x2x3                      | 2' x 3'      | 414.1516x2x75     | 2' x 75'      | 415.916x2x3   | 2' x 3'     | 415.916x2x75                  | 2' x 75' |
| 414.1516x3x5                      | 3' x 5'      | 414.1516x3x75     | 3' x 75'      | 415.916x3x5   | 3' x 5'     | 415.916x3x75                  | 3' x 75' |
|                                   |              | 414.1516x4x75     | 4' x 75'      |   |             | 415.916x4x75                  | 4' x 75' |
|                                   |              | 414.1516x5x75     | 5' x 75'      |   |             | 415.916x5x75                  | 5' x 75' |
|                                   |              | 414.1516x6x75     | 6' x 75'      |   |             | 415.916x6x75                  | 6' x 75' |
|                                   |              | Cut Sizes up to 7 | 75′ in length |   |             |                               |          |
| Note: 5' and 6' widths are seamed |              | 414.1516x2Cut     | 2' Cut        | <b>Note:</b> 5' and 6' widths are seamed<br>and only available in<br>Black or Black/Yellow. |             | Cut Sizes up to 75' in length |          |
| and only available in             |              | 414.1516x3Cut     | 3' Cut        |   |             | 415.916x2Cut                  | 2' Cut   |
| Black or Black/Yellow.            |              | 414.1516x4Cut     | 4' Cut        |   |             | 415.916x3Cut                  | 3' Cut   |
|                                   |              | 414.1516x5Cut     | 5' Cut        |   |             | 415.916x4Cut                  | 4' Cut   |
|                                   |              | 414.1516x6Cut     | 6' Cut        |   |             | 415.916x5Cut                  | 5' Cut   |
|                                   |              |                   |               |   |             | 415.916x6Cut                  | 6' Cut   |

Specify Color: Black (BK), Gray (GY), Black/Yellow (BYL), Black/Chevron (CHV) when ordering.

## Specs Uses Compound Compression **Coefficient of Friction Tabor Abrasion**

**Flammability** 

**UltraSoft** 

All dry work areas

Vinyl surface with a double thick Nitricell® sponge base .50 inche @ 35 psi per ASTM D575

.68 Dry per ASTM F1677 1% lost @ 1,000 cycles per Fed Std. 191 "A" Rating per MVSS 302 Safety beveled Approx. 15/16"

### **Standard**

All dry work areas Vinyl surface with a Nitricell® sponge base

.415 inche @ 35 psi per ASTM D575 .68 Dry per ASTM F1677

1% lost @ 1,000 cycles per Fed Std. 191 "A" Rating per MVSS 302 Safety beveled Approx. 9/16"



**Edges** 

**Thickness** 

## All Diamond-Plate mats can be Customized!

In fact, we frequently make Diamond-Plate SpongeCote® No. 415, UltraSoft Diamond-Plate No. 414 and now, Diamond-Plate with GritWorks!® No. 416, in custom lengths, widths and unique configurations. If you have a "U" or "L" shaped work area we can make a mat to fit it. If your space requires a circular, oval or triangle mat, simply give us a template. And if you have cut-outs in odd places, we can accommodate that too. Basically the **sky is the limit** when it comes to customizing Diamond-Plate.

Some mats may require two or more sections depending on size, weight and shipping requirements. Square edges are also available. Please call for pricing.



Distributed by:

**All-Spec Industries** 5228 US Hwy 421 N Wilmington, NC 28401

www.all-spec.com sales@all-spec.com

PH: 800-537-0351 FX: 800-379-9903