

## **Technical Data Sheet**

## **Static Dissipative Papers**

**All-Spec** ESD paper is a <u>permanently static dissipative</u> paper product with low sensitivity to changes in relative humidity and almost free in component critical contaminants, (i.e. low amine, chloride and sodium). The paper has a hard surface, is printable with no bleeding, and virtually lint free. Available in single sheets, continuous forms, or machine roll and can be supplied blank or preprinted.

**All-Spec** Static Dissipative Papers exhibit superior physical properties compared to regular paper.

High fold resistance High tensile strength

High burst strength High moisture and solvent resistance

Cleanroom Class 10,000 compatible

Two thickness (calipers) offered: 0.0038"and 0.0080"

Typical Test Data - Physical:

Base weight (3000 sq. ft.) 20# 40#

**Thickness** 0.0080" (0.2mm)

0.0038" (0.097mm) 2.9x10<sup>10</sup>  $7.0x10^9$ Resistivity (@ 15% RH at 10 Volts AP) 2.2x10<sup>10</sup>  $3.0x10^9$ Resistivity (@ 15% RH at 100 Volts AP) 2.7x10<sup>8</sup> Resistivity (@ 50% RH at 10 Volts AP) 5.1x10<sup>7</sup> Resistivity (@ 50% RH at 100 Volts AP)  $2.3x10^{8}$ 4.3x10<sup>7</sup>

Typical Test Data - Chemical:

Ph (acid level) 7.02 (neutral) Chloride (CI) < 100 ppm Nitrate (NO<sub>3</sub>) < 10 ppm Amine  $(NH_2 - R)$ < 55 ppm Sodium (Na) < 85 ppm

Standard Sizes:

8 ½ x 11" loose sheet (0.0038" and 0.0080" thick) 11 x 17" loose sheet (0.0038" and 0.0080" thick) A4 metric loose sheet (0.0038" and 0.0080" thick)

9 ½ x 11" continuous feed sheet (0.0038" thick)

Standard Colors:

White (with Pink ESD indication stripe) / Blue / Pink / Green / Yellow Many other colors available

Rolls: all roll paper is 0.0031" (0.079mm) thick From 2.5" to 36" wide on various cores 1/2" to 3"

Pads: Pads of 60 sheets in large (8.5 x 11" or medium (5.5 x 8.5") sheets

Paper can be printed to customer's specifications. Tech sheet A09-STDPART-Dec06

ESD Paper is Recyclable and RoHS Compliant

5228 US HWY 421 N **WILMINGTON, NC 28401** 

800-379-9903 (fax) 800-537-0351 (tel) sales@all-spec.com (email) www.all-spec.com (web)