



1613 Series Low Static Masking Tape

The Dadas 1613 series is a low static, general purpose crepe paper masking tape for use in ESD-sensitive environments. This masking tape produces less than 200 volts at removal from roll with typical usage. It also offers excellent adhesion, temperature resistance, and holding properties. This all-purpose masking tape is coated with a natural rubber adhesive.



Products:

Part No.	Description
1613-05	Low Static Masking Tape, 1/2" x 60 yards
1613-75	Low Static Masking Tape, 3/4" x 60 yards
1613-10	Low Static Masking Tape, 1" x 60 yards
1613-15	Low Static Masking Tape, 1-1/2" x 60 yards
1613-20	Low Static Masking Tape, 2" x 60 yards
1613-30	Low Static Masking Tape, 3" x 60 yards

PRODUCT SPECIFICATIONS

Physical Properties	Typical Values
Total Thickness	5.2 mil
Peel Adhesion to Steel	16 oz/in
Adhesive Type	Natural Rubber
Elongation at Break	9%
Temperature Rating	One hour up to 203°F (95°C)
Static Charge at Removal from Roll	< 200 volts
Color	Pale Beige
Core Size	3"
Core Type	Paper
Roll Length	60 yards (180 feet)

- This information is offered as a guide to aid in proper selection. The user must determine the suitability of the product for the intended use. Because of varied applications and performance conditions, Dadas products are warranted against manufacturing defects only.
- This product should be kept away from direct exposure to sunlight and must be stored in a ventilated storage environment with temperature of approximately 68°F.