

BONDERITE S-ST 6776 LO AERO

PAINT STRIPPER

(KNOWN AS TURCO 6776-LO)

INTRODUCTION:

BONDERITE S-ST 6776 LO AERO (known as TURCO 6776-LO) is a low odor, thixotropic paint remover developed for effective stripping of such resistant finishes as epoxies, epoxy primers, polyurethanes, and similar catalyzed paints.

BONDERITE S-ST 6776 LO AERO paint remover offers a significant advance in work place safety. It does not contain methylene chloride, chlorinated solvents, phenols, chromates, ammonia or amines. It complies fully with the aircraft/aerospace NESHAP.

BONDERITE S-ST 6776 LO AERO can be used on aluminum, mild steel, cast iron, and titanium when used as directed. BONDERITE S-ST 6776 LO AERO is not recommended for use on high strength steel or magnesium.

FEATURES:

- Low odor
- Reduced air pollution, 0 lb/gal H.A.P.S.; <2 mm Hg V.O.C. Vapor Pressure
- Significantly lower waste disposal costs
- Can be easily treated on site (see MSDS)
- Amount of stripper used less than conventional methylene chloride strippers
- No flash point to boil (Pensky-Martens)
- Used as received, No mixing or dilution required
- Excellent cling to vertical and overhead surfaces
- Positive pressure air respirators are not required

USE INSTRUCTIONS:

Application: Apply a uniform to surface being stripped by means of non-atomizing spray. Allow sufficient time for stripper to work. Performance improves as temperature increases. Agitation with a stiff bristle brush will aid in removal of the finish. Repeat if necessary.

Removal: Squeegee off bulk of loosened paint and BONDERITE S-ST 6776 LO AERO, followed by high pressure water rinse.

DISPOSAL INFORMATION:

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional disposal information.

Concentrates: **(1)** Transfer to reclaiming center for recycling or reuse, if possible. **(2)** Transfer to licensed hazardous waste treatment or disposal site for disposition under applicable local, state and regional regulations as hazardous waste. **(3)** Small amounts may be dissolved in water and treated as described below. The clarified water may be released to sewer if local regulations permit.



**BONDERITE S-ST 6776 LO AERO
PAINT STRIPPER
(KNOWN AS TURCO 6776-LO)**

Spent solution and rinses: Dispose per (1) or (2) above or heavy metals (if present) may be precipitated by pH adjustment to 9.5 - 10.5; the pH of the separated water should then be readjusted to pH 7.0 - 8.0. The clarified water may be released to sewer if local regulations permit.

PRECAUTIONARY INFORMATION:

BONDERITE S-ST 6776 LO AERO contains formic acid. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in confined areas. Avoid prolonged breathing of vapors. Use with adequate (equivalent to outdoor) ventilation.

Note: VOC = 395 g/L

Protective clothing, such as a chemical face shield or goggles and gloves, should be worn and a **NIOSH approved** respirator equipped with a mechanical filter should be worn for mist conditions.

Store containers at temperature between 2° to 40°C.

Before using this product refer to container label and HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 8/2013

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | www.henkelna.com/

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.**

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

