

FLUX PEN: NO CLEAN, LEAD FREE

836-P

Safety Data Sheet

Section 1: Product and Company Identification

Product Identifier and Other Means of Identification

Product Name: Flux Pen: No Clean, Lead Free**SDS Code:** 836-Pen**Related Part #** 836-P

Recommended Use and Restriction on Use

Use: No clean flux pen**Uses Advised Against:** Not applicable

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**☎** +1-905-331-1396**FAX** +1-800-340-0773**FAX** +1-905-331-2682**E-MAIL** support@mgchemicals.com**E-MAIL** info@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents
USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7
CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

FLUX PEN: NO CLEAN, LEAD FREE

836-P

Section 2: Hazards Identification

Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation Specific Target Organ Toxicity Single Exposure	2A 3	Warning Warning	Exclamation Exclamation


Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Other Classifications

HMIS® RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES





Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE
836-P
Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness and dizziness
Prevention	Precautionary Statements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261	Avoid breathing vapors.
P271	Use only outdoors or in well ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
P302 + P353	IF ON SKIN: Rinse skin with water.
Storage	Precautionary Statements
P403 + P235	Store in well ventilated place. Keep cool.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE

836-P

Other Hazards

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Hazardous Ingredients

CAS #	Chemical Name	%(weight)
67-63-0	propan-2-ol ^{a)}	≤90%

a) Commonly known as isopropyl alcohol (IPA)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, tearing, redness, pain</i>
Response	Rinse cautiously with water for 15 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF ON SKIN	P302 + P353
Immediate Symptoms	<i>redness, mild irritation</i>
Response	Rinse skin with water.
IF INHALED	P304 + P340 + P312
Immediate Symptoms	<i>cough, dizziness, drowsiness, headaches, weakness</i>
Response	Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing. If feeling unwell: Call a POISON CENTRE/doctor.

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE**836-P****IF SWALLOWED** P301 + P330 + P331**Immediate Symptoms** *nausea, dizziness, weakness, headaches***Response** Rinse mouth.
Do NOT induce vomiting.**Section 5: Fire-Fighting Measures****In case of fire** P370 + P378**Response** Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish. Use water spray to cool containers.**Specific Hazards** Vapors may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.**Combustion Products** Produces carbon oxides (CO, CO₂)**Fire-Fighter** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.**Section 6: Accidental Release Measures****Personal Protection** See personal protection equipment in Section 8.**Precautions for Response** Remove or keep away all sources of ignition or extreme heat. Avoid breathing vapors.**Environmental Precautions** Not applicable**Containment** Not applicable**Cleaning** Collect wipes in a sealable, solvent-resistant container.**Disposal Methods** Dispose of spill waste according to Section 13.

FLUX PEN: NO CLEAN, LEAD FREE

836-P

Section 7: Handling and Storage

- Prevention** Keep out of reach of children.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Avoid breathing vapors. Use only outdoors or in a well-ventilated area.
- Handling** Wear protective gloves/eye protection.
 Wash hands thoroughly after handling.
- Storage** Store in a well-ventilated area. Keep cool.
RECOMMENDATION: Keep in a dry and clean area, away from incompatible substances.

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Eye contact, Inhalation, Skin contact, Ingestion

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from by RTECS database² of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE**836-P****Engineering Controls**

Ventilation Keep airborne concentrations below exposure limits.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.
RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection Wear appropriate protective clothing to prevent skin contact.
RECOMMENDATION: Use of protective gloves in butyl rubber, nitrile rubber, or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.
Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.
RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this MSDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

FLUX PEN: NO CLEAN, LEAD FREE
836-P
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	2%
Appearance	Light straw color	Upper Flammability Limit	12%
Odor	Alcohol like	Vapor Pressure @20 °C	4.2 kPa [32 mmHg]
Odor Threshold	0.44 ppm	Vapor Density	2.1 (Air =1)
pH	Not available	Specific Gravity @25 °C	0.8
Freezing/Melting Point	-88 °C [-126 °F]	Solubility in Water	Partially miscible
Boiling Point	≥81.8 °C [≥179 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	12 °C [54 °F]	Auto-ignition Temperature	425 °C [797 °F]
Evaporation Rate	1.5 (ButAc = 1)	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @20 °C	Not available

a) Tag closed cup value

Section 10: Stability and Reactivity

Reactivity	At elevated temperatures, may react with aluminum and generate hydrogen gas.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid Ignition sources, excessive heat, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, halogenated compounds, aluminum at temperatures ≥ 49 °C [>120 °F]
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

FLUX PEN: NO CLEAN, LEAD FREE**836-P****Section 11: Toxicological Information****Routes of Exposure**

Eye Contact, Inhalation, Skin contact, and Ingestion

Symptoms Summary

Eyes	Causes serious eye irritation, tearing, redness or pain.
Skin	Causes dry mild skin or redness.
Inhalation	May cause drowsiness or dizziness. Excessive exposure may cause narcotic effects, weakness, and headaches.
Ingestion	See inhalation symptoms.
Chronic	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat

Note: Toxicity data from the RTECS database accessed through the Canadian Centre for Occupational Health and Safety (CCOHS)² were consulted. The data from supplier (M)SDS were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are not met. Causes mild skin irritation based on Draize tests on rabbits.
Serious eye damage/irritation	Causes severe eye irritation: propan-2-ol is a severe irritant based on Draize tests on rabbits.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Propan-2-ol is not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE**836-P**

Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources. The ecotoxicity of the mixture was estimated by the calculation method using the summation of classified ingredients.

Based on available data, propan-2-ol does not meet the environmental toxicant classification with LC50 and EC50 >100 mg/L.

- Propan-2-ol has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of 2 000 mg/L Desmodesmus subspicatus (green algae).

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds

Biodegradability

The constituents are volatile.

Other Effects

Not available

FLUX PEN: NO CLEAN, LEAD FREE**836-P****Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground**

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 5 liters and under

Limited Quantity**Air**

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under

Excepted Quantity
Document as class **E2**

UN number: UN1219
Shipping Name: ISOPROPANOL solution
Class: 3
Packing Group: II
Marine Pollutant: No
Flash Point = 12 °C [54 °F]

Section continued on the next page


FLUX PEN: NO CLEAN, LEAD FREE**836-P****Sea****Refer to IMDG regulations.**

Sizes 30 mL and under

Excepted Quantity
Document as class **E2****UN number:** UN1219**Shipping Name:** ISOPROPANOL
solution**Class:** 3**Packing Group:** II**Marine Pollutant:** No

Flash Point = 12 °C [54 °F]

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****WHMIS 1988 Classification**

B2 – Flammable Liquid; D2B – Toxic Material (Eye Irritant)

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE**836-P****USA****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains up to $\geq 90\%$ propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any of the listed substances.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by Michel Hachey

Date of Revision 12 June 2015

Supersedes Not applicable

Reason for Changes: New product classified according to HCS 2012 and WHMIS 2015.

Reference

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

FLUX PEN: NO CLEAN, LEAD FREE**836-P****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.