



PRODUCT DATA SHEET

Dry PTFE Lube, 10 Wt Oz
Part Number: 03044



| | |
|---------------------------|---|
| Product Description | Contains PTFE, the advanced Dry Film lubricant technology from DuPont®. Penetrates and bonds to most surfaces. Prevents sticking, reducing friction and wear and is highly resistant to oil, dust and dirt build-up. NSF H2 Registered. |
| Applications | Hinges, locks, catches, pulleys, conveyors, machine parts, chutes & slides, coin mechanisms, window guides, drawers, rollers, control buttons, switches, electrical wires & harnesses. |
| Unit Package Description | 16 Ounce Aerosol |
| Brand | CRC |
| Generic Description 1 | Dry Film Lubricant |
| Net Fill | 10 Wt Oz |
| UPC Code | 078254030449 |
| Unit Dimensions | 7.75H x 2.63W x 2.63D in |
| Units Per Case | 12 |
| Case Dimensions | 8.1H x 8.3W x 11.1D in |
| Cases Per Pallet | 133 |
| Case Weight | 11 lbs |
| I 2 of 5 Code | 30078254030440 |
| Appearance | Hazy White Suspension in Liquid |
| Base Type | PTFE |
| Flash point (F) | <20°F |
| Flash point (C) | <-7°C |
| Flammability Class - CPSC | Flammable |
| Spec Gravity Concentrate | 0.73 |
| Plastic Safe | Yes |
| Film Type | Micro-Thin and Dry |
| Film Thickness | 0.05 to 0.1 Mil |
| Evaporation Rate | Fast |

Last revised: 5/4/2016
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



| | |
|----------------------------|--|
| Working Temp (F) | -40 to 450°F |
| Working Temp (C) | -40 to 232.2°C |
| Propellant | Hydrocarbon |
| NSF Category Code | H2 |
| NSF Number | 121621 |
| Aerosol Flammability Level | III |
| DOT Proper Shipping Name | Aerosols, Flammable, Limited Quantity |
| VOC % (Federal) | 98 |
| VOC g/L (Federal) | 715.4 |
| VOC Lbs./Gal. (Federal) | 5.96 |
| VOC Category | Not Regulated |
| Removal (How To) | Remove with IPA or hexane if wet; hard rubbing when dry. |



Last revised: 5/4/2016
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.