

PREMIUM ACRYLIC CONFORMAL COATING

419D-AEROSOL

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

Product Name: Premium Acrylic Conformal Coating

SDS Code: 419D-Aerosol

Related Part # 419D-340G

### Recommended Use and Restriction on Use

Use: Protective coating for printed circuit boards

Uses Advised Against: Not available

### Details of Manufacturer or Importer

#### Manufacturer

MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA

MG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA

☎ +1-800-340-0772

Fax +1-800-340-0773

E-mail [support@mgchemicals.com](mailto:support@mgchemicals.com)Web [www.mgchemicals.com](http://www.mgchemicals.com)

☎ +1-905-331-1396

Fax +1-905-331-2682

E-mail [info@mgchemicals.com](mailto:info@mgchemicals.com)E-MAIL (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

For hazardous material incidents **ONLY**—leaks, spills, fires, exposures or accidents  
USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7




CANADA: Call CANUTEC ☎: **+1-613-996-6666** or **\*666** on cellular phones

**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol Gas Under Pressure	2 Liquefied Gas	Warning Warning	Flame Gas cylinder
Sensitization Specific Target Organ Toxicity	Skin Single Exposure 1 3	Warning Warning	Exclamation Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H223: Flammable aerosol
	H280: Contains gas under pressure; may explode if heated
	H317: May cause an allergic skin reaction H336: May cause drowsiness or dizziness

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
*Continued ...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
<b>Response</b>	<b>Precautionary Statements</b>
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in well-ventilated place.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents/container in accordance to local/regional/international regulations.

**Other Hazards**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	% (weight)
115-10-6	dimethyl ether	40%
123-86-4	n-butyl acetate	35%
78-93-3	butan-2-one <sup>a)</sup>	7%
108-65-6	1-methoxy-2-propanol acetate	4%
80-62-6	methyl methacrylate	0.1%
97-88-1	n-butyl methacrylate	0.1%

a) Also known as methyl ethyl ketone (MEK)

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364
<b>Immediate Symptoms</b>	<i>redness, mild irritation, rash, dry skin, allergic reaction</i>
<b>Response</b>	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take of contaminated clothing and wash it before reuse.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>dizziness, drowsiness, cough, headaches, sore throat, nausea</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, mild irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>nausea, sore throat, diarrhea, drowsiness, dizziness, vomiting</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	<p>Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].</p> <p>Produces irritating and toxic fumes in fires or in contact with hot surfaces.</p> <p>The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.</p>
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the mist/spray/vapors. Remove or keep away all sources of ignition or extreme heat.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	<p>Collect liquid in a sealable, solvent-resistant container.</p> <p>Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.</p>
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**PREMIUM ACRYLIC CONFORMAL COATING**

**419D-AEROSOL**

**Section 7: Handling and Storage**

- Prevention**      Keep out of reach of children.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source.
- Do not pierce or burn, even after use.
- Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.
- Handling**        Wear protective gloves/eye protection/face protection
- Contaminated work clothing should not be allowed out of the workplace.
- Storage**          Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
- Store in well-ventilated place.
- Store locked up.

**Section 8: Exposure Controls/Personal Protection**

**Substances with Occupational Exposure Limit Values**

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
dimethyl ether	ACGIH	Not established	Not established
	U.S.A. WEEL	1 000 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	1 000 ppm	Not established
	Canada ON	Not established	Not established
n-butyl acetate	Canada QC	Not established	Not established
	ACGIH	150 ppm	Not established
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	200 ppm
Canada ON	150 ppm	Not established	
Canada QC	150 ppm	200 ppm	

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
*Continued...*

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
butan-2-one	ACGIH	200 ppm	125 ppm
	U.S.A. OSHA PEL	200 ppm	300 ppm
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm
1-methoxy-2-propanol acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A. California <sup>a)</sup>	100 ppm	150 ppm
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
methyl methacrylate	ACGIH	50 ppm <sup>b)</sup>	100 ppm
	U.S.A. OSHA PEL	100 ppm	Not established
	Canada AB	50 ppm	100 ppm
	Canada BC	50 ppm <sup>b)</sup>	100 ppm
	Canada ON	50 ppm	100 ppm
	Canada QC	100 ppm	Not established
n-butyl methacrylate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	Not established
	Canada ON	Not established	Not established
	Canada QC	Not established	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) California Code of Regulations, Title 8, Section 5155. Airborne Contaminants. Can be absorbed through skin.

b) Sensitizer (S)

## Engineering Controls

### Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**Recommendation:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.



**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b> <sup>c)</sup>	2%
<b>Appearance</b>	Clear	<b>Upper Flammability Limit</b> <sup>c)</sup>	11%
<b>Odor</b>	Ester-like, fruity	<b>Vapor Pressure @20 °C</b> <sup>c)</sup>	35 hPa [26 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>1.59 (Air =1)
<b>pH</b>	Not available	<b>Specific Gravity @25 °C</b>	0.91
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Slightly soluble
<b>Boiling Point</b> <sup>a)</sup>	≥80 °C [≥176 °F]	<b>Partition Coefficient</b>	Not available
<b>Flash Point</b> <sup>b)</sup>	9 °C [48 °F]	<b>Auto-ignition Temperature</b> <sup>d)</sup>	≥226 °C [≥439 °F]
<b>Evaporation Rate</b>	<1 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available	<b>Viscosity @25 °C</b>	110 mm <sup>2</sup> /s

a) Values based on butan-2-one component.

b) Pensky-Martens closed cup

c) Calculated based on liquid content without propellant.

d) Values based on dimethyl ether, which is the component with the lowest auto-ignition value.

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

**PREMIUM ACRYLIC CONFORMAL COATING**
**419D-AEROSOL**
**Section 11: Toxicological Information**
**Routes of Exposure**

Skin contact, Inhalation, Eye contact

**Symptoms Summary**

<b>Eyes</b>	May cause redness, mild irritation and/or pain.
<b>Skin</b>	Cause skin redness, mild irritation, dry skin, rash and allergic reaction.
<b>Inhalation</b>	May cause dizziness, drowsiness, cough, headaches, sore throat or nausea.
<b>Ingestion</b>	May cause nausea, sore throat, diarrhea, or vomiting (see inhalation symptoms).
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.  Prolonged or repeated exposure may cause skin allergies.

**Acute Toxicity (Lethal Exposure Concentrations)**

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
dimethyl ether	Not available	Not available	308 g/m <sup>3</sup> Rat
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	21.1 mg/L 4 h Rat
butan-2-one	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m <sup>3</sup> 8 h Rat
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available
methyl methacrylate	7 872 mg/kg Rat	>5 000 mg/kg Rabbit	78 000 mg/m <sup>3</sup> 4 h Rat
n-butyl methacrylate	16 000 mg/kg Rat	113 000 µL/kg Rabbit	29 mg/L 4 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Based on available data, the classification criteria are not met.
<b>Sensitization</b> (allergic reactions)	The n-butyl methacrylate and methyl methacrylate may cause skin sensitization according to animal studies.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	The n-butyl acetate, butan-2-one, 1-methoxy-2-propanol acetate, n-butyl methacrylate, and methyl methacrylate components can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There are no Cat 1 substances, and the kinematic viscosity is >20.5 mm <sup>2</sup> /s at 40 °C.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The n-butyl acetate ingredient is an acute category 3 environmental toxicant (biodegradable, with minimal LC50 96 h of 18 mg/L for fathead minnow).

The butan-2-one (MEK), methyl methacrylate, and n-butyl methacrylate ingredients are not classified as an environmental hazard according to GHS criteria.

- The 1-methoxy-2-propanol acetate component has a minimal LC50 96 h of  $\geq 100$  mg/L *Salmo gairdneri*; and EC50 48 h >500 mg/L *Daphnia magna* (water flea).

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Acute Ecotoxicity**

Available data doesn't give rise to classification as an acute ecotoxicant.

**Chronic Ecotoxicity**

Available data doesn't give rise to classification as a chronic ecotoxicant.

**Biodegradability**

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

**Other Effects**

Actual Volatile Organic Compounds (VOC) content.

VOC = 87% [794 g/L]

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**Section 14: Transport Information****Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA CFR 49** (Parts 100 to 185) **Regulations.**

Limited Quantity



**UN number:** UN1950

**Shipping Name:** AEROSOL,  
flammable

**Class:** 2.1

**Packing Group:** Not applicable

**Marine Pollutant:** No



*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Air**

Refer to ICAO-IATA Dangerous Goods Regulations.

**Limited Quantity**  
See package  
instruction Y203**UN number:** UN1950  
**Shipping Name:** AEROSOL,  
flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No**Sea**

Refer to IMDG regulations.

**Limited Quantity****UN number:** UN1950  
**Shipping Name:** AEROSOL,  
flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No

*Note:* Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

**Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


**Industry and Science Canada**

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

*Section continued on the next page*

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****USA****Other Classifications****HMIS® RATING**

<b>HEALTH:</b>	* 2
<b>FLAMMABILITY:</b>	3
<b>PHYSICAL HAZARD:</b>	0
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA (Clean Air Act, USA)**

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains methyl methacrylate, which is listed as hazardous air pollutants.

**EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)**

This product contains 0.2% of methyl methacrylate (CAS# 80-62-4; reportable quantity = 1000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains n-butyl acetate (CAS# 123-86-4) and 2-butanone (CAS# 78-93-3), which are subject to the CERCLA reporting requirements at the 5000 lb (2268 kg) threshold.

**TSCA (Toxic Substances Control Act of 1976, USA)**

All substances are TSCA listed.

**California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).**

This product does not contain any substances known to be listed in California.

**Europe****RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

**WEEE (Waste Electrical and Electronic Equipment Directive)**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**PREMIUM ACRYLIC CONFORMAL COATING****419D-AEROSOL****Section 16: Other Information**

**SDS Prepared by** Michel Hachey  
**Date of Creation** 07 September 2016  
**Supersedes** Not available

**Reason for Changes:** New aerosol format product classified in accordance with both HCS 2012 and WHMIS 2015.

**Reference**

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

*Section continued on the next page*



**PREMIUM ACRYLIC CONFORMAL COATING**

**419D-AEROSOL**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** Manufacturing & Support  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

Head Office  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer** This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.