

Technical Data Sheet

AXAREL® 32

Product Description

AXAREL 32 Defluxer is a proprietary cleaning mixture composed of highly refined solvents and surfactants designed for temperature flexible defluxing applications using semi-aqueous spray and immersion cleaning processes.

Features and Benefits

 Removes 	Flux Residues
-----------------------------	---------------

Water Rinsable

• Separates for Recycling

High Soil Loading

• Removes Ionics

Excellent Solvency

Properties

Odor Mild Hydrocarbon 205 °F (96 °C) Flash Point

Specific Gravity (25 °C) 0.85 Viscosity (25 °C) 2.8 cps Vapor Pressure (20 °C) < 0.1 mmHg 64

Kauri-Butanol (KB) Value

Soils Removed

Lead-free Flux Residues

• No Clean Flux Residues

• RMA Flux Residues

• Ionic Contamination

Water Soluble Flux Residues

• HMP Flux Residues

• Fingerprint Oils

• Uncured SMD Adhesives

Equipment

Suitable for use in specially designed cleaning equipment including immersion, ultrasonics, spray-in-air* and spray-under-immersion systems.

Process

Wash Bath Concentration	100% Concentration
Wash Bath Temperature	140-160 °F (60-71 °C)
DI Water Rinse Temperature	140-160 °F (60-71 °C)

AXAREL 32 may be separated from the water and returned to the wash reservoir for reuse. Most systems incorporate two or three successive rinses. Mechanical or ultrasonic agitation is recommended.

^{*}may require fire suppression system



Technical Data Sheet

AXAREL® 32

Environmental/Regulatory

Ozone Depletion Potential (ODP)

Global Warming Potential (GWP)

Volatile Organic Compound (VOC)

Hazardous Air Pollutant (HAP)

Zero

Low

786 g/L

National Emission Standards for Hazardous Air Pollutants (NESHAPs)

Superfund Amendments and Reauthorization Act (SARA)

Resource Conservation and Recovery Act (RCRA)

Not regulated

Not regulated

Disposal/Safety

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal. Safety

Please see Safety Data Sheet for further information.

Packaging

Available in 33 lb (15 kg) pails and 365 lb (166 kg) drums.

Shelf Life

36 months when stored in original, sealed container above 50 °F (10 °C).



ISO 9001:2008









 $\label{eq:alpha} \textbf{AXAREL} \ \textbf{is a registered trademark of Vantage Specialties, Inc.}$

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.