

Technical Data Sheet

Product Description

LENIUM GS Vapor Degreasing Solvent is a mixture based on n-propyl bromide (*n*PB) and stabilizers designed for use in open-top and vacuum vapor degreasers. It removes adhesives, buffing compounds, drawing oils, greases, hydraulic oils, lapping compounds, resins, inks, silicone oils and waxes. LENIUM GS is a drop-in replacement for trichloroethylene (TCE), HCFC-141b, HCFC-225, perchloroethylene (PCE) and methylene chloride (MeCl).

Features and Benefits

- General Metal Cleaner
- Replaces TCE, PCE, etc.
- Good Material Compatibility
- Aerospace Approved
- Low Surface Residues

Properties

Appearance	Clear Liquid
Specific Gravity (25°C)	1.32
Viscosity (25 °C)	0.49 cps
Vapor Pressure (20 °C)	110.8 mm Hg
Vapor Density (20 °C)	3.4
Flash Point	None
Boiling Point	160 °F (71 °C)
Specific Heat (25 °C)	0.27
Heat of Vaporization	58.8 cal/g
Kauri-Butanol (KB) Value	125

Soils Removed

- Adhesives
- Hydraulic Oils
- Buffing Compounds
- Lapping Compounds
- Drawing Oils
- Resins & Inks
- Silicone Oils
- Greases
- Waxes

Equipment

Suitable for use in a variety of commercially available cleaning equipment including open-top and vacuum vapor degreasers.

Technical Data Sheet

Process

Add LENIUM GS at full concentration to the tank reservoir(s). See Vapor Degreasing Operating Manual for more information.

Controller Settings

Liquid Temperature Controller Sensor (LTC)	170 °F (77 °C)
High Temperature Controller (HTC)	175 °F (79 °C)
Safety Vapor Controller (SVC)	150 °F (66 °C)
Vapor Up Temperature (VU)	150 °F (66 °C)
Primary Refrigeration Temperature	35-40 °F (2-5 °C)

Environmental/Regulatory

Ozone Depletion Potential (ODP)	0.013-0.018
Global Warming Potential (GWP)	Low
Acceptable Exposure Limit (AEL)	25 ppm
Volatile Organic Compound (VOC)	1320 g/L
National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Not regulated
Superfund Amendments and Reauthorization Act (SARA)	Not regulated
Resource Conservation and Recovery Act (RCRA)	Not regulated
Permissible Exposure Limit (PEL, ACGIH)	0.1 ppm

Disposal/Safety

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal.

Safety

Please see Safety Data Sheet for further information.

Approvals/Testing

Approvals

Bell Helicopter Bulletin No.: 1918 n-Propyl Bromide, Vapor Degreasing Grade

Boeing BAC 5408 Vapor Degreasing Specification (PSD 6-68)

Scott Aviation SMP No.: 7700009 Rev. AP, Cleaning of Components & Assemblies for Use in Breathing Equipment

Lockheed Martin EMAP G41.149

Praxair ID# GDE 10055434

Safran In-1500 Products Used For Degreasing-Organic Solvents (n-Propyl Bromide)

Testing

ASTM F-519, F-945, F-1110

Packaging

Available in 55 lb (25 kg) pails and 602 lb (273 kg) drums.

Technical Data Sheet

Shelf Life

36 months when stored in original, sealed container above 50 °F (10 °C).



LENIUM is a registered trademark of Vantage Specialties, Inc.

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.