

Technical Data Sheet

AXAREL® 4100

Product Description

AXAREL 4100 Precision Cleaner is a highly versatile proprietary cleaner that is a mixture of modified alcohols and refined hydrocarbons. It is formulated with a broad range of solvency that effectively removes greases, mineral oils, coolants, synthetics and other metalworking fluids. AXAREL 4100 is a direct replacement for acetone, isopropyl alcohol (IPA), methyl ethyl ketone (MEK), toluene and other low-flash point, flammable materials. With fast dry times and low surface residues, this cleaning solvent may be used prior to painting, plating and other surface finishes. AXAREL 4100 is designed for use in manual or immersion. It is compatible with many polymeric substrates, elastomers and is safe for use with ferrous and non-ferrous alloys.

Features and Benefits

- Broad Based Solvency
- Replaces IPA, MEK, Acetone
- Low Surface Residues
- Fast Dry Time
- Aerospace Approved
- Used for Final Cleaning

Properties

Odor	Mild
Flash Point	116 °F (47 °C)
Specific Gravity (25 °C)	0.76
Vapor Pressure (20 °C)	2.0 mmHg

Soils Removed

- Mineral Oils
- Water Soluble Oils
- Synthetic Oils
- Coolants
- Rust Inhibitors
- Greases
- Lubricating Oils
- Fingerprint Oils
- Dust
- Removes Polar and Non-Polar Soils

Equipment

Suitable for use in a variety of commercially available cleaning equipment including immersion tanks and low pressure spray-under-immersion systems.

Process

Manual Cleaning

Apply at full concentration to the desired substrate by brush, pad or cloth.

Immersion Cleaning

Add at full concentration to the wash tank reservoir.

Technical Data Sheet

AXAREL® 4100

Health, Safety and Disposal

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal.

Safety

Please see Safety Data Sheet for further information.

Environmental/Regulatory

Ozone Depletion Potential (ODP)	Zero
Global Warming Potential (GWP)	Low
Volatile Organic Compound (VOC)	758 g/L
Hazardous Air Pollutant (HAP)	No
Superfund Amendments and Reauthorization Act (SARA)	Not regulated
National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Not Regulated
Resource Conservation and Recovery Act (RCRA)	Not Regulated

Approvals and Testing

Approvals

Goodrich Actuation Systems 981-100-020 Issue 4 Solvent Degreasing

Rolls-Royce CSS No. 255 Type A Non-Halogenated Organic Solvent Cleaner (MLC104)

Rolls-Royce OMat 1/257M Solvent Cleaner

Testing

SAE ARP 1755B, ASTM F945

NSN# 8010-01-535-0740

Packaging

Available in 31 lb (14 kg) pails and 350 lb (159 kg) drums.

Shelf Life

36 months when stored in original, sealed container above 50 °F (10 °C).

Technical Data Sheet

AXAREL® 4100



ISO 9001:2008



RoHS
Compliant



LEAD FREE



REACH✓

AXAREL is a registered trademark of Vantage Specialties, Inc.

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.

Vantage Specialties, Inc.

3938 Porett Drive • Gurnee, Illinois 60031 USA • **P** +1 847 244 3410 • **F** +1 847 249 6346 • www.vantagegrp.com