

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **LORD 406**
Product Use/Class: **Acrylic Adhesive, Part 1 of 2**

LORD Corporation
111 LORD Drive
Cary, NC 27511-7923 USA

Telephone: 814 868-3180
Non-Transportation Emergency: 814 763-2345
Chemtrec 24 Hr Transportation Emergency No.
800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 04/28/2016

2. HAZARDS IDENTIFICATION**GHS CLASSIFICATION:**

Flammable liquids Category 2
Acute toxicity Inhalation - Vapours Category 4 - 40.5% of the mixture consists of ingredient(s) of unknown toxicity.
Acute toxicity Inhalation - Dust and Mist Category 4 - 39.9% of the mixture consists of ingredient(s) of unknown toxicity.
Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1
Skin sensitization Category 1
Respiratory sensitization Category 1
Carcinogenicity Category 2
Reproductive toxicity Category 2
Specific target organ systemic toxicity (single exposure) Category 1 circulatory system, Nervous system, Cardio-vascular system
Specific target organ systemic toxicity (single exposure) Category 3
Specific target organ systemic toxicity (repeated exposure) Category 1 Blood, Liver, spleen, Adrenal gland, Kidney, Nervous system, Central nervous system, Respiratory system
Hazardous to the aquatic environment - acute hazard Category 3
Hazardous to the aquatic environment - chronic hazard Category 3

GHS LABEL ELEMENTS:**Symbol(s)****Signal Word**

DANGER

Hazard Statements

Highly flammable liquid and vapor.
Harmful if inhaled.
Causes severe skin burns and eye damage.
Causes serious eye damage.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs.(circulatory system, Nervous system, Cardio-vascular system)
May cause drowsiness or dizziness.

May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure.(Blood, Liver, spleen, Adrenal gland, Kidney, Nervous system, Central nervous system, Respiratory system)
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.
In case of inadequate ventilation wear respiratory protection.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.

Response

In case of fire: refer to section 5 of SDS for extinguishing media.
Immediately call a POISON CENTER or doctor/physician.
Specific treatment (see supplemental first aid instructions on this label).
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
Wash contaminated clothing before reuse.

Storage

Store in a well-ventilated place. Keep cool.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Harmful if absorbed through skin. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause headache and nausea.Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: Contains N,N-Dimethylaniline. Excessive overexposure by skin absorption or ingestion may result in anoxia due to the formation of methemoglobin. This condition impairs the blood's ability to transport oxygen. Prolonged or repeated contact may result in dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Methyl methacrylate	80-62-6	30 - 35 %

Methacrylate Blend	PROPRIETARY	1 - 5 %
Methacrylate phosphate ester	PROPRIETARY	1 - 5 %
Methacrylic acid	79-41-4	1 - 5 %
Amine curative	PROPRIETARY	1 - 5 %
N,N-Dimethylaniline	121-69-7	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Using non-sparking tools, scoop the spilled material into a container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

STORAGE: Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Inorganic acids, organic acids, caustics, oxidizing agents, amines, peroxides.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

Chemical Name	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	Skin
Methyl methacrylate	50 ppm	100 ppm	410 mg/m ³ 100 ppm	N.E.	N.A.
Methacrylate Blend	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylate phosphate ester	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylic acid	20 ppm	N.E.	N.E.	N.E.	S
Amine curative	N.E.	N.E.	N.E.	N.E.	N.A.
N,N-Dimethylaniline	5 ppm	10 ppm	25 mg/m ³ 5 ppm	N.E.	S

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Observe OSHA regulations (29CFR 1910.134) for respirator use. Contains a small amount of dimethylaniline (DMA) which has poor odor-warning properties. If the exposure limit for DMA is exceeded, an air-supplied respirator is recommended. Otherwise, a NIOSH approved properly-fitted organic vapor, air purifying respirator is recommended. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact. If contact with the product is prolonged or repeated, Silver Shield or Butyl rubber gloves are recommended.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR:	Sweet	VAPOR PRESSURE:	N.D.
APPEARANCE:	Off-white	VAPOR DENSITY:	Heavier than Air
PHYSICAL STATE:	Paste	LOWER EXPLOSIVE LIMIT:	1 %(V)
FLASH POINT:	59 °F, 15 °C Setaflash	UPPER EXPLOSIVE LIMIT:	8.8 %(V)
BOILING RANGE:	Closed Cup N.A.	EVAPORATION RATE:	Slower than n-butyl- acetate
AUTOIGNITION TEMPERATURE:	N.D.	DENSITY:	1.12 g/cm ³ - 9.31 lb/gal
DECOMPOSITION TEMPERATURE:	N.D.	VISCOSITY, DYNAMIC:	N.D.
ODOR THRESHOLD:	N.D.	VISCOSITY, KINEMATIC:	N.D.
SOLUBILITY IN H₂O:	Insoluble	VOLATILE BY WEIGHT:	0.00 %
pH:	N.A.	VOLATILE BY VOLUME:	0.00 %
FREEZE POINT:	N.D.	VOC CALCULATED:	0 lb/gal, 0 g/l

COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: Storage above 100 degrees F and below 32 degrees F. Exposure to sunlight, ultraviolet light irradiation. Avoid dropping or puncture of containers.

INCOMPATIBILITY: Inorganic acids, organic acids, caustics, oxidizing agents, amines, peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	LD50/LC50
Methyl methacrylate	Oral LD50: Rat 7,900 mg/kg Dermal LD50: Rabbit > 5 g/kg Inhalation LC50: Rat 4632 ppm/4 h GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l
Methacrylate Blend	Oral LD50: rat > 5,000 mg/kg Dermal LD50: rat > 2,000 mg/kg
Methacrylate phosphate ester	Oral LD50: rat > 5,000 mg/kg
Methacrylic acid	Oral LD50: Rat 1,060 mg/kg Dermal LD50: Rabbit 500 - 1,000 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l GHS LC50 (dust and mist): Acute toxicity point estimate 1.5 mg/l
Amine curative	N.D.
N,N-Dimethylaniline	Oral LD50: Rat 951 mg/kg Dermal LD50: Rabbit 1770 µL/kg Inhalation LC50: Rat > 0.5 - < 5.0 mg/l /4 h

Germ cell mutagenicity: No classification proposed

Carcinogenicity: Category 2 - Suspected of causing cancer.
Components contributing to classification: N,N-Dimethylaniline.

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child.
Components contributing to classification: Methyl methacrylate.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
Methyl methacrylate	Fish: Pimephales promelas 243 - 275 mg/196 h flow-through Pimephales promelas 125.5 - 190.7 mg/196 h Static Lepomis macrochirus 170 - 206 mg/196 h flow-through Lepomis macrochirus 153.9 - 341.8 mg/196 h Static Oncorhynchus mykiss > 79 mg/196 h flow-through

	<p>Oncorhynchus mykiss > 79 mg/196 h Static Poecilia reticulata 326.4 - 426.9 mg/196 h Static <u>Invertebrates:</u> Daphnia magna 69 mg/148 h <u>Plants:</u> Pseudokirchneriella subcapitata 170 mg/196 h</p>
Methacrylate Blend	N.D.
Methacrylate phosphate ester	N.D.
Methacrylic acid	N.D.
Amine curative	N.D.
N,N-Dimethylaniline	<p><u>Fish:</u> Pimephales promelas 52.6 mg/196 h flow-through Pimephales promelas 65.6 mg/196 h Poecilia reticulata 53.7 mg/196 h semi-static Brachydanio rerio 51.1 mg/196 h semi-static Brachydanio rerio 0.183 - 0.186 mg/196 h <u>Invertebrates:</u> Daphnia magna 5 mg/148 h <u>Plants:</u> Desmodesmus subspicatus 340 mg/196 h</p>

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

DOT Proper Shipping Name: Adhesives
DOT Hazard Class: 3
SECONDARY HAZARD: None
DOT UN/NA Number: 1133
Packing Group: II
Emergency Response Guide Number: 128

IATA Cargo

PROPER SHIPPING NAME: Adhesives
DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133
PACKING GROUP: II
EMS: 3L

IMDG

PROPER SHIPPING NAME: Adhesives
DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133
PACKING GROUP: II
EMS: F-E

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>
Methyl methacrylate	80-62-6	35.0 %
N,N-Dimethylaniline	121-69-7	5.0 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 3 PHYSICAL HAZARD: 1

* - Indicates a chronic hazard; see Section 2

Revision: Section 2

Effective Date: 04/28/2016

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **LORD ACCELERATOR 17**
Product Use/Class: **Acrylic Adhesive, Part 2 of 2**

LORD Corporation
111 LORD Drive
Cary, NC 27511-7923 USA

Telephone: 814 868-3180
Non-Transportation Emergency: 814 763-2345
Chemtrec 24 Hr Transportation Emergency No.
800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 03/11/2016

2. HAZARDS IDENTIFICATION**GHS CLASSIFICATION:**

Organic peroxides Type E
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Skin sensitization Category 1
Specific target organ systemic toxicity (single exposure) Category 3
Hazardous to the aquatic environment - acute hazard Category 1
Hazardous to the aquatic environment - chronic hazard Category 2

GHS LABEL ELEMENTS:**Symbol(s)****Signal Word**

WARNING

Hazard Statements

Heating may cause a fire.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

Precautionary Statements**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep/Store away from clothing/ combustible materials.
Keep only in original container.
Wear protective gloves/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.

Response

Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment (see supplemental first aid instructions on this label).
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash before reuse.
Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight.
Store at temperatures not exceeding .? °C/.? °F. Keep cool.
Store away from other materials.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: Prolonged or repeated contact may result in dermatitis. IARC has designated titanium dioxide (TiO2) as Group 2B □ possibly carcinogenic to humans in dust form. However, a number of long term animal studies and human epidemiology studies evaluating TiO2 and workplace exposure show insufficient evidence for carcinogenic effects. EPA, NTP and OSHA do not designate TiO2 as a carcinogen and ACGIH designates TiO2 as A4 - not classifiable as a human carcinogen. Mortality from other chronic diseases, including other respiratory diseases, was not associated with exposure to TiO2 dust. TiO2 is not present in this product as a dust and no airborne exposure is expected during application.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Epoxy resin	PROPRIETARY	40 - 45 %
Isodecyl benzoate	131298-44-7	20 - 25 %
Benzoyl peroxide	94-36-0	20 - 25 %
Titanium dioxide	13463-67-7	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Avoid contact. Avoid breathing vapors. Use appropriate respiratory protection for large spills or spills in confined area.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>	<u>Skin</u>
Epoxy resin	N.E.	N.E.	N.E.	N.E.	N.A.
Isodecyl benzoate	N.E.	N.E.	N.E.	N.E.	N.A.
Benzoyl peroxide	5 mg/m ³	N.E.	5 mg/m ³	N.E.	N.A.
Titanium dioxide	10 mg/m ³	N.E.	15 mg/m ³	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR:	No	VAPOR PRESSURE:	N.D.
APPEARANCE:	White	VAPOR DENSITY:	Heavier than Air
PHYSICAL STATE:	Paste	LOWER EXPLOSIVE LIMIT:	Not Applicable
FLASH POINT:	≥ 201 °F, 93 °C	UPPER EXPLOSIVE LIMIT:	Not Applicable
	Setaflash Closed Cup		
BOILING RANGE:	100 °C	EVAPORATION RATE:	Not Applicable
AUTOIGNITION TEMPERATURE:	N.D.	DENSITY:	1.2 g/cm3 - 10.00 lb/gal
DECOMPOSITION TEMPERATURE:	N.D.	VISCOSITY, DYNAMIC:	N.D.
ODOR THRESHOLD:	N.D.	VISCOSITY, KINEMATIC:	N.D.
SOLUBILITY IN H2O:	Insoluble	VOLATILE BY WEIGHT:	5.98 %
pH:	N.A.	VOLATILE BY VOLUME:	7.45 %
FREEZE POINT:	N.D.	VOC CALCULATED:	0 lb/gal, 0 g/l
COEFFICIENT OF WATER/OIL DISTRIBUTION:	N.D.		

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes, Metal oxides

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	LD50/LC50
Epoxy resin	Oral LD50: Rat 11,400 mg/kg
Isodecyl benzoate	N.D.
Benzoyl peroxide	Oral LD50: Rat 7,710 mg/kg
Titanium dioxide	Oral LD50: Rat > 10,000 mg/kg Dermal LD50: rabbit > 5,000 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 55 mg/l

Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

Reproductive toxicity: No classification proposed

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

<u>Chemical Name</u>	<u>Ecotoxicity</u>
Epoxy resin	N.D.
Isodecyl benzoate	N.D.
Benzoyl peroxide	N.D.
Titanium dioxide	N.D.

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

DOT Proper Shipping Name: Organic peroxide type E, solid
DOT Hazard Class: 5.2
SECONDARY HAZARD: None
DOT UN/NA Number: 3108
Packing Group: II
Emergency Response Guide Number: 145

IATA Cargo

PROPER SHIPPING NAME: Organic peroxide type E, solid
DOT Hazard Class: 5.2
HAZARD CLASS: None
UN-NUMBER: 3108
PACKING GROUP: II
EMS: 5L

IMDG

PROPER SHIPPING NAME: Organic peroxide type E, solid
DOT Hazard Class: 5.2
HAZARD CLASS: None
UN-NUMBER: 3108
PACKING GROUP: II
EMS: F-J

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>
Benzoyl peroxide	94-36-0	25.0 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 2

* - Indicates a chronic hazard; see Section 2

Revision: Section 2, Section 11

Effective Date: 03/11/2016

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.