

Botron B8511 Technical Data Sheet



Overview:

Botron's ESD safe paper is uniquely formulated to reduce particulation and smudging. Ideal for controlled environments such as clean rooms and other static free zones. Lays flat and works great in mechanical printing machines.

PROPERTIES

SPECIFICATIONS

Base Weight:	60# Offset (20# Bond)
Thickness:	4mil
Tear MD/CD:	30/32
Tenile MD/CD:	22/14
Sheffield	
Smoothness FS/WS:	50/50
Brightness:	91
Opacity:	92
Resistivity (@50% RH):	5 x 10e7
Resistivity (@20% RH):	6 x 10e9
PH (Acid level):	7.02 (Neutral)
Chloride:	<100ppm
Nitrate:	<10ppm
Amine:	<55ppm
Sodium:	<85ppm
Sulfate:	<100ppm
Size:	8.5" x 11", 11" x 17"
Ream Size:	500 Sheets
Color:	White w/Pink Stripe*

*Other colors available on special order

Product Notes and Features

- Permanently Static Dissipative
- Ultra Low Particulation
- 500 Page Ream
- 8.5" x 11"
- 11" x 17"



PART NUMBERS

B8511 ESD Safe Paper

B851117 ESD Safe Paper

Distributed by: Hisco | 877-447-2650 | www.hisco.com | info@hiscoinc.com
and All-Spec | 800-537-0351 | www.all-spec.com | sales@all-spec.com

Botron Company Inc. | 325 W. Melinda Ln Phoenix AZ 85027 | Ph# 623-582-6700 | Fax# 623-582-6776

Disclaimer. All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user. The statements herein shall have no force or effect.