



Made in the
United States of America



Listing #90P1

UL Listed

Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the ESD Series.

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

The Adjustable Wrist Strap set provides a cost-effective method of grounding personnel. Features a comfortable, adjustable band, a 5 ft./10 ft. (1.5 m/3 m) coil cord with a 4mm snap. One size adjusts to most any size wrist to provide reliable, 360-degree protection. A 1 megohm resistor is built into the ground cord. Adjust band over a range of diameters, 1.7 in. – 3.5 in. Meets ANSI/ESD S20.20 and ANSI/ESD S1.1.

Specifications - Band	Typical Value	Test Method
Fabric	Elastic Nylon	
Resistance	< 500 ohms	ANSI/ESD S1.1
Contact	360° Around Wrist	
Color	Burgundy	
Snap	4mm	
Snap Release	< 2 lbs.	
Back Plate	Stainless Steel	

Specifications - Cord	Typical Value	Test Method
Length	5 or 10 feet	
Resistance	1 Megohm Resistor	ANSI/ESD S1.1
Flex life average	1,000,000 cycles	ANSI/ESD S1.1
Color	Black	
Snap	4mm	

Item	Description
2204	Adjustable Wristband
2214	Adjustable Wrist Strap with 5' Coil Cord. Includes alligator clip.
2224	Adjustable Wrist Strap with 10' Coil Cord. Includes alligator clip.

SINGLE-WIRE ADJUSTABLE FABRIC WRIST STRAP

926 JR Industrial Drive, Sanford, NC 27332
WEB SITE: StaticControl.com
PHONE (919) 718-0000

**DRAWING
NUMBER**
2204

DATE
October
2015

SCS