

# SAFETY DATA SHEET

## Section 1 - Chemical Product and Company Information

**Product Name:** 1201A Red Insulation Enamel - Aerosol **Product Code:** 1201A

**Trade Name:** Glyptal

**Manufactured by:**

GLYPTAL, INC.  
305 Eastern Ave.  
Chelsea, MA 02150  
Telephone (617) 884-6918

**IN CASE OF EMERGENCY:**

CHEMTREC 1-800-424-9300

**Product Use:** Coatings

**Not recommended for:** Nonindustrial Use

## Section 2 - Hazards Communication

**NFPA Ratings, risk phrases, and suggested WHMIS Hazard Categories:**

**GHS Ratings:**

Flammable aerosol	1	Flammable aerosol class 1
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Reproductive toxin	2	Human or animal evidence possibly with other information
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity $\leq 20.5$ mm <sup>2</sup> /s at 40° C.

**GHS Hazards**

H222	Extremely flammable aerosol
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child

**GHS Precautions**

P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P211	Do not spray on an open flame or other ignition source
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash skin thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P403+P233	Store in a well ventilated place. Keep container tightly closed
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container to an approved waste disposal plant

**Signal Word: Danger**



### Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Acetone	67-64-1	30.00% - 40.00%
Propane	74-98-6	15.00%
Methyl Ethyl Ketone	78-93-3	5.00% - 10.00%
Toluene	108-88-3	5.00% - 10.00%
Methyl Propyl Ketone	107-87-9	1.00% - 5.00%
Methyl Normal Amyl Ketone	110-43-0	1.00% - 5.00%
n-Butanol	71-36-3	1.00% - 5.00%

### Section 4 - First Aid Measures

**INHALATION** - Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room, or physician as further medical treatment may be necessary. Administer oxygen if a qualified operator is available.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. If irritation persists, contact a poison control center, emergency room, or physician as further medical treatment may be necessary.

**SKIN CONTACT** - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. If symptoms persist, contact a poison control center, emergency room, or physician as further medical treatment may be necessary.

**INGESTION** - If material is ingested, seek immediate medical attention. Do not induce vomiting. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. Contact a poison control center, emergency room, or physician as further medical treatment will be necessary.

## Section 5 - Fire Fighting Measures

**Flash Point:** 4 °C (39 °F)

**LEL:** 1.00

**UEL:** 13.00

**EXTINGUISHING MEDIA:** Use carbon dioxide (CO<sub>2</sub>), "alcohol" foam, dry chemical

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback. Closed containers may explode or burst when exposed to extreme heat. May produce hazardous decomposition products when exposed to extreme heat.

**HAZARDOUS COMBUSTION PRODUCTS:** See section 10 for a list of hazardous decomposition products for this mixture.

**FIRE FIGHTING:** Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

**FIRE FIGHTING EQUIPMENT:** Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

## Section 6 - Accidental Release Measures

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

**SMALL SPILLS:** Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

**LARGE SPILLS:** Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## Section 7 - Handling and Storage

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 50 to 85 °F (10 to 30 °C).

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120 F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst . Keep out of the reach of children.

**STORAGE:** Prevent from freezing. Do not store above 95 °F (35 °C).

Store only in original containers. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120 °F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst . Keep out of the reach of children.

## Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Acetone 67-64-1	PEL 1000 ppm - TWA	TLV 500 ppm - TWA STEL 750 ppm	Not Established
Propane 74-98-6	1000 ppm PEL	1000 ppm TWA	Not Established
Methyl Ethyl Ketone 78-93-3	PEL 200 ppm - TWA VPEL 200 ppm - TWA VPEL 300 ppm - STEL	TLV 200 ppm - TWA TLV 300 ppm - STEL	Not Established
Toluene 108-88-3	100 ppm - TWA (Z-1) 150 ppm - STEL (Z-1) 200 ppm TWA (Z-2)	TLV 20 ppm - TWA	Not Established
Methyl Propyl Ketone 107-87-9	PEL 200 ppm - TWA VPEL 200 ppm - TWA VPEL 250 ppm - STEL	TLV 200 ppm - TWA TLV 250 ppm - STEL	Not Established
Methyl Normal Amyl Ketone 110-43-0	PEL 100 ppm - TWA VPEL 100 ppm - TWA	TLV 50 ppm - TWA TLV 233 mg/m3 - TWA	Not Established
n-Butanol 71-36-3	PEL 100 ppm - TWA VPEL 50 ppm - Ceiling (Skin)	TLV 20 ppm - TWA	Not Established

**ENGINEERING:** Provide general dilution of local exhaust ventilation in volume and pattern to keep concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the workplace. Use explosion-proof equipment and good manufacturing practice.

**VENTILATION:** Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Refer to OSHA standards 1910.94, 1910.107, 1910.108.

## PERSONAL PROTECTIVE EQUIPMENT

### EYES:

Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

### PROTECTIVE GLOVES:

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear. If necessary, wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

### RESPIRATORY PROTECTION:

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. Where ventilation is inadequate, use a NIOSH/MSHA-approved, air-purifying respirator equipped with the appropriate chemical cartridges or positive-pressure, air-supplied respirator. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.

**CONTAMINATED EQUIPMENT:** Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<b>Appearance</b> Red Liquid	<b>Odor</b> Solvent odor
<b>Physical State</b> Liquid	<b>Vapor Density</b> Heavier than air
<b>Vapor Density</b> 2.08	<b>Vapor Pressure</b> 58.4 psi
<b>Evaporation Rate</b> Faster than ether	<b>Boiling Range</b> -42 to 149 °C
<b>Specific Gravity (SG)</b> 0.945	<b>Lbs VOC/Gallon Solids</b> 14.6
<b>Lbs VOC/Gallon Less Water and Exempt Solvent</b> 3.14	

## Section 10 - Stability and Reactivity

### Stability:

STABLE

### Components of this mixture are incompatible with the following materials:

Strong oxidizing agents  
Copper, copper alloys, strong alkalis, strong oxidizing agents  
Alkali metals, Aluminum, Halogens, Lead, Strong mineral acids, Strong oxidizing agents  
Strong oxidizing agents, acids, alkali/base/caustic solutions, and reducing agents

### This mixture is likely to exhibit the following combustion products:

Carbon Dioxide, Carbon Monoxide

Hazardous polymerization will not occur.

## Section 11 - Toxicological Information

### Component Toxicity

67-64-1 Acetone  
Oral LD50: 6 g/kg (Rat) Dermal LD50: 7 g/kg (Guinea Pig) Inhalation LC50: 50 g/m3 (Rat)

78-93-3	Methyl Ethyl Ketone Oral LD50: 2,737 mg/kg (Rat) Dermal LD50: 6 g/kg (Rabbit) Inhalation LC50: 320 g/m3 (Mouse)
107-87-9	Methyl Propyl Ketone Oral LD50: 1,600 mg/kg (Rat) Inhalation LC50: 26 mg/L (Rat)
110-43-0	Methyl Normal Amyl Ketone Oral LD50: 1,600 mg/kg (Rat) Dermal LD50: 5,000 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)
71-36-3	n-Butanol Oral LD50: 790 mg/kg (Rat) Dermal LD50: 3,400 mg/kg (Rabbit)

**Toxicological information:** The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 3 and 15 for details.

**Routes of Entry:**

Inhalation      Skin Contact      Eye Contact

**Exposure to this material may affect the following organs:**

Blood    Eyes      Kidneys    Liver      Lungs      Central Nervous System      Skin

**Effects of Overexposure**

**107-87-9**

**Methyl Propyl Ketone**

Eye Contact

May cause mild irritation. Symptoms include stinging, tearing, and redness.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits.

Skin Contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**108-88-3**

**Toluene**

Signs of symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in mood and behavior, muscle weakness, loss of coordination, confusion, irregular heartbeat, coma, and death.

Eye Contact

May cause mild irritation. Symptoms include stinging, tearing, and redness.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits.

Skin Contact May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**110-43-0**

**MAK**

Signs of symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Eye Contact May cause mild irritation. Symptoms include stinging tearing, and redness.

Inhalation Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing larger amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

Ingestion Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Skin Contact May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**67-64-1**

**Acetone**

Signs of symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and other central nervous system effects, high blood sugar, coma.

Eye Contact May cause mild irritation. Symptoms include stinging, tearing, and redness.

Ingestion Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits.

Skin Contact May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**71-36-3**

**n-Butanol**

Signs of symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), blurred vision.

Eye Contact	Can cause severe eye irritation. Symptoms include stinging tearing, and redness, and swelling of eyes. Can injure eye tissue.
Ingestion	Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.
Inhalation	Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits.
Skin Contact	Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, burns, and other skin damage.. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

#### **74-98-6**

##### **Propane**

Can cause rapid suffocation if in high enough concentrations. Extremely flammable liquified gas. Vapors may spread long distances and ignite.

Eye Contact	Contact with liquid may cause cold burns/frost bite
Ingestion	Ingestion is not considered a potential route of exposure.
Inhalation	In high concentrations, may cause asphyxiation. Symptoms may include loss of mobility/consciousness. victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.
Skin Contact	Contact with liquid may cause cold burns/frost bite.

#### **78-93-3**

##### **Methyl Ethyl Ketone**

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.  
Methyl Ethyl Ketone (78-93-3)

Eye Contact	May cause mild irritation. Symptoms include stinging, tearing, and redness.  Methyl Ethyl Ketone (78-93-3)
Ingestion	Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury. Methyl Ethyl Ketone (78-93-3)
Inhalation	Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits.  Methyl Ethyl Ketone (78-93-3)



Skin Contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Methyl Ethyl Ketone (78-93-3)

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing). See Section 15 for carcinogenicity assessment.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
108-88-3	Toluene	5% - 10%	

## Section 12 - Ecological Information

### Component Ecotoxicity

Acetone

Ecotoxicity

No data available

Persistence and Degradability

No data available

Bioaccumulative Potential

No data available

Mobility in Soil

No data available

Other Adverse Effects

Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances - Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Propane

Ecotoxicity  
No data available

Persistence and Degradability  
No data available

Bioaccumulative Potential  
No data available

Mobility in Soil  
No data available

Other Adverse Effects

Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Methyl Ethyl Ketone

Ecotoxicity  
No data available

Persistence and Degradability  
No data available

Bioaccumulative Potential  
No data available

Mobility in Soil  
No data available

Other Adverse Effects

Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toluene

Ecotoxicity

Toxicity to fish - LC50; (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l;  
Exposure time: 96 h; Test Type: flow-through test  
Toxicity to daphnia and other aquatic invertebrates - LC50 (Ceriodaphnia dubia):  
3.78 mg/l; Exposure time: 48 h; Test Type: Renewal  
Toxicity to daphnia and other aquatic invertebrates (Chronic Toxicity)- NOEC:  
0.74 mg/l; Exposure time: 7 d  
Acute aquatic toxicity (Assessment) - Toxic to aquatic life .  
Chronic aquatic toxicity (Assessment) - Harmful to aquatic life with long lasting effects.

Persistence and Degradability

No data available

Bioaccumulative Potential

Partition coefficient: n-octanol/water - log Pow: 2.73 (20 °C); pH: 7

Mobility in Soil

No data available

Other Adverse Effects

Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Methyl Propyl Ketone

Ecotoxicity

No data available

Persistence and Degradability

No data available

Bioaccumulative Potential

No data available

Mobility in Soil

No data available

Other Adverse Effects

Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Methyl Normal Amyl Ketone

Ecotoxicity  
No data available

Persistence and Degradability  
No data available

Bioaccumulative Potential  
No data available

Mobility in Soil  
No data available

Other Adverse Effects  
Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

n-Butanol

Ecotoxicity  
No data available

Persistence and Degradability  
No data available

Bioaccumulative Potential  
No data available

Mobility in Soil  
No data available

Other Adverse Effects  
Ozone Depletion Potential - Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances -  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### Section 13 - Disposal Considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IMDG	Aerosols	1950		2.1
DOT	Aerosols	1950		2.1

May be classed as Consumer Commodity, ORM-D, Limited Quantity

## Section 15 - Regulatory Information

According to the Reg. (EC) No 1272/2008, relating of the classification packaging and labelling of dangerous substances and preparations, the product is labelled as follows:

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):** WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Toluene 108-88-3 5 - 10%

**Carcinogenicity:**

**IARC:** Group 2B: Possibly carcinogenic to humans

**ACGIH:** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA:** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP:** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Carcinogenicity:**

**IARC -** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH -** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potentiation carcinogen by ACGIH.

**OSHA -** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potentiation carcinogen by OSHA.

**NTP -** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

n-Butanol 71-36-3 1 - 5%

Methyl Normal Amyl Ketone 110-43-0 1 - 5%

Methyl Propyl Ketone 107-87-9 1 - 5%

Toluene 108-88-3 5 - 10%

Methyl Ethyl Ketone 78-93-3 5 - 10%

Propane 74-98-6 15%

Acetone 67-64-1 30 - 40%

**Commonwealth of Massachusetts "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

n-Butanol 71-36-3 1 - 5%

Methyl Propyl Ketone 107-87-9 1 - 5%

Toluene 108-88-3 5 - 10%

Methyl Ethyl Ketone 78-93-3 5 - 10%

Propane 74-98-6 15%

Acetone 67-64-1 30 - 40%

**New Jersey Worker and Community Right To Know Hazardous Substance List:** The following substances appear on the New Jersey Right To Know Hazardous Substance List.

n-Butanol 71-36-3 1 - 5%

Methyl Normal Amyl Ketone 110-43-0 1 - 5%

Methyl Propyl Ketone 107-87-9 1 - 5%

Toluene 108-88-3 5 - 10%  
 Methyl Ethyl Ketone 78-93-3 5 - 10%  
 Propane 74-98-6 15%  
 Acetone 67-64-1 30 - 40%

**Commonwealth of Pennsylvania Worker and Community Right-To-Know Act:** This product contains the following chemicals which appear on the Pennsylvania Hazardous Substance List:

n-Butanol 71-36-3 1 - 5%  
 Methyl Normal Amyl Ketone 110-43-0 1 - 5%  
 Methyl Propyl Ketone 107-87-9 1 - 5%  
 Toluene 108-88-3 5 - 10%  
 Methyl Ethyl Ketone 78-93-3 5 - 10%  
 Propane 74-98-6 15%  
 Acetone 67-64-1 30 - 40%

**WHMIS Classification B2 Flammable Liquid / D2A Very Toxic Material**



**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

**Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA).** This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations, part 372.

78-93-3 Methyl Ethyl Ketone 5 - 10%  
 71-36-3 n-Butanol 1.0 - 5%  
 108-88-3 Toluene 5 - 10%


**Section 16 - Other Information**

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	2
<b>FLAMMABILITY</b>	4
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH  
 4 = EXTREME

**National Fire Protection Association (NFPA)**



**NON-WARRANTY.** The information presented in this publication is based upon the research and experience of Glyptal, Inc. No representation or warranty is made concerning the accuracy or completeness of the information presented in this publication. Glyptal, Inc. makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Glyptal, Inc. are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Glyptal, Inc. shall in no event be liable for any special, incidental, or consequential damages.

The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Glyptal, Inc., and to recommend precautionary measures for the storage and handling of the products. No liability can be assumed for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products. It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented

here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product . Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions . The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws . The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Reviewer Revision

Date Prepared: 9/15/2020