HumiSea













SAFETY DATA SHEET

1. Identification

Product identifier HumiSeal UV500

Other means of identification

Product code HumiSeal UV500

Recommended use Protective Coating for Printed Circuit Board

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

CHASE CORPORATION Zeta Drive Plant Company name

Address 201 Zeta Drive

Pittsburgh, PA 15238

United States

Telephone 1-866-932-0800 E-mail Not available.

1-800-424-9300 Chemtrec, US **Emergency phone number**

> Chemtrec, outside of US (+1)703-527-3887

2. Hazard(s) identification

Not classified. Physical hazards

Health hazards Acute toxicity, dermal Category 4 Acute toxicity, inhalation Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, respiratory Category 1 Sensitization, skin Category 1 Carcinogenicity Category 2 Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 2

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Material name: HumiSeal UV500

Hazard statement

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

80.17% of the mixture consists of component(s) of unknown acute inhalation toxicity. 71.6% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 71.02% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ISO-OCTYL ACRYLATE		29590-42-9	20 - < 30
ALIPHATIC POLYISOCYANATE		28182-81-2	10 - < 20
Tosyl isocyanate		4083-64-1	1 - < 3
Benzophenone		119-61-9	< 1
Diphenyl(2,4,6-trimethylbenzoyl)pho sphine Oxide		75980-60-8	< 1
Trimethylolpropane triacrylate		15625-89-5	< 1
Other components below reportable levels	5		50 - < 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Material name: HumiSeal UV500

General information

media

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighter Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hydiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace	Environmental	Exposure Level	(WEEL)	Guides
---------------	---------------	-----------------------	--------	--------

Туре	Value	
TWA	0.5 mg/m3	
TWA	37.5 mg/m3	
TWA	5 ppm 1 mg/m3	
	TWA TWA	TWA 0.5 mg/m3 TWA 37.5 mg/m3 5 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US WEEL Guldes: Skin designation

Trimethylolpropane triacrylate (CAS 15625-89-5)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove Hand protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

workplace.

Color

Odor

Light yellow.

Mild Organic.

Odor threshold

Not available.

pН Melting point/freezing point Does not apply.

Initial boiling point and boiling

Not available. Not available.

range Flash point Not available.

Evaporation rate

Not available.

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Not applicable.

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available. Not available.

Explosive limit - upper (%) Vapor pressure

0.13 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Negligible

Partition coefficient

Not available.

(n-octanol/water) Auto-Ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

275 - 375 cP

Other information

275 - 375 cP **Brookfield viscosity**

1.00 - 1.10 g/cm3 Density

Not explosive. **Explosive properties** Negligible Miscible (water)

Not oxidizing. Oxidizing properties 0.03 % estimated Percent volatile

Specific gravity 1 - 1 1

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Causes serious eye irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation, May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. **Acute toxicity**

Test Resuits Product Species

HumiSeal UV500

Acute Inhalation

87975 mg/l. 6 Hours estimated LC50 Rat

Test Results Species Components

Benzophenone (CAS 119-61-9)

Acute Oral

2895 mg/kg LD50 Mouse

Skin corrosion/irritation

Causes skin irritation.

Causes serious eye irritation.

Serious eye damage/eye irritation

Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization

May cause an allergic skin reaction. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzophenone (CAS 119-61-9)

2B Possibly carcinogenic to humans.

Material name: HumiSeal UV500

HumiSeal UV500 Version #: 06 Revision date: 09-25-2015 Issue date: 11-10-2014

^{*} Estimates for product may be based on additional component data not shown.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Product		Species	Test Results
HumiSeal UV500			
Aquatic			
Fish	LC50	Fish	2846.6406 mg/l, 96 hours estimated
Components		Species	Test Results

Aquatic

Fish

LC50

Fathead minnow (Pimephales promelas) 9.64 - 12.31 mg/t, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Material name: HumiSeal UV500 HumiSeal UV500 Version #: 06

Revision date: 09-25-2015 | Issue date: 11-10-2014

^{*} Estimates for product may be based on additional component data not shown.