DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Mixture

Chemical nature

Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethyldisilazane reaction with Silica	68909-20-6	>= 12 - <= 16
Methyltrimethoxysilane	1185-55-3	>= 2.1 - <= 3.5
Octamethylcyclotetrasiloxane	556-67-2	>= 0.21 - <= 0.22
Methanol	67-56-1	>= 0.1 - <= 0.13

SECTION 4. FIRST AID MEASURES

General advice

: In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled

If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact

In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact

: Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Suspected of damaging fertility.

Protection of first-aiders

First Aid responders should pay attention to self-protection,

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

SECTION 1. IDENTIFICATION

Product name

: DOWSIL™ 3140 RTV Coating

Product code

02709961

Manufacturer or supplier's details

Company Identification

THE DOW CHEMICAL COMPANY 2030 WILLARD H DOW CENTER

MIDLAND MI 48674-0000

UNITED STATES

Telephone

800-258-2436

24-Hour Emergency Contact

Chemtrec +1 800-424-9300

Local Emergency Number

800-424-9300

E-mail address

SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use

Adhesive, binding agents

Electrical industry and electronics

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Reproductive toxicity

: Category 2

GHS label elements

Hazard pictograms

Signal Word

: Warning

Hazard Statements

H361f Suspected of damaging fertility.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures

See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use only with adequate ventilation.

Advice on safe handling

Avoid inhalation of vapor or mist.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid

Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hexamethyldisilazane reaction with Silica	68909-20-6	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
Methyltrimethoxysilane	1185-55-3	TWA	7.5 ppm	DCC OEL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m³	NIOSH REL

DOWSIL™ 3140 RTV Coating



Version

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

7.0

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician

Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :

: Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides

Silicon oxides Formaldehyde

Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Hand protection

Material

Chemical-resistant gloves

Remarks

For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection

Wear the following personal protective equipment:

Safety glasses

Skin and body protection

Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures

Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Chemical customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Color

white, translucent

Odor

slight

Odor Threshold

No data available

pН

No data available

Melting point/freezing point

No data available

Initial boiling point and boiling :

> 65 °C

range

Ш

DOWSIL™ 3140 RTV Coating



Version Revision Date: SDS Number: Date of last issue: 03/07/2017 7.0 10/16/2017 1265102-00011 Date of first issue: 02/10/2015

ST	250 ppm 325 mg/m³	NIOSH REL
TWA	200 ppm 260 mg/m³	OSHA Z-1

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Hexamethyldisilazane reaction with Silica

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m³	NIOSH REL
		ST	250 ppm 325 mg/m³	NIOSH REL
		TWA	200 ppm 260 mg/m³	OSHA Z-1

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures

Processing may form hazardous compounds (see section

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be

released.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid

Exposure to moisture.

Incompatible materials

Oxidizing agents

Water

Hazardous decomposition products

Contact with water or humid

: Methanol

air

Thermal decomposition

Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity

Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

Hexamethyldisilazane reaction with Silica:

Acute oral toxicity

: LD50 (Rat): > 5,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Methyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 12.3 ml/kg

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Flash point

: > 101.1 °C

Method: closed cup

Evaporation rate

: No data available

Flammability (solid, gas)

Not applicable

Flammability (liquids)

Ignitable (see flash point)

Self-ignition

: The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure

No data available

Relative vapor density

No data available

Relative density

1.05

Solubility(ies)

Water solubility

No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature

No data available

Decomposition temperature

No data available

Viscosity

Viscosity, dynamic

300 Poise

Explosive properties

Not explosive

Oxidizing properties

The substance or mixture is not classified as oxidizing.

Molecular weight

: No data available

Particle size

Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Not classified as a reactivity hazard.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reac- :

tions

Can react with strong oxidizing agents.

Adequate ventilation is required.

See OSHA formaldehyde standard, 29 CFR 1910.1048

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Ingredients:

Hexamethyldisilazane reaction with Silica:

Assessment: Repeated exposure may cause skin dryness or cracking.

Methyltrimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Methanol:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Hexamethyldisilazane reaction with Silica:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Methyltrimethoxysilane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Methanol:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 42.1 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 9,500 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Skin corrosion/irritation

Not classified based on available information.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Result: positive

Remarks: On basis of test data.

Genotoxicity in vivo

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Remarks: On basis of test data.

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Remarks: On basis of test data.

Genotoxicity in vivo

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: On basis of test data.

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Methanol:

Genotoxicity in vitro

Test Type: Bacterial reverse mutation assay (AMES)

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Product:

Assessment: Does not cause skin sensitization.

Test Type: Buehler Test Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

Ingredients:

Methyltrimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitization rate in humans

Test Type: Buehler Test Species: Guinea pig Result: positive

Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test

Species: Guinea pig Result: negative

Remarks: On basis of test data.

Methanol:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Hexamethyldisilazane reaction with Silica:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Methyltrimethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: positive

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

Octamethylcyclotetrasiloxane:

Effects on fertility

Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female Application Route: inhalation (vapor) Symptoms: Effects on fertility. Remarks: On basis of test data.

Effects on fetal development

Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rabbit

Application Route: inhalation (vapor)

Symptoms: No effects on fetal development.

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

Methanol:

Effects on fertility

Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development

Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: The effects were seen only at maternally toxic

doses.

STOT-single exposure

Not classified based on available information.

Ingredients:

Methanol:

Target Organs: Eyes, Central nervous system Assessment: Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Methyltrimethoxysilane:

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011 Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:

Methanol:

Species: Mouse

Application Route: inhalation (vapor)

Exposure time: 18 Months

Result: negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen.

by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Ingredients:

Methyltrimethoxysilane:

Effects on fertility

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: No effects on fertility. Remarks: On basis of test data.

Effects on fetal development

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: On basis of test data.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011 Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Product:

No aspiration toxicity classification

Further information

Ingredients:

Octamethylcyclotetrasiloxane:

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Methyltrimethoxysilane:

: LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia sp. (Water flea)): > 122 mg/l

Exposure time: 48 h

: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120 Toxicity to algae

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms

EC50: > 100 mg/l

Method: OECD Test Guideline 209

Octamethylcyclotetrasiloxane:

Toxicity to fish LC50 (Cyprinodon variegatus (sheepshead minnow)): >

0.0063 mg/l

Exposure time: 336 h

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): >

0.022 mg/l

Exposure time: 72 h

Remarks: No toxicity at the limit of solubility.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

bw or less.

Octamethylcyclotetrasiloxane:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg

bw or less.

Repeated dose toxicity

Ingredients:

Methyltrimethoxysilane:

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Octamethylcyclotetrasiloxane:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact Remarks: On basis of test data.

Methanol:

Species: Rat NOAEL: 1.06 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 Days

Aspiration toxicity

Not classified based on available information.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Bioaccumulative potential

Ingredients:

Methyltrimethoxysilane:

Partition coefficient: n-

octanol/water

: log Pow: -2.36

Octamethylcyclotetrasiloxane:

Bioaccumulation

Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 12,400

Partition coefficient: n-

octanol/water

log Pow: 6.48 (25.1 °C)

Methanol:

Bioaccumulation

Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): < 10

Partition coefficient: n-

octanol/water

log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

Ingredients:

Octamethylcyclotetrasiloxane:

Results of PBT and vPvB

assessment

Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada. D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living

organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Dispose of in accordance with local regulations. Waste from residues

Contaminated packaging Empty containers should be taken to an approved waste

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

Toxicity to fish (Chronic toxic-:

itv)

NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l

Remarks: On basis of test data. No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity) NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l

Exposure time: 21 d

Remarks: On basis of test data. No toxicity at the limit of solubility.

Ecotoxicology Assessment

Chronic aquatic toxicity

May cause long lasting harmful effects to aquatic life.

Methanol:

Toxicity to fish

LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae

EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxic-:

ity)

NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l

Exposure time: 200 h

Toxicity to microorganisms

IC50: > 1,000 mg/l Exposure time: 3 h

Persistence and degradability

Ingredients:

Octamethylcyclotetrasiloxane:

Biodegradability

Result: Not readily biodegradable.

Biodegradation: 3.7 % Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in water

Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7

Method: OECD Test Guideline 111

Methanol:

Biodegradability

Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 20 d

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

NZIoC

: All ingredients listed or exempt.

TSCA

All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS

: All ingredients listed or exempt.

IECSC

All ingredients listed or exempt.

ENCS/ISHL

All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI

All ingredients listed, exempt or notified.

PICCS

: All ingredients listed or exempt.

DSL

All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

REACH

For purchases from Dow Chemical EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the

intention to export into EEA please contact your DC

representative/local office.

TCSI

: All ingredients listed or exempt.

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
The second secon		(lbs)	(lbs)
Methanol	67-56-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Reproductive toxicity

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated Hexamethyldisilazane reaction with Silica Methanol

70131-67-8 68909-20-6 67-56-1

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017

SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

tion Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB -Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date

10/16/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US/Z8

DOWSIL™ 3140 RTV Coating



Version 7.0

Revision Date: 10/16/2017


SDS Number: 1265102-00011

Date of last issue: 03/07/2017 Date of first issue: 02/10/2015

SECTION 16. OTHER INFORMATION


Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

DCC OEL : Dow Chemical Guide

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
DCC OEL / TWA : Time weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Avia-