

XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

SECTION 1. IDENTIFICATION

Product name

: XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Product code

000000000004088701

Manufacturer or supplier's details

Company name of supplier

Dow Corning Corporation

Address

South Saginaw Road

Midland Michigan 48686

Telephone

(989) 496-6000

Emergency telephone

24 Hour Emergency Telephone: (989) 496-5900

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use

Process regulators, other than polymerization or vulcanization

processes Intermediate Cosmetics

Lubricants and lubricant additives Anti-set off and adhesive agents

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Substance

Substance name

Dimethyl siloxane, trimethylsiloxy-terminated

CAS-No.

63148-62-9

Chemical nature

Silicone

Hazardous ingredients

No hazardous ingredients



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

SECTION 4. FIRST AID MEASURES

If inhaled

If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact

Wash with water and soap as a precaution. Get medical attention if symptoms occur.

In case of eye contact

Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed

If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders

No special precautions are necessary for first aid responders.

Notes to physician

Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides Silicon oxides Formaldehyde

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essarv

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

Personal precautions, protec- :

tive equipment and emergency procedures Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures

See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use only with adequate ventilation.

Advice on safe handling

Handle in accordance with good industrial hygiene and safety

practice.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid

Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures

Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.



XIAMETER(R) PMX-200 SILICONE FLUID 50

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006 Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

Hand protection

Remarks

Wash hands before breaks and at the end of workday.

Eye protection

Wear the following personal protective equipment:

Safety glasses

Skin and body protection

Skin should be washed after contact.

Hygiene measures

Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or

contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Color

colorless

Odor

characteristic

Odor Threshold

No data available

рΗ

No data available

Melting point/freezing point

No data available

Initial boiling point and boiling : > 65 °C

range

Flash point

> 120 °C

Method: closed cup

Evaporation rate

No data available

Flammability (solid, gas)

Not applicable



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

Upper explosion limit

No data available

Lower explosion limit

No data available

Vapor pressure

No data available

Relative vapor density

No data available

Relative density

0.96

Solubility(ies)

Water solubility

No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature

No data available

Decomposition temperature

No data available

Viscosity

Viscosity, kinematic

50 cSt

Explosive properties

Not explosive

Oxidizing properties

The substance or mixture is not classified as oxidizing.

Molecular weight

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not classified as a reactivity hazard.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be re-

leased.

Adequate ventilation is required.

See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid

None known.

Incompatible materials

Oxidizing agents

Hazardous decomposition products



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 20

Revision Date: 04/21/2016

SDS Number:

Date of first issue: 11/19/2014

Date of last issue: 11/02/2015

778933-00006

Thermal decomposition

Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity

LD50 (Rat): > 15,400 mg/kg

Assessment: The substance or mixture has no acute oral tox-

Remarks: Based on data from similar materials

Acute dermal toxicity

LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species: Rabbit

Result: No skin irritation Remarks: Based on test data

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.



XIAMETER(R) PMX-200 SILICONE FLUID 50

Version

Revision Date:

SDS Number:

Date of last issue: 11/02/2015

2.0

04/21/2016

778933-00006

Date of first issue: 11/19/2014

Test Type: Maximization Test

Species: Guinea pig

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on test data

Carcinogenicity

Not classified based on available information.

Product:

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity - Assess-

ment

Animal testing did not show any carcinogenic effects.

No ingredient of this product present at levels greater than or **IARC**

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

No ingredient of this product present at levels greater than or NTP

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility

Species: Rabbit, male

Application Route: Ingestion

Symptoms: No effects on fertility.

Remarks: Based on data from similar materials

Effects on fetal development

Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rabbit, female

Application Route: Skin contact

Symptoms: No effects on fetal development. Remarks: Based on data from similar materials

Reproductive toxicity - As-

No evidence of adverse effects on sexual function and fertility,



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

sessment

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Product:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg

bw or less.

Repeated dose toxicity

Product:

Species: Rat

Application Route: Ingestion Remarks: Based on test data

Species: Rabbit

Application Route: Skin contact

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

LC50 (Pleuronectes platessa (European plaice)): 350 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Mytilus edulis (blue mussel)): > 1,020 mg/l

Exposure time: 96 h

EC50 (Nereis diversicolor (ragworm)): > 10,000 mg/l

Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015

Date of first issue: 11/19/2014

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics

and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues

Dispose of in accordance with local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: No SARA Hazards



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015
Date of first issue: 11/19/2014

SARA 302

No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, trimethylsiloxy-terminated 63148-62-9

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other repro-

ductive defects.

The ingredients of this product are reported in the following inventories:

NZIoC

All ingredients listed or exempt.

REACH

All ingredients (pre-)registered or exempt.

TSCA

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical

Substances.

PICCS

All ingredients listed or exempt.

KECI

All ingredients listed, exempt or notified.

AICS

All ingredients listed or exempt.

IECSC

All ingredients listed or exempt.

ENCS/ISHL

All components are listed on ENCS/ISHL or exempted from

inventory listing.

DSL

All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the

1999 and NOW and are on or exempt from listing on

Canadian Domestic Substances List (DSL).

TCSI

All ingredients listed or exempt.



XIAMETER(R) PMX-200 SILICONE FLUID 50

Version 20


Revision Date: 04/21/2016

SDS Number: 778933-00006 Date of last issue: 11/02/2015 Date of first issue: 11/19/2014

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;



XIAMETER(R) PMX-200 SILICONE FLUID 50 CS

Version 2.0

Revision Date: 04/21/2016

SDS Number: 778933-00006

Date of last issue: 11/02/2015
Date of first issue: 11/19/2014

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date

: 04/21/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8