## DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010 Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

**SECTION 1. IDENTIFICATION** 

Product name

: DOWSIL™ 838 Silicone Adhesive Sealant

Product code

02008220

Manufacturer or supplier's details

Company Identification

THE DOW CHEMICAL COMPANY 2030 WILLARD H DOW CENTER

MIDLAND MI 48674-0000

**UNITED STATES** 

Telephone

: 800-258-2436

24-Hour Emergency Contact

Chemtrec +1 800-424-9300

Local Emergency Number

800-424-9300

E-mail address

SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use

: Adhesive, binding agents

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization

: Category 1

**GHS label elements** 

Hazard pictograms



Signal Word

Warning

**Hazard Statements** 

H317 May cause an allergic skin reaction.

**Precautionary Statements** 

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

1/21

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS** 

Substance / Mixture

Mixture

Chemical nature

Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Amorphous fumed silica	112945-52-5	>= 7 - <= 8
Methyltrimethoxysilane	1185-55-3	>= 1 - <= 3.4
Diisopropoxy di(ethoxyacetoacetyl) titanate	27858-32-8	>= 1.5 - <= 1.8
Titanium dioxide	13463-67-7	>= 0.69 - <= 0.77
Methanol	67-56-1	>= 0.1 - <= 0.12

## **SECTION 4. FIRST AID MEASURES**

General advice :

In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled

If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact

In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact

Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Protection of first-aiders

First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

when the potential for exposure exists.

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date:

10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

П

Notes to physician

Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media

Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides Silicon oxides

Formaldehyde Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions

: Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures

: See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

: Use only with adequate ventilation.

Advice on safe handling

Do not get on skin or clothing.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid

Do not store with the following product types:

Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Amorphous fumed silica	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m³ (Silica)	NIOSH REL
Methyltrimethoxysilane	1185-55-3	TWA	7.5 ppm	DCC OEL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m³ OSHA Z-1	
		TWA	10 mg/m³ (Titanium dioxide)	ACGIH
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m³	NIOSH REL

**Revision Date:** 

Version

## DOWSIL™ 838 Silicone Adhesive Sealant



5.0 10/16/2017 1197214-00010 Date of first issue: 02/02/2015

ST 250 ppm NIOSH REL 325 mg/m³

TWA 200 ppm OSHA Z-1 260 mg/m³

Date of last issue: 03/10/2017

### Hazardous components without workplace control parameters

SDS Number:

Ingredients	CAS-No.
Diisopropoxy	27858-32-8
di(ethoxyacetoacetyl) titanate	

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Amorphous fumed silica

Titanium dioxide

## Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m³	NIOSH REL
		ST	250 ppm 325 mg/m³	NIOSH REL
		TWA	200 ppm 260 mg/m³	OSHA Z-1
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m³	NIOSH REL
		ST	500 ppm 1,225 mg/m³	NIOSH REL
		TWA	400 ppm 980 mg/m³	OSHA Z-1

## Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

**Engineering measures** 

그는 말이 하셨습니까 하다 하시다.

Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

## DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Minimize workplace exposure concentrations.

## Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material

Chemical-resistant gloves

Remarks

Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection

Wear the following personal protective equipment:

Safety glasses

Skin and body protection

Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures

Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may

require added precautions.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance

: paste

Color

white

Odor

alcohol-like

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

**Revision Date:** 

SDS Number: 10/16/2017 1197214-00010 Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Odor Threshold

No data available

pΗ

Not applicable

Melting point/freezing point

No data available

Initial boiling point and boiling

Not applicable

range

Flash point **Evaporation rate**  Not applicable

Not applicable

Flammability (solid, gas)

Not classified as a flammability hazard

Self-ignition

The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure

Not applicable

Relative vapor density

No data available

Relative density

1.03

Solubility(ies)

Water solubility

No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature

No data available

Decomposition temperature

No data available

Viscosity

Viscosity, dynamic

Not applicable

**Explosive properties** 

Not explosive

Oxidizing properties

The substance or mixture is not classified as oxidizing.

Molecular weight

No data available

Particle size

No data available

**SECTION 10. STABILITY AND REACTIVITY** 

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Reactivity

: Not classified as a reactivity hazard.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reac-

tions

Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid

Exposure to moisture.

Incompatible materials

Oxidizing agents

Water

Hazardous decomposition products

Contact with water or humid

Methanoi

air

Propan-2-ol

Thermal decomposition

Formaldehyde

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Skin contact Ingestion Eye contact

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity

Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

### **Ingredients:**

### Amorphous fumed silica:

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date:

10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Acute dermal toxicity

: LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Information taken from reference works and the literature.

Methyltrimethoxysilane:

Acute oral toxicity

: LD50 (Rat): 12.3 ml/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity

LC50 (Rat): > 42.1 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity

: LD50 (Rabbit): > 9,500 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Acute oral toxicity

: LD50 (Rat): 23,020 mg/kg

Acute inhalation toxicity

: LC50 (Rat): > 173 mg/l Exposure time: 6 h

Test atmosphere: vapor

Remarks: Based on data from similar materials

Acute dermal toxicity

: LD50 (Rabbit): 12,870 mg/kg

Remarks: Based on data from similar materials

Titanium dioxide:

Acute oral toxicity

: LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity

LC50 (Rat): > 6.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Methanol:

Acute oral toxicity

Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Acute inhalation toxicity

Acute toxicity estimate: 3 mg/l

Exposure time: 4 h

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Test atmosphere: vapor Method: Expert judgment

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity

Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

### Skin corrosion/irritation

Not classified based on available information.

### Ingredients:

### Amorphous fumed silica:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Information taken from reference works and the literature.

### Methyltrimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

## Diisopropoxy di(ethoxyacetoacetyl) titanate:

Species: Rabbit

Result: No skin irritation

### Titanium dioxide:

Species: Rabbit

Result: No skin irritation

### Methanol:

Species: Rabbit

Result: No skin irritation

## Serious eye damage/eye irritation

Not classified based on available information.

## **Ingredients:**

## Amorphous fumed silica:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Information taken from reference works and the literature.

## Methyltrimethoxysilane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

11

## Diisopropoxy di(ethoxyacetoacetyl) titanate:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

### Titanium dioxide:

Species: Rabbit

Result: No eye irritation

### Methanol:

Species: Rabbit

Result: No eye irritation

## Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

## Respiratory sensitization

Not classified based on available information.

### **Ingredients:**

### Methyltrimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitization rate in humans

Test Type: Buehler Test Species: Guinea pig Result: positive

Remarks: On basis of test data.

## Diisopropoxy di(ethoxyacetoacetyl) titanate:

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

### Titanium dioxide:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

### Methanol:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig Result: negative

#### Germ cell mutagenicity

Not classified based on available information.

# **DOWSIL™ 838 Silicone Adhesive Sealant**



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

**Ingredients:** 

Methyltrimethoxysilane:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: positive

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

**Application Route: Ingestion** 

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse Result: negative

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

## DOWSIL™ 838 Silicone Adhesive Sealant



Version

**Revision Date:** 

SDS Number:

Date of last issue: 03/10/2017

5.0

10/16/2017

1197214-00010

Date of first issue: 02/02/2015

### Carcinogenicity

Not classified based on available information.

### **Ingredients:**

### Titanium dioxide:

Species: Rat

Application Route: inhalation (dust/mist/fume)

Exposure time: 24 Months

Method: OECD Test Guideline 453

Result: positive

Remarks: The mechanism or mode of action may not be relevant in humans.

These substance(s) are inextricably bound in the product and therefore do not contribute to a

dust inhalation hazard.

Carcinogenicity - Assess-

: Limited evidence of carcinogenicity in inhalation studies with

ment

animals.

### Methanol:

Species: Mouse

Application Route: inhalation (vapor)

Exposure time: 18 Months

Result: negative

IARC

Group 2B: Possibly carcinogenic to humans

Titanium dioxide

13463-67-7

**OSHA** 

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## Reproductive toxicity

Not classified based on available information.

### **Ingredients:**

### Methyltrimethoxysilane:

Effects on fertility

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female **Application Route: Ingestion** Symptoms: No effects on fertility. Remarks: On basis of test data.

Effects on fetal development

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: On basis of test data.

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Reproductive toxicity - As-

sessment

: No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Effects on fetal development:

Test Type: Embryo-fetal development

Species: Rabbit

**Application Route: Ingestion** 

Result: negative

Remarks: Based on data from similar materials

Methanol:

Effects on fertility

Test Type: Fertility/early embryonic development

Species: Mouse

**Application Route: Ingestion** 

Result: negative

Effects on fetal development

Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: The effects were seen only at maternally toxic

doses.

STOT-single exposure

Not classified based on available information.

Ingredients:

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Assessment: May cause drowsiness or dizziness.

Methanol:

Target Organs: Eyes, Central nervous system Assessment: Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Methyltrimethoxysilane:

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

ess.

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

5.0 10/16/20

1197214-00010

# nated dans toxicity

## Repeated dose toxicity

## **Ingredients:**

### Methyltrimethoxysilane:

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

## Diisopropoxy di(ethoxyacetoacetyl) titanate:

Species: Rat NOAEL: 86.7 mg/l

Application Route: inhalation (vapor)

Exposure time: 13 Weeks

Remarks: Based on data from similar materials

#### Titanium dioxide:

Species: Rat

NOAEL: 24,000 mg/kg Application Route: Ingestion Exposure time: 28 Days

Species: Rat NOAEL: 10 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: These substance(s) are inextricably bound in the product and therefore do not

contribute to a dust inhalation hazard.

### Methanol:

Species: Rat NOAEL: 1.06 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 Days

## **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

### Ingredients:

## Methyltrimethoxysilane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l

Exposure time: 96 h

# DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

**Revision Date:** 

SDS Number: 10/16/2017 1197214-00010 Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia sp. (Water flea)): > 122 mg/l

Exposure time: 48 h

Toxicity to algae

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms

EC50: > 100 mg/l

Method: OECD Test Guideline 209

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Toxicity to fish

: LC50 (Pimephales promelas (fathead minnow)): 11,130 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae

: EC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l

Remarks: Based on data from similar materials

Titanium dioxide:

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae

: EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l

Exposure time: 72 h

Toxicity to microorganisms

EC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Methanol:

Toxicity to fish

: LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)); > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae

: EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxic-:

NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l

Exposure time: 200 h

Toxicity to microorganisms

IC50: > 1,000 mg/l

Exposure time: 3 h

## DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Persistence and degradability

Ingredients:

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Biodegradability

: Result: Readily biodegradable.

Biodegradation: 66 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

Methanol:

Biodegradability

Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 20 d

**Bioaccumulative potential** 

**Ingredients:** 

Methyltrimethoxysilane:

Partition coefficient: n-

: log Pow: -2.36

octanol/water

Diisopropoxy di(ethoxyacetoacetyl) titanate:

Partition coefficient: n-

octanol/water

: log Pow: 0.05

Methanol:

Bioaccumulation

Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): < 10

Partition coefficient: n-

octanol/water

: log Pow: -0.77

Mobility in soil
No data available

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

Disposal methods

Resource Conservation and Recovery Act (RCRA)

:

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues

Dispose of in accordance with local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste

## **DOWSIL™ 838 Silicone Adhesive Sealant**



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010 Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

UNRTDG

Not regulated as a dangerous good

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

**49 CFR** 

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

## **CERCLA Reportable Quantity**

Ingredients	CAS-No.	CAS-No. Component RQ	
		(lbs)	(lbs)
Methanol	67-56-1	5000	*
Butan-1-ol	71-36-3	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Respiratory or skin sensitization

**SARA 313** 

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **US State Regulations**

### Pennsylvania Right To Know

Dimethyl siloxane, trimethoxysilyl-terminated Dimethyl Siloxane, Dimethylvinylsiloxy-terminated Amorphous fumed silica

68083-19-2 112945-52-5 67-56-1

Not Assigned

Methanol

## DOWSIL™ 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010 Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

### California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### California Permissible Exposure Limits for Chemical Contaminants

Amorphous fumed silica

112945-52-5

The ingredients of this product are reported in the following inventories:

**NZIoC** 

: All ingredients listed or exempt.

**KECI** 

All ingredients listed, exempt or notified.

REACH

For purchases from Dow Chemical EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the

intention to export into EEA please contact your DC

representative/local office.

**TSCA** 

All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

**AICS** 

All ingredients listed or exempt.

**IECSC** 

All ingredients listed or exempt.

**PICCS** 

All ingredients listed or exempt.

DSL

All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

## DOWSIL™ 838 Silicone Adhesive Sealant



Version

Revision Date:

SDS Number:

Date of last issue: 03/10/2017

5.0

10/16/2017


1197214-00010

Date of first issue: 02/02/2015

## **SECTION 16. OTHER INFORMATION**


### Further information

#### NFPA:



Special hazard.

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV) ACGIH BEI ACGIH - Biological Exposure Indices (BEI)

DCC OEL Dow Chemical Guide

NIOSH REL USA. NIOSH Recommended Exposure Limits

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit DCC OEL / TWA Time weighted average

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA 8-hour time weighted average OSHA Z-3 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer, IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial

# DOWSIL<sup>™</sup> 838 Silicone Adhesive Sealant



Version 5.0

Revision Date: 10/16/2017

SDS Number: 1197214-00010

Date of last issue: 03/10/2017 Date of first issue: 02/02/2015

Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified: NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship: RCRA - Resource Conservation and Recovery Act: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory: TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date

10/16/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8