



Revision Number: 006.0

Issue date: 04/18/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	BONDERITE C-SO 2382-BK AERO known as TURCO 4460-BK	IDH number:	882982
Product type:	Cleaner	Item number:	882982
Restriction of Use:	None identified	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information:	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE RESPIRATORY IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Toluene	108-88-3	20 - 30
Ethyl acetate	141-78-6	20 - 30
Methyl isobutyl ketone	108-10-1	10 - 20
Solvent naphtha (petroleum), light aliph., <0.1% benzene	64742-89-8	10 - 20
2-Propanol	67-63-0	10 - 20
n-Heptane	142-82-5	5 - 10
Cyclohexane	110-82-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If symptoms are experienced, remove source of contamination or move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	For skin contact flush with large amounts of water. Obtain medical attention if irritation persists. Launder contaminated clothing before reuse.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.
Notes to physician:	If breathing is difficult, give oxygen. This material, if aspirated into the lungs, may cause lipoid pneumonitis. Treat affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	Vapors are heavier than air and may travel to ignition sources and flash back. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Prevent further leakage or spillage if safe to do so. Contain spill.

Clean-up methods:

Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of according to Federal, State and local governmental regulations. Ventilate area.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Keep container closed. Provide adequate ventilation. Wash thoroughly after handling. Keep away from heat, spark and flame. Ground and bond all equipment as required (when transferring products). Use non-sparking tools when opening or closing containers.

Storage:

Keep the container tightly closed and in a cool, well-ventilated place.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling 500 ppm MAX. CONC 10 minutes	None	None
Ethyl acetate	400 ppm TWA	400 ppm (1,400 mg/m3) PEL	None	None
Methyl isobutyl ketone	20 ppm TWA 75 ppm STEL	100 ppm (410 mg/m3) PEL	None	None
Solvent naphtha (petroleum), light aliph., <0.1% benzene	None	100 ppm (400 mg/m3) PEL	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Cyclohexane	100 ppm TWA	300 ppm (1,050 mg/m3) PEL	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Prevent electrostatic charge build-up by using common bonding and grounding techniques.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear chemical goggles; face shield (if splashing is possible).

Skin protection:

Chemical resistant, impermeable gloves. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Water white
Odor:	Solvent
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	45 mm hg calculated
Boiling point/range:	76.7 °C (170.1 °F)calculated
Melting point/ range:	Not available.
Specific gravity:	0.81 at 25 °C (77°F)
Vapor density:	Not available.
Flash point:	-3.9 °C (24.98 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Appreciable
Partition coefficient (n-octanol/water):	Not available.
VOC content:	100 % EPA Method 24
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	Strong acids, alkalies and oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting. Repeated inhalation may be harmful; lung irritation and serious central nervous system disorders may result.

Skin contact: This product is irritating to the skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Prolonged contact with skin may cause dermatitis. A component in this product may be absorbed through the skin, especially if skin is damaged.

Eye contact: This product may be severely irritating to the eyes. Prolonged or repeated contact may worsen irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances. Ingestion of this product may result in central nervous system effects including headache, sleepiness, dizziness, slurred speech and blurred vision. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Toluene	Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 5,000 mg/kg Dermal LD50 (Rabbit) = 12,124 mg/kg Inhalation LC50 (Rat, 4 h) = 8000 ppm	Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant
Ethyl acetate	Oral LD50 (Rat) = 5.6 g/kg Oral LD50 (Mouse) = 0.44 g/kg	Blood, Central nervous system, Irritant
Methyl isobutyl ketone	Oral LD50 (Rat) = 2,080 mg/kg Dermal LD50 (Rabbit) = > 16,000 mg/kg Inhalation LC50 (Rat, 4 h) = 8.2 mg/l	Irritant, Central nervous system
Solvent naphtha (petroleum), light aliph., <0.1% benzene	None	Irritant
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
n-Heptane	Inhalation LC50 (Rat, 4 h) = 103 mg/l	Central nervous system, Irritant
Cyclohexane	Oral LD50 (Rat) = 29,820 mg/kg Oral LD50 (Mouse) = 1,300 mg/kg	Irritant, Central nervous system

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Toluene	No	No	No
Ethyl acetate	No	No	No
Methyl isobutyl ketone	No	Group 2B	No
Solvent naphtha (petroleum), light aliph., <0.1% benzene	No	No	No
2-Propanol	No	No	No
n-Heptane	No	No	No
Cyclohexane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: If discarded, this product is considered a RCRA ignitable waste, D001. This product contains a component or components identified as hazardous under 40 CFR 261.24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Flammable liquids, n.o.s. (Toluene, Ethyl acetate)
Hazard class or division: 3
Identification number: UN 1993
Packing group: II
DOT Hazardous Substance(s): Toluene, Ethyl acetate

International Air Transportation (ICAO/IATA)

Proper shipping name: Flammable liquid, n.o.s. (Toluene, Ethyl acetate)
Hazard class or division: 3
Identification number: UN 1993
Packing group: II

Water Transportation (IMO/MDG)

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Toluene, Ethyl acetate)
Hazard class or division: 3
Identification number: UN 1993
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene (CAS# 108-88-3). Methyl isobutyl ketone (CAS# 108-10-1).

CERCLA Reportable quantity: Toluene (CAS# 108-88-3) 1,000 lbs. (454 kg)
Ethyl acetate (CAS# 141-78-6) 5,000 lbs. (2,270 kg)
Methyl isobutyl ketone (CAS# 108-10-1) 5,000 lbs. (2,270 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Timothy Pratt, Regulatory Affairs Specialist

Issue date: 04/18/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.