

SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

E828RS /A100 500LB CLOSED HEAD

Section 1. Product and company identification

GHS product identifier

E828RS /A100 500LB CLOSED HEAD

MSDS Number

K122F

Product type Material uses **Epoxy Resin Epoxy Resin Systems**

Manufacturer/Supplier/Impor

Hexion Inc.

180 East Broad Street Columbus. Ohio 43215 USA

Contact person

4information@hexion.com

Telephone

For additional health and safety or regulatory information, call

1 888 443 9466.

Emergency telephone number

For Emergency Medical Assistance

Call Health & Safety Information Services

1-866-303-6949

For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887 CANUTEC CA Domestic (613) 996-6666

Section 2. Hazards identification

· Classification of the substance or

mixture

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

[Respiratory tract irritation] - Category 3

GHS label elements

Hazard pictograms

Signal word

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Version:

19.0

Date of issue/Date of revision: 02/03/2015

Date of previous issue: 05/28/2014

EPON™ Resin 828

Precautionary statements

General

Not applicable.

Prevention

Wear protective gloves.

Wear eye or face protection.

Use only outdoors or in a well-ventilated area.

Avoid breathing vapor.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the

workplace.

Response

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable

Call a POISON CENTER or physician if you feel unwell.

IF ON SKIN:

Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs:

Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result

None known.

in classification

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Ingredient name	% by weight	CAS number
4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer	100	25068-38-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Version: 19.0

Date of issue/Date of revision: 02/03/2015

Date of previous issue: 05/28/2014

EPONTM Resin 828 Page: 3/13

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position

and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before rcuse. Clean shoes

thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first aid personnel : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly

with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media
Unsuitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

EPONTM Resin 828 Page: 4/13

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of

any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste

disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see section 8 of

Page: 5/13

SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash

EPONTM Resin 828 Page: 6/13

contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with

an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Viscous liquid.

Color : Clear.

Odor : Not available
Odor threshold : Not available

pH : Not available

Melting point/ Freezing point : Not available
Boiling point : 260 °C (500.00 °F)

Flash point : Pensky-Martens Closed Cup: 251 °C (483.80 °F) (ASTM D 93)

Burning time: Not availableBurning rate: Not availableEvaporation rate: Not available

Flammability (solid, gas) : Not available

Lower and upper explosive : Lower: Not available

EPONTM Resin 828 Page: 7/13

(flammable) limits

Upper: Not available

Vapor pressure

: 0.03 mbar @ 77 °C (170.60 °F)

Vapor density

: Not available

Relative density

: 1.17

Solubility

: Not available

Solubility in water

: Negligible

Partition coefficient: n-

: Not available

octanol/water

Auto-ignition temperature

: Not available

Decomposition temperature

Not availableNot available

SADT

Dynamic: Not available

Viscosity

Dynamic. Not available

Kinematic: Not available

Other information

No additional information.

Section 10. Stability and reactivity

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Reactive or incompatible with the following materials:

aliphatic amines, strong oxidizing agents,

strong acids,

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Other hazards Reacts with considerable heat release with some curing agents.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4.4'-Isopropylidenediphenol-	idenediphenol-Epichlorohydrin Copolymer			

Page:8/13 EPONTM Resin 828

LD50 Oral	Rat	11,400 mg/kg	-
LD50 Dermal	Rat	2,000 mg/kg	

Conclusion/Summary

Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-Isopropylidenediphenol- Epichlorohydrin Copolymer	Skin - Erythema/E schar 404 Acute Dermal Irritation/Co rrosion	Rabbit	1.5 - 2		-
	Skin - Edema 404 Acute Dermal Irritation/Co	Rabbit	1.0 - 1.5		-
	eyes 405 Acute Eye Irritation/Co rrosion	Rabbit	0		-
	eyes - Redness of the conjunctiva	Rabbit	0.7		-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Mild irritant	Rabbit			-

Conclusion/Summary

Skin eyes Respiratory Not available Not available

Not available

Sensitization

Conclusion/Summary

Skin Respiratory Not available Not available

Mutagenicity

Conclusion/Summary

Not available

Carcinogenicity

Conclusion/Summary

Not available

Version: 19.0

Date of issue/Date of revision: 02/03/2015

Date of previous issue:

05/28/2014

EPONTM Resin 828

LD50 Oral	Rat	11,400 mg/kg	-
LD50 Dermal	Rat	2,000 mg/kg	-

Conclusion/Summary

Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-Isopropylidenediphenol- Epichlorohydrin Copolymer	Skin - Erythema/E schar 404 Acute Dermal Irritation/Co rrosion	Rabbit	1.5 - 2		-
	Skin - Edema 404 Acute Dermal Irritation/Co rrosion	Rabbit	1.0 - 1.5		-
	eyes 405 Acute Eye Irritation/Co rrosion	Rabbit	0		-
	eyes - Redness of the conjunctiva e	Rabbit	0.7		-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Mild irritant	Rabbit			-

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

Sensitization

Conclusion/Summary

Skin: Not availableRespiratory: Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

EPONTM Resin 828 Page: 9/13

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
4,4'-	-	-	•	-	-	-
Isopropylidenediphenol						
-Epichlorohydrin						
Copolymer						
Remarks:			ects were observed in			
	, –		udy conducted up to a	a high dose le	evel of 750 mg/l	kg/day that resulted
	in adult body w	eight decrem	ents.			

Conclusion/Summary

Not available

Teratogenicity

Conclusion/Summary

Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-Isopropylidenediphenol-	Category 3		Respiratory tract irritation
Epichlorohydrin Copolymer			

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on the likely routes of

Not available

exposure

Potential acute health effects

Eye contact

Causes serious eye irritation.

Inhalation

May cause respiratory irritation.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Ingestion

Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Adverse symptoms may include the following:

pain or irritation

watering

redness

Inhalation

Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact

Adverse symptoms may include the following:

irritation redness

Ingestion

No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

19.0 Version:

Date of issue/Date of revision: 02/03/2015

Date of previous issue: 05/28/2014

EPONTM Resin 828 Page: 10/13

Potential immediate effects Potential delayed effects Not availableNot available

Long term exposure

Potential immediate effects Potential delayed effects Not availableNot available

Potential chronic health effects

Conclusion/Summary

Not available

General

: Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

No known significant effects or critical hazards.

Carcinogenicity
Mutagenicity
Teratogenicity
Developmental effects
Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
reaction product: bisphenol-A-(e	epichlorhydrin); epoxy resin (number avera	ge molecular weight ≤ 700)
	Acute LC50 1.3 mg/l - 203 Fish, Acute	Fish - Fish	96 h
	Toxicity Test		
	Acute EC50 2.1 mg/l - 202 Daphnia	Aquatic invertebrates.	48 h
	sp. Acute Immobilization Test and	Water flea	
	Reproduction Test		
	Acute NOEC 0.3 mg/l - 211 Daphnia	Aquatic invertebrates.	21 d
	Magna Reproduction Test	Water flea	
	Acute LC50 > 11 mg/l -	Aquatic plants - Algae	72 h

Conclusion/Summary

Not available

Persistence/degradability

Conclusion/Summary

Not available

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4,4'-Isopropylidenediphenol-	2.64 - 3.78	3 - 31 31.00	low

Date of previous issue: 05/28/2014

Version: 19.0 Date of issue/Date of revision: 02/03/2015

EPONTM Resin 828 Page: 11/13

Epichlorohydrin Copolymer

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory UN/NA information

number

Proper shipping name

Classes/*PG

Reportable Quantity (RQ)

CFR

Non-regulated

TDG

Non-regulated

IMO/IMDG

Non-regulated

IATA (Cargo)

Non-regulated

*PG: Packing group

Special precautions for user

Transport within user's premises: always transport in closed

containers that are upright and secure. Ensure that persons

transporting the product know what to do in the event of an accident

Date of previous issue:

05/28/2014

or spillage,'

Section 15. Regulatory information

Version: 19.0 Date of issue/Date of revision: 02/03/2015 EPONTM Resin 828 Page: 12/13

United States

U.S. Federal regulations

: United States - TSCA 12(b) - Chemical export notification: None

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not

listed

United States - TSCA 5(e) - Substances consent order: Not listed

California Prop. 65:

WARNING: This product contains less than 0.1% of a chemical known to

the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxymethyl)-	Yes.	No.	5 μg/day	No.

United States inventory (TSCA:

All components are listed or exempted.

8b)

Canada

WHMIS (Canada) : Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : None required.

CEPA Toxic substances : None required.

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted. Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4

EPONTM Resin 828 Page: 13/13

representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

Not applicable.

statements

History

Date of printing: 02/20/2015Date of issue/Date of revision: 02/03/2015Date of previous issue: 05/28/2014

Version : 19.0

Prepared by : Product Safety Stewardship
Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

References : Not available

Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

® and (TM) Licensed trademarks of Hexion Inc.