

Revision Number: 005.1

## **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name:

Product type/use: Catalyst Restriction of Use: None ide Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE CAT 23LV CL known as CATALYST 23LV CLR 1LB 0.454KG Catalyst None identified

IDH number:

1188035

Item number:44207Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

|         | EMERGENCY OVERVIEW                       |
|---------|--|
| DANGER: | HARMFUL IF SWALLOWED.                    |
|         | CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. |
|         | MAY CAUSE AN ALLERGIC SKIN REACTION.     |

| HAZARD CLASS        | HAZARD CATEGORY |
|---------------------|-----------------|
| ACUTE TOXICITY ORAL | 4               |
| SKIN CORROSION      | 1               |
| SERIOUS EYE DAMAGE  | 1               |
| SKIN SENSITIZATION  | 1               |



#### **Precautionary Statements**

| Prevention: | Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eve and face protection.   |
|-------------|---|
| Response:   | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting, by and had be protochin.<br>NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF<br>INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.<br>Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for<br>several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin<br>irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. |
| Storage:    | Store locked up.  |
| Disposal:   | Dispose of contents and/or container according to Federal, State/Provincial and local<br>governmental regulations.  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                   | CAS Number | Percentage* |
|--|------------|-------------|
| Polypropylene glycol diamine (MW=230)    | 9046-10-0  | 30 - 60     |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9  | 30 - 60     |

IDH number: 1188035

Product name: LOCTITE CAT 23LV CL known as CATALYST 23LV CLR 1LB 0.454KG Page 1 of 5 \* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

| 4. FIRST AID MEASURES              |   |  |
|------------------------------------|---|--|
| Inhalation:                        | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.  |  |
| Skin contact:                      | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.                                       |  |
| Eye contact:                       | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.   |  |
| Ingestion:                         | Do not induce vomiting or give anything by mouth because this material can<br>enter the lungs and cause severe lung damage. Never give anything by mout<br>to an unconscious person. Get medical attention. |  |
| Symptoms:                          | See Section 11.   |  |
| 5. FI                              | RE FIGHTING MEASURES  |  |
| Extinguishing media:               | Water spray (fog), foam, dry chemical or carbon dioxide.  |  |
| Special firefighting procedures:   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.  |  |
| Unusual fire or explosion hazards: | Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.   |  |
| Hazardous combustion products:     | Oxides of carbon, oxides of nitrogen, irritating organic vapors. Ammonia. Tox fumes.  |  |

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| Environmental precautions: | Do not allow product to enter sewer or waterways.  |  |
|----------------------------|--|--|
| Clean-up methods:          | Remove all sources of ignition. Ensure adequate ventilation. Isolate area.<br>Keep unnecessary personnel away. Soak up with inert absorbent material<br>(e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed<br>container until ready for disposal. Refer to Section 8 "Exposure Controls /<br>Personal Protection" prior to clean up. |  |
| 7. HANDLING AND STORAGE    |  |  |

| Handling: | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8. Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8. |
|-----------|---|
| Storage:  | For safe storage, store at or below 25 °C (77°F)<br>Keep in a cool, well ventilated area away from heat, sparks and open flame.<br>Keep container tightly closed until ready for use.   |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                   | ACGIH TLV   | OSHA PEL  | AIHA WEEL                  | OTHER |
|--|---|---|----------------------------|-------|
| Polypropylene glycol diamine (MW=230)    | None  | None  | None                       | None  |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | None  | None  | None                       | None  |
| Engineering controls:                    | exposu  | e adequate local exhaust<br>re limits. Provide adequa<br>re below exposure limits   | ate local exhaust ventilat | •     |
| Respiratory protection:                  | Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.  |   |                            |       |
| Eye/face protection:                     | Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available. |   |                            |       |
| Skin protection:                         | apron o   | Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Cover as much of the exposed skin area as possible with appropriate clothing. |                            |       |

# 9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical state:                          | Liquid   |
|--|--|
| Color:                                   | Amber  |
| Odor:                                    | Amine  |
| Odor threshold:                          | Not available.                                 |
| pH:                                      | > 11.7   |
| Vapor pressure:                          | < 0.01 mbar (25 °C (77°F))                     |
| Boiling point/range:                     | > 160 °C (> 320°F)                             |
| Melting point/ range:                    | Not applicable                                 |
| Specific gravity:                        | 1.01   |
| Vapor density:                           | Not applicable                                 |
| Flash point:                             | > 93 °C (> 199.4 °F) Pensky Martens closed cup |
| Flammable/Explosive limits - lower:      | Not available.                                 |
| Flammable/Explosive limits - upper:      | Not available.                                 |
| Autoignition temperature:                | Not available.                                 |
| Flammability:                            | Not applicable                                 |
| Evaporation rate:                        | Not applicable                                 |
| Solubility in water:                     | Soluble  |
| Partition coefficient (n-octanol/water): | Not determined                                 |
| VOC content:                             | 250 g/l  |
| Viscosity:                               | Not available.                                 |
| Decomposition temperature:               | Not available.                                 |
|  |  |

| Stability:                           | Stable under normal conditions of storage and use.   |  |
|--------------------------------------|--|--|
| Hazardous reactions:                 | Will not occur.  |  |
| Hazardous decomposition<br>products: | Oxides of carbon. Oxides of nitrogen. Toxic fumes. Ammonia.  |  |
| Incompatible materials:              | Strong acids and oxidizing agents. Sodium hypochlorite. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces. |  |
| Reactivity:                          | Not available.   |  |
| Conditions to avoid:                 | High temperatures. Store away from incompatible materials. Heat, flames, sparks and other sources of ignition.   |  |

10 STABILITY AND REACTIVITY

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Product name: LOCTITE CAT 23LV CL known as CATALYST 23LV CLR 1LB 0.454KG Page 3 of 5

#### Potential Health Effects/Symptoms

| Inhalation:   | May cause respiratory tract irritation.  |
|---------------|--|
| Skin contact: | Causes skin burns. May cause allergic skin reaction.   |
| Eye contact:  | Causes serious eye damage. Burns of the eye may cause blindness.   |
| Ingestion:    | Harmful if swallowed. Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if swallowed. |

| Hazardous Component(s)                   | LD50s and LC50s | Immediate and Delayed Health Effects |
|--|-----------------|--------------------------------------|
| Polypropylene glycol diamine (MW=230)    | None            | Corrosive, Irritant                  |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | None            | Corrosive                            |
|  |                 |                                      |

| Hazardous Component(s)                   | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--|----------------|-----------------|---|
| Polypropylene glycol diamine (MW=230)    | No             | No              | No  |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | No             | No              | No  |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Polyamines, liquid, corrosive, n.o.s. (Polyoxy propylene diamine, 3,3'oxybis(ethyleneoxy)bis(propylamine)) Hazard class or division: 8 Identification number: UN 2735 Packing group: Ш International Air Transportation (ICAO/IATA) Proper shipping name: Polyamines, liquid, corrosive, n.o.s. (Polyoxy propylene diamine, 3,3'oxybis(ethyleneoxy)bis(propylamine)) Hazard class or division: 8 Identification number: UN 2735 Packing group: II Water Transportation (IMO/IMDG) Proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxy propylene diamine, 3,3'oxybis(ethyleneoxy)bis(propylamine)) Hazard class or division: 8 Identification number: UN 2735 Packing group: II

## **15. REGULATORY INFORMATION**

United States Regulatory Information

| TSCA 8 (b) Inventory Status:     | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. |
|----------------------------------|--|
| TSCA 12 (b) Export Notification: | None above reporting de minimis  |
| CERCLA/SARA Section 302 EHS:     | None above reporting de minimis.   |
| CERCLA/SARA Section 311/312:     | Immediate Health, Delayed Health   |
| CERCLA/SARA Section 313:         | None above reporting de minimis.   |
| California Proposition 65:       | This product contains a chemical known in the State of California to cause cancer.                                   |

Product name: LOCTITE CAT 23LV CL known as CATALYST 23LV CLR 1LB 0.454KG Page 4 of 5

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/30/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.