



Made in America

Features:

- D-Ring fastening is ideal for bundling trays and IC tubes
- Adjustable, releasable and reusable - easy to install
- Low charging meets ANSI/ESD S20.20 and ANSI/ESD S541
- Custom sizes available
- Operating Temperature: 300°F (149°C) max
- Melting Temperature: 459°F (237°C)
- Straps should be tested regularly to make sure they retain their ESD properties
- Made in America



*Trays not included

35653	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 18 in (457 mm)
35654	Low Charging Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 20 in (19 mm)
35655	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 24 in (609 mm)
35656	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 30 in (762 mm)

Specifications and procedures subject to change without notice. Unless otherwise noted, tolerance is ±10%.

LOW CHARGING CABLE TIES

MENDA

3651 WALNUT AVE., CHINO, CA 91710
 PHONE: (951) 627-2453 • FAX: (951) 755-8848
 WEBSITE: MendaPump.com

DRAWING NUMBER:
35653

DATE:
April 2017