

Ultranitril 381

DESCRIPTION AND GENERAL PROPERTIES


Material Nitrile
 Length (inches) 14
 Thickness (inches) 0.033 (Med. Wt.)
 Wrist Scalloped cuff
 Colour/Color Green
 Interior finish Textile support Mapa Technology
 Exterior finish Embossed texture
 Size / EAN 7 8 9 10 11
 Packaging 12 pairs/bag - 72 pairs/carton
 Complementary information Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3


CE 0334




Dexterity EN 420 : 5/5

Legends

EN 388 MECHANICAL HAZARDS



EN 407 THERMAL RISKS heat and fire



CHEMICAL RISKS

EN ISO 374-1 Type A



U V W X Y Z

- A Methanol
- B Acetone
- C Acetonitrile
- D Dichloromethane
- E Carbon Disulfide
- F Toluene
- G Diethylamine
- H Tetrahydrofurane
- I Ethyl acetate

EN ISO 374-1 Type B



X Y Z

- J n-Heptane
- K Sodium hydroxide 40%
- L Sulphuric acid 96%
- M Nitric acid 65%
- N Acetic acid 99%
- O Ammonia 25%
- P Hydrogen peroxide 30%
- S Hydrofluoric acid 40%
- T Formaldehyde 37%

EN ISO 374-1 Type C



CUT RESISTANCE

- | | | |
|-------------|-------------|-------------|
| A1 ≥ 200 G | A4 ≥ 1500 G | A7 ≥ 4000 G |
| A2 ≥ 500 G | A5 ≥ 2200 G | A8 ≥ 5000 G |
| A3 ≥ 1000 G | A6 ≥ 3000 G | A9 ≥ 6000 G |

MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5




Protection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS



EN 421



RADIOACTIVE CONTAMINATION

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

Extremely supple, due to the unique Mapa multi-layer process
Embossed texture for better grip of wet objects
Added comfort and thermal insulation, due to the cotton-knit lining
Previous name: Stansolv AK-22 381

MAIN FIELDS OF USE

Automotive/mechanical industry

Surface treatment
Part degreasing
Automotive assembly

Other industries

Machine maintenance
Laboratory tests

Chemical industry

Handling drums of chemical products
Chemical product blending
Manipulating valves

INSTRUCTIONS FOR USE

Instructions for use

It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the "CE"-type tests.

It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.

Put the gloves on dry, clean hands.

Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.

Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.

Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their packaging protected from light and humidity.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

in use with paints, pigments and inks: wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth

in use with a solvent (diluent, etc...): rub over with a dry cloth

in use with acids or alkalis: thoroughly rinse the gloves under running water, and rub over with a dry cloth.

Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

UE type certificate or CE type examination certificate : 0075/014/162/08/18/1663

Issued by the notified body nr : 0075 - C.T.C. – 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07

Quality assurance certificat : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS