# Valutek Ultra Thin Nitrile Powder-Free 9.5" Glove

Part Number: VTGNUTPFB95



## Description:

Valutek's ultra thin 3mil nitrile powder-free ambidextrous 9.5" glove is constructed from 100% clean synthetic nitrile polymer and contains no rubber latexs. This glove comes with beaded cuff and a textured fingertip design to ensure positive grip and to reduce particle count. All Valutek gloves are tested and manufactured in ISO compliant facilities under Valutek inspection and strict process control to ensure Valutek quality standards and product specifications.



#### Features:

- 100% clean and synthetic nitrile polymer (Acrylonitrile Butadiene)
- 9.5"/240mm length with beaded cuff
- Textured fingertips
- Powder-free, single chlorination and filtered water wash
- ESD compliant, acid and solvent compatible

## Application:

As part of the **Valutek Microtek product family**, this controlled environment packaged glove is recommended for use in a cleanroom Class 100 - 1,000. It is also commonly used in a wide variety of applications, including semiconductor, pharmaceutical, food handling, laboratory work, electronic, intricate parts handling and maintenance and cleanup.

#### **VTGNUTPFB95** Physical Properties

Part Number	Size	Palm Width (mm)	Weight (gm)	Length (inch/mm)	Test Method
VTGNUTPFB95-SM	SM	83 ± 3	$3.0 \pm 0.3$		IEST-RP-CC005.4 ASTM D3767
VTGNUTPFB95-MD	MD	95 ± 3	3.5 ± 0.3	9.5"/240	
VTGNUTPFB95-LG	LG	106 ± 3	4.0 ± 0.3	9.5 /240	
VTGNUTPFB95-XL	XL	112 ± 3	4.5 ± 0.3		

Tensile Properties	Tensile Strength	Ultimate Elongation	Test Method	Measured Points	Thickness		Test Method
Before Aging After Aging	14 MPa, min 12 MPa, min	500%, min 450%, min		Fingertip	3.94 mil	0.10 mm, min	ASTM D3767
				Palm	3.15 mil	0.08 mm, min	
				Cuff	2.36 mil	0.06 mm, min	

<sup>\*</sup>Barrier Integrity: AQL 1.5



Valutek West USA-Phoenix.AZ

USA-Albany.i

Valutek Asia Sdn. Bho

Valutek P.R.C

p 800.763.1250

• f 602.252.1972

info@valutek.com

## Valutek Ultra Thin Nitrile Powder-Free 9.5" Glove

Part Number: VTGNUTPFB95



### **VTGNUTPFB95** Technical Performance

Test result available upon request. Please contact Valutek for further details.

## VTGNUTPFB95 Packaging





- Outer bag contains inner bag with 2 stacks of 50 gloves. Gloves packaged cuffs on bottom, vacuum sealed, flat packed and with a carton liner. 100 ea/bag, 10 bags/case, 1000 ea/case.
- Critical environment compatible. All gloves are lot traceable with retention samples held in Quality Control for 36 months from date of manufacturing.

