

Technical Data Sheet

B&B™ 5151-B

Product Description

B&B 5151-B is a viscous liquid compound for removing high and low VOC polysulfide primers and sealants from metallic aircraft surfaces.

Features and Benefits

- Contains no chlorinated solvents, phenols, heavy metals, chromates
- Safe on aluminum, magnesium, steel, high strength steel, cadmium, titanium, and other structural metals.
- Low odor
- Flash point over 200°F (93°C)

Process

B&B 5151-B comes ready to use. Apply to coatings to be removed from metal surfaces by spray, flow, mop, brush or dip. Prior to application, surfaces should be clean and free of water. B&B 5151-B removes polysulfide primers and sealants and some polyurethane top coats.

Approvals

Approvals

U.S. Air Force T.O. 1-1-8

NSN # 6850-01-495-0149 (5 g), 6850-01-495-0150 (55 g)

Disposal/Safety

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal. Safety

Please see Safety Data Sheet for further information.

Packaging

Available in pails and drums.

Shelf Life

12 months when stored in original, sealed container above 50°F (10°C).

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.