

Technical Data Sheet

B&B™ 5151-M

Product Description

B&B 5151-M is a viscous liquid compound used in the removal of high and low VOC polysulfide primers, sealants and other coatings for metallic aircraft surfaces.

Features and Benefits

- Contains no chlorinated solvents, phenols, heavy metals, chromates
- Low odor
- Flash point over 200°F (93°C)
- B&B 5151-M removes:
 - MIL-S-81733 Type III (Sealing and coating compound [polysulfide] corrosion inhibitive)

Process

B&B 5151-M comes ready to use. Apply to coatings to be removed from metal surfaces by spray, flow, mop, brush or dip. Prior to application, surfaces should be clean and free of water. Dwell time will vary based on conditions of paint systems to be removed. Remove loosened polyurethane and polysulfide coatings with a brush or pad, then squeegee or wipe off. Rinse surfaces with water, **B&B JET-7** or **B&B RE-GEL**.

Approvals/Testing

Approvals

Navy TT-R-2918, Remover, Paint, No Hazardous Air Pollutants (HAPs) Type II

NSN # 8010-01-483-4367

Disposal/Safety

Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal.

Safety

Please see Safety Data Sheet for further information.

Packaging

Available in pails and drums.

Shelf Life

12 months when stored in original, sealed container above 50°F (10°C).



B&B™ 5151-M

Technical Data Sheet

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.

Vantage Specialties, Inc.

3938 Porett Drive • Gurnee, Illinois 60031 USA • P +1 847 244 3410 • F +1 847 249 6346 • www.vantagegrp.com