



We put space to work.

Item # _____

Job _____

Security Units - Electronic Keyless PIN Lock

Safe Storage: Protects valuable materials and sensitive items from loss or pilferage.

Convenient Security: Keyless electronic PIN Lock eliminates need for padlocks, key replacement, and is simple to use. Allows up to 20 different codes and has a 5+ year battery life. (2) AAA batteries included.

Microban® Antimicrobial Product Protection*: Metroseal 3 and MetroMax Q models feature Microban Antimicrobial Product Protection, designed to stay "cleaner between cleanings."

Ready View of Contents: Heavy-gauge open wire construction keeps the entire contents of the unit visible at all times, making it easy to check inventory.

Adjustable, Optional Intermediate Shelves: Patented, easily adjustable shelf designs — Super Adjustable Super Erecta, MetroMax Q, and qwikSLOT — allow flexibility to meet changing needs. Can be positioned in 1" (25 mm) increments along the entire height of post.

Patented, Ergonomic, 1/4 - Turn Door Handle: Makes opening and closing the unit easier than conventional security unit designs.

Double Door: Each door opens 270 degrees and can be secured along the sides of the unit.

Time Saving Assembly: Metro security units assemble quickly — right out of the box. PIN locks are pre-assembled on the door.

Shipped Knocked-Down: Saves on freight costs. Easily assembled.

Choose from Stationary or Mobile Standard and Heavy-Duty Configurations:

Safe Transportation: Mobile, security trucks provide the advantage of quick, protective transportation.

Easy Cleaning of Storage Areas: Mobile units move easily from walls to allow thorough cleaning of floors and walls.

Mobile Units: Available in Standard and Heavy-Duty models Heavy-Duty units offer increased rigidity and durability for applications such as crossing thresholds.

Stationary Units: Posts have leveling feet to compensate for uneven surfaces.



Super Erecta Shelf (HD Mobile) with optional Super Adjustable Super Erecta® Intermediate shelves.



MetroMax Q (Stationary) with optional Intermediate shelves.



quwikSLOT (Mobile) with optional Intermediate shelves.



PIN Lock

PIN Lock Material Specifications:

- Lock Body: Epoxy coated cast zinc
- Battery Cover: Polycarbonate ABS blend
- Buttons: Sealed membrane
- Operates on (2) AAA batteries

Application Guidelines for the PIN Lock:

- Not intended to be used in the following conditions: freezers, coolers, and cart wash chambers.
- Disinfecting protocols including autoclaves and chemical fogging are also not recommended.
- Acceptable continuous usage range: 50-120° F (10-49° C).



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

LO2-245
Printed in U.S.A. 7/20

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2020 InterMetro Industries Corp.



Security Units Electronic Keyless PIN Lock

14.03



Security Units - Electronic Keyless PIN Lock

Specifications

Super Erecta Shelf Stationary Security

Model No. Chrome	Model No. Metroseal 3	Model No. Stainless Steel	Width		Length		Height		Fits Shelf		Approx. Pkd. Wt.	
			in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
SEC33CPL	SEC33K3PL	-	21 ¹ / ₂	546	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695	18x36	457x914	140	64
SEC35CPL	SEC35K3PL	-	21 ¹ / ₂	546	50 ¹ / ₂	1295	66 ¹³ / ₁₆	1695	18x48	457x1219	159	72
SEC53CPL	SEC53K3PL	-	27 ¹ / ₄	692	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695	24x36	610x914	156	71
SEC55CPL	SEC55K3PL	-	27 ¹ / ₄	692	50 ¹ / ₂	1295	66 ¹³ / ₁₆	1695	24x48	610x1219	176	80
SEC56CPL	SEC56K3PL	-	27 ¹ / ₄	692	62 ¹ / ₂	1587	66 ¹³ / ₁₆	1695	24x60	610x1524	197	90
SEC63CPL	-	-	33 ¹ / ₂	851	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695	30x36	760x914	169	77
SEC65CPL	-	-	33 ¹ / ₂	851	50 ¹ / ₂	1295	66 ¹³ / ₁₆	1695	30x48	760x1219	195	89
SEC66CPL	-	-	33 ¹ / ₂	851	62 ¹ / ₂	1587	66 ¹³ / ₁₆	1695	30x60	760x1524	217	99

Super Erecta Shelf Mobile Security

Standard-Duty Stem Caster Models: feature 5" (127mm) swivel casters. Please note model numbers for specific caster types.

Model No. Chrome	Model No. Metroseal 3	Caster Type	Width		Length		Height		Fits Shelf		Approx. Pkd. Wt.	
			in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
SEC33ECPL	-	(2) 5MP/(2) 5MPB	21 ¹ / ₂	546	40 ³ / ₄	1035	68 ¹ / ₂	1740	18x36	457x914	148	67
SEC35ECPL	-	(2) 5MP/(2) 5MPB	21 ¹ / ₂	546	52 ³ / ₄	1340	68 ¹ / ₂	1740	18x48	457x1219	167	76
SEC53ECPL	-	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	40 ³ / ₄	1035	68 ¹ / ₂	1740	24x36	610x914	164	75
SEC55ECPL	-	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	52 ³ / ₄	1340	68 ¹ / ₂	1740	24x48	610x1219	184	84
SEC56ECPL	-	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	65	1651	68 ¹ / ₂	1740	24x60	610x1524	205	93
	SEC33EK3PL	(2) 5PC/(2) 5PCB	21 ¹ / ₂	546	40 ³ / ₄	1035	68 ¹ / ₂	1740	18x36	457x914	148	67
	SEC35EK3PL	(2) 5PC/(2) 5PCB	21 ¹ / ₂	546	52 ³ / ₄	1340	68 ¹ / ₂	1740	18x48	457x1219	167	76
-	SEC53VK3PL	(2) 5PC/(2) 5PCB	27 ¹ / ₄	692	40 ³ / ₄	1035	68 ¹ / ₂	1740	30x36	760x914	164	75
-	SEC55VK3PL	(2) 5PC/(2) 5PCB	27 ¹ / ₄	692	52 ³ / ₄	1340	68 ¹ / ₂	1740	30x48	760x1219	184	84
-	SEC56VK3PL	(2) 5PC/(2) 5PCB	27 ¹ / ₄	692	65	1651	68 ¹ / ₂	1740	30x60	760x1524	205	93
SEC63ECPL	-	(2) 5MP/(2) 5MPB	33 ¹ / ₂	851	40 ³ / ₄	1035	68 ¹ / ₂	1740	30x36	760x914	177	81
SEC65ECPL	-	(2) 5MP/(2) 5MPB	33 ¹ / ₂	851	52 ³ / ₄	1340	68 ¹ / ₂	1740	30x48	760x1219	204	93
SEC66ECPL	-	(2) 5MP/(2) 5MPB	33 ¹ / ₂	851	65	1651	68 ¹ / ₂	1740	30x60	760x1524	225	102

Casters: 5MP and 5MPB (with locking brake) feature a polyurethane tread.

5PC and 5PCB (with locking brake) casters feature a polymer horn and resist rusting. They are recommended for high-moisture environments.

Heavy-Duty Models: feature aluminum dollies with wraparound bumpers and 5" (127mm) diameter casters.

Model No. Chrome	Caster Type	Width		Length		Height		Fits Shelf		Approx. Pkd. Wt.	
		in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
SEC53LCPL	(2) B5P/B5PB	28 ¹ / ₁₆	713	38 ¹ / ₂	980	68 ¹ / ₂	1740	24x36	610x914	189	86
SEC55LCPL	(2) B5P/B5PB	28 ¹ / ₁₆	713	50 ¹ / ₂	1285	68 ¹ / ₂	1740	24x48	610x1219	212	96
SEC56LCPL	(2) B5P/B5PB	28 ¹ / ₁₆	713	63 ¹ / ₈	1600	68 ¹ / ₂	1740	24x60	610x1524	237	108

Intermediate Shelves for Super Erecta Shelf Security Units

Model No. Chrome	Model No. Metroseal 3	Model No. Stainless Steel	Width		Length		Approx. Pkd. Wt.	
			in.	mm	in.	mm	lbs.	kg
A1836NC	A1836NK3	-	18	457	36	914	9 ¹ / ₂	4.3
A1848NC	A1848NK3	-	18	457	48	1219	12	5.4
A2436NC	A2436NK3	-	24	610	36	914	13	6.0
A2448NC	A2448NK3	-	24	610	48	1219	16	7.0
A2460NC	A2460NK3	-	24	610	60	1524	21	9.5
A3036NC	-	-	30	760	36	914	15	6.8
A3048NC	-	-	30	760	48	1219	21	9.5
A3060NC	-	-	30	760	60	1524	26 ¹ / ₂	11.8

NOTE: Standard Super Erecta shelves can also be used as intermediate shelves. Refer to catalog sheet 10.01 for more information.

Security Units - Electronic Keyless PIN Lock

MetroMax Q Security Units

- Microban antimicrobial product protection is built into the enclosures, doors, handles, and shelves to keep the product “cleaner between cleanings.”
- Optional intermediate shelves: MetroMax Q quick adjust shelves or corrosion proof MetroMax i.

Specifications

- Standard Units consist of taupe epoxy coated top and bottom wire shelves, tri-lobal steel posts, wire enclosures, and doors. Casters and bumpers are included with mobile units. Intermediate shelves are sold separately.
- Grid openings: 13/4" x 13/4" (44 x 44mm).

MetroMax Q Stationary Units — 66 3/16" (1681mm) High

Model No.	Width		Length		Fits Shelf		Approx. Pkd. Wt.	
	in.	mm	in.	mm	in.	mm	lbs.	kg
MQSEC53EPL	26 15/16	685	38 7/8	987	24 x 36	610 x 914	150	68
MQSEC55EPL	26 15/16	685	50 7/8	1292	24 x 48	610 x 1219	158	72
MQSEC56EPL	26 15/16	685	62 7/8	1597	24 x 60	610 x 1524	163	74

Note: Leveling foot on post can be adjusted up to 1" (25mm) to compensate for uneven floors.

MetroMax Q Stem Caster Mobile Units — 67 13/16" (1723mm) High

Model No. includes four 5" (127mm) diameter casters	Width		Length		Fits Shelf		Approx. Pkd. Wt.	
	in.	mm	in.	mm	in.	mm	lbs.	kg
MQSEC53VEPL	27 13/16	707	40 3/4	1035	24x36	610x914	168	76
MQSEC55VEPL	27 13/16	707	52 3/4	1340	24x48	610x1219	178	81
MQSEC56VEPL	27 13/16	707	64 3/4	1645	24x60	610x1524	181	82

Note: Caster units use two 5PCX and two PCSX casters.

Optional Intermediate Shelves

Shelf with Grid Mat Model No.	Shelf with Solid Mat Model No.	Q Shelf with Grid Mat Model No.	Nominal Width		Nominal Length	
			in.	mm	in.	mm
MX2436G	MX2436F	MQ2436G	24	610	36	914
MX2448G	MX2436F	MQ2436G	24	610	48	1219
MX2460G	MX2436F	MQ2436G	24	610	60	1524



MQSEC53VEPL with optional intermediate shelves



Ergonomic 1/4-turn door handle

Replacement Tri-Lobal Adapters for MetroMax Q Wire Security Shelves



Model No. MTLA* - Four pair per bag

*Not compatible with MetroMax Q security units manufactured prior to May 2009. For older MetroMax Q security units, use MQ9965 wedges if replacements are needed for the wire shelves.

Replacement Doors with PIN Lock

Upgrade your existing security cages with a replacement door with a PIN lock already installed.

Size	Model No. Chrome	Model No. Metroseal 3	Model No. Stainless Steel	Model No. MetroMax Q
36" Shelf Unit	RPSECX3C-PLDOOR	RPSECX3NK3-PLDOOR	-	RPMQSECX3-PLDOOR
48" Shelf Unit	RPSECX5C-PLDOOR	RPSECX5NK3-PLDOOR	-	RPMQSECX5-PLDOOR
60" Shelf Unit	RPSECX6C-PLDOOR	RPSECX6NK3-PLDOOR	-	RPMQSECX6-PLDOOR

Job _____




Security Units - Electronic Keyless PIN Lock

We put space to work.

qwikSLOT™ Security Units

- Add/Remove a Shelf Feature: Allows the unit to be quickly adapted to fit your changing storage needs.
- Shelves can easily be adjusted in seconds.



Interior shelves pictured are optional and must be ordered separately.

Specifications

qwikSLOT Stationary Security

Model No. Chrome	Width		Length		Height		Fits Shelf		Approx. Pkd. Wt.	
	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
SEC33CQPL	21 ¹ / ₂	546	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695	18x36	457x914	140	64
SEC35CQPL	21 ¹ / ₂	546	50 ¹ / ₂	1283	66 ¹³ / ₁₆	1695	18x48	457x1219	159	72
SEC53CQPL	27 ¹ / ₄	692	38 ¹ / ₂	980	66 ¹³ / ₁₆	1695	24x36	610x914	156	71
SEC55CQPL	27 ¹ / ₄	692	50 ¹ / ₂	1283	66 ¹³ / ₁₆	1695	24x48	610x1219	176	80
SEC56CQPL	27 ¹ / ₄	692	62 ¹ / ₂	1578	66 ¹³ / ₁₆	1695	24x60	610x1524	197	90

qwikSLOT Mobile Security

Model No. Chrome	Caster Type	Width		Length		Height		Fits Shelf		Approx. Pkd. Wt.	
		in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
SEC33ECQPL	(2) 5MP/(2) 5MPB	21 ¹ / ₂	546	40 ³ / ₄	1035	68 ¹ / ₂	1740	18x36	457x914	148	67
SEC35ECQPL	(2) 5MP/(2) 5MPB	21 ¹ / ₂	546	52 ³ / ₄	1340	68 ¹ / ₂	1740	18x48	457x1219	167	76
SEC53ECQPL	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	40 ³ / ₄	1035	68 ¹ / ₂	1740	24x36	610x914	164	75
SEC55ECQPL	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	52 ³ / ₄	1340	68 ¹ / ₂	1740	24x48	610x1219	184	84
SEC56ECQPL	(2) 5MP/(2) 5MPB	27 ¹ / ₄	692	65	1651	68 ¹ / ₂	1740	24x60	610x1524	205	93

Intermediate Shelves for Super Erecta Shelf Security Units

Model No. Chrome	Width		Length		Approx. Pkd. Wt.	
	in.	mm	in.	mm	lbs.	kg
1836QBR*	18	457	36	914	8 ¹ / ₂	3.8
1848QBR*	18	457	48	1219	11 ¹ / ₄	5.0
2436QBR*	24	610	36	914	13	6.0
2448QBR*	24	610	48	1219	16	7.0
2460QBR	24	610	60	1524	21	9.5

*Chrome qwikSLOT shelves available in sizes 18x36, 18x48, 24x36, and 24x48 (457x914, 457x1219, 610x914, 610x1219, and 610x1524).

**Drop Mat qwikSLOT shelves with 1" (25mm) ledge also available in sizes 24x36, 24x48 (610x914, 610x1219).

an Ali Group Company



The Spirit of Excellence