

Valutek Nitrile Cleanroom 12" Glove

Part Number: VTGNCRB12



Description: Valutek's 12" ambidextrous nitrile powder-free cleanroom glove is constructed from 100% clean, synthetic nitrile polymer and contains no rubber latex. This glove has a textured fingertip and a beaded long cuff design which offers the ultimate cleanliness and operator dexterity with very low levels of particle and extractable counts. All Valutek gloves are tested and manufactured in ISO compliant facilities under Valutek inspection and strict process control to ensure Valutek quality standards and product specifications.

- Features:**
- 100% clean and synthetic nitrile polymer (Acrylonitrile Butadiene)
 - Accelerator and sulfur free
 - 12"/290 mm length with beaded long cuff
 - Textured fingertips
 - Powder-free, double chlorination and 18 megaohm D.I. water rinse
 - Low levels of particles and extractable counts
 - ESD compliant, acid and solvent compatible

Application: As part of the **Valutek Nanotek product family**, this cleanroom packaged glove is recommended for use in a cleanroom Class 1-10 (ISO 3-4) critical environment. It is also recommended for use in a wide variety of applications that require an extremely clean glove such as wafer fabrication, disk drives, semiconductor, biotechnology, non-aseptic pharmaceutical and optics.

VTGNCRB12 Packaging



- Outer bag contains inner bag with 2 stacks of 50 gloves. Gloves packaged cuffs on bottom, vacuum sealed, flat packed and with a carton liner. 100 ea/bag, 10 bags/case, 1000 ea/case.
- Critical environment compatible. All gloves are lot traceable with retention samples held in Quality Control for 36 months from date of manufacturing.



Valutek West
USA-Phoenix,AZ

Valutek East
USA-Albany,NY

Valutek Asia Sdn. Bhd
Malaysia

Valutek P.R.C.
China

p 800.763.1250 • f 602.252.1972 • info@valutek.com

www.valutek.com

Distributed by:

Hisco
Ph: 877-447-2650
info@hiscoinc.com

and

All-Spec
Ph: 800-537-0351
sales@all-spec.com

Valutek Nitrile Cleanroom 12" Glove

Part Number: VTGNCRB12

VTGNCRB12 Physical Properties

Part Number	Size	Palm Width (mm)	Weight (gm)	Length (inch/mm)	Test Method
VTGNCRB12-XS	XS	75 ± 5	5.5 ± 0.2	12"/290	IEST-RP-CC005.4 ASTM D3767
VTGNCRB12-SM	SM	85 ± 5	6.0 ± 0.2		
VTGNCRB12-MD	MD	95 ± 5	6.5 ± 0.2		
VTGNCRB12-LG	LG	105 ± 5	7.0 ± 0.2		
VTGNCRB12-XL	XL	115 ± 5	7.5 ± 0.2		
VTGNCRB12-2X	2X	125 ± 5	8.0 ± 0.2		

Tensile Properties	Tensile Strength	Ultimate Elongation	Test Method	Measured Points	Thickness	Test Method
Before Aging	18 MPa, min	500%, min	ASTM D412	Fingertip	4.72 mil	0.12 mm, min
				Palm	3.94 mil	0.10 mm, min
After Aging	16 MPa, min	450%, min		Cuff	3.15 mil	0.08 mm, min

*Barrier Integrity: AQL 1.5

VTGNCRB12 Technical Performance

Attribute	Value	Units	Test Method
Particle Counts			
LPC: ≥0.5 µm	<600	particles/cm ²	IEST-RP-CC005.4, Sec 16.4
Non Volatile Residue (NVR)			
DI Water	<2.0	µg/cm ²	IEST-RP-CC005.4, Sec 17.2
IPA	<5.0	µg/cm ²	IEST-RP-CC005.4, Sec 17.2
FTIR			
Silicone Oil, Amide, DOP	Not Detectable		IEST-RP-CC005.4, Sec 17.4

Extractable Counts (Ions)					
Sodium(Na)	<0.02	µg/cm ²	Fluoride(F ⁻)	<0.001	µg/cm ²
Potassium(K)	<0.02	µg/cm ²	Bromide(Br ⁻)	<0.001	µg/cm ²
Calcium(Ca)	<0.30	µg/cm ²	Phosphate(PO ₄ ³⁻)	<0.002	µg/cm ²
Magnesium(Mg)	<0.005	µg/cm ²	Chloride(Cl ⁻)	<0.20	µg/cm ²
Ammonium(NH ₄ ⁺)	<0.005	µg/cm ²	Sulfate(SO ₄ ²⁻)	<0.06	µg/cm ²
Nitrate(NO ₃ ⁻)	<0.12	µg/cm ²	Nitrite(NO ₂ ⁻)	<0.001	µg/cm ²
Lithium(Li)	<0.005	µg/cm ²	Aluminium(Al)	<0.01	µg/cm ²
Zinc(Zn)	<0.07	µg/cm ²	Iron(Fe)	<0.005	µg/cm ²
Copper(Cu)	<0.0004	µg/cm ²			

ESD Properties					
Electrostatic Decay	<5	seconds	Tribo Charge	<50	V
Surface resistivity	< 1 X 10 ¹¹	Ω ⁻²			ANSI/ESD SP15.1



Gloves




Wipers



Apparel



Adhesive Mats



Cleaning & Maintenance



Documentation



Glove Liners



ESD

Distributed by: Hisco and All-Spec
 Ph: 877-447-2650 Ph: 800-537-0351
 info@hiscoinc.com sales@all-spec.com

Version V 3.0/10.25.2017

www.valutek.com

INNOVATIVE SOLUTIONS FOR CRITICAL ENVIRONMENTS