

Safety Data Sheet dated 26/5/2020, version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Trade name: SURFACER FR4-45 BASE
Trade code: 64000XXXB
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended use:
Water based 2K polyurethane paint
- 1.3. Details of the supplier of the safety data sheet
Company:
MAPAERO SAS
10, Avenue de la Rijole
09100 PAMIERES
FRANCE
Tel : +33 (0)5 34 01 34 01 / Fax : +33 (0)5 61 60 23 30
Competent person responsible for the safety data sheet:
PSRA_PAMIERES@akzonobel.com
- 1.4. Emergency telephone number
Tel: 0044 151 951 3317

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
Adverse physicochemical, human health and environmental effects:
No other hazards
- 2.2. Label elements
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
Hazard pictograms:
None
Hazard statements:
None
Precautionary statements:
None
Special Provisions:
EUH210 Safety data sheet available on request.
EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass. May produce an allergic reaction.
Special provisions according to Annex XVII of REACH and subsequent amendments:
Restricted to professional users.
- 2.3. Other hazards
vPvB Substances: None - PBT Substances: None
Other Hazards:
No other hazards

SECTION 3: Composition/information on ingredients

- 3.1. Substances
N.A.
- 3.2. Mixtures
Hazardous components within the meaning of the CLP regulation and related classification:

Safety Data Sheet

SURFACER FR4-45 BASE

AkzoNobel

Qty	Name	Ident. Number		Classification
>= 10% - < 20%	talc	CAS:	14807-96-6	The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
		EC:	238-877-9	
>= 5% - < 10%	titanium dioxide	CAS:	13463-67-7	The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
		EC:	236-675-5	
		REACH No.:	01-2119489379-17	
>= 0.5% - < 2.5%	silane, dichlorodimethyl-, reaction products with silica	CAS:	68611-44-9	The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
		EC:	271-893-4	
< 0.1%	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass	Index number:	613-167-00-5	<div> <div>3.2/1B Skin Corr. 1B H314</div> <div>3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317</div> <div>4.1/A1 Aquatic Acute 1 H400 M=100.</div> <div>4.1/C1 Aquatic Chronic 1 H410 M=10.</div> <div>3.1/3/Oral Acute Tox. 3 H301</div> <div>3.1/3/Dermal Acute Tox. 3 H311</div> <div>3.1/3/Inhal Acute Tox. 3 H331</div> </div>
		CAS:	55965-84-9	
		EC:	611-341-5	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water with AFFF (Aqueous Film Forming Foam) additive

Foam

Unsuitable methods of extinction :

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Stored between 5°C and 35°C (41°F and 95°F) in full and sealed original packaging.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

talca - CAS: 14807-96-6

- OEL Type: MAK-TMW - TWA(8h): 2 mg/m³

- OEL Type: ACGIH - TWA(8h): 2 mg/m³

titanium dioxide - CAS: 13463-67-7

- OEL Type: ACGIH - TWA(8h): 10 mg/m³

- OEL Type: VME - TWA: 10 mg/m³

- OEL Type: MAK-KZW - STEL(15min): 10 mg/m³

- OEL Type: MAK-TMW - TWA(8h): 5 mg/m³

- OEL Type: DFG - TWA(8h): 0.3 mg/m³ - STEL(15min): 2.4 mg/m³

silane, dichlorodimethyl-, reaction products with silica - CAS: 68611-44-9

- OEL Type: VME - TWA(8h): 5 mg/m³

- OEL Type: VME - TWA(8h): 10 mg/m³

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass - CAS: 55965-84-9

- OEL Type: MAK-TMW - TWA(8h): 0.05 mg/m³

DNEL Exposure Limit Values

titanium dioxide - CAS: 13463-67-7

Worker Professional: 10 mg/m³

PNEC Exposure Limit Values

titanium dioxide - CAS: 13463-67-7

Target: Marine water - Value: 1 mg/l

Target: Marine water sediments - Value: 100 mg/kg

Target: Fresh Water - Value: 0.127 mg/l

Target: Freshwater sediments - Value: 1000 mg/kg

8.2. Exposure controls

Eye protection:

Before handling, wear safety goggles with protective sides accordance with standard EN166.

Protection for skin:

Wear protective clothing against solid chemicals and particles suspended in the air (type 5) in accordance with standard EN13982-1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Protection for hands:

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Respiratory protection:

Full-/Half-/quarter-face masks (DIN EN 136/140).

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 : A2

Particle filter according to standard EN143 : P3

Thermal Hazards:

None

Environmental exposure controls:

It is recommended using all available means to prevent and regulate exposure in compliance with legal requirements.

Use all the appropriate means to keep suspended dust levels under exposure limits.

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:	Thick	
Odour:	Characteristic	
Odour threshold:	N.A.	
pH:	N.A.	
Melting point / freezing point:	0 °C	
Initial boiling point and boiling range:	100 °C	
Solid/gas flammability:	N.A.	
Upper/lower flammability or explosive limits:		N.A.
Vapour density:	N.A.	
Flash point:	PE> 93 °C	
Evaporation rate:	N.A.	
Vapour pressure:	N.A.	
Relative density:	<1	
Solubility in water:	N.A.	
Solubility in oil:	N.A.	
Partition coefficient (n-octanol/water):		N.A.
Auto-ignition temperature:	N.A.	
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	

9.2. Other information

Miscibility:	N.A.	
Fat Solubility:	N.A.	
Conductivity:	N.A.	
Substance Groups relevant properties:		N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Flames and hot surfaces
The accumulation of electrostatic discharges

10.5. Incompatible materials

Acids
Bases
Oxidizing agents

Metals

10.6. Hazardous decomposition products

Nitrogen oxides
Carbon oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

silane, dichlorodimethyl-, reaction products with silica - CAS: 68611-44-9

a) acute toxicity:

Test: LC50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 0.477 mg/l - Duration: 4h

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass - CAS: 55965-84-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4467 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

silane, dichlorodimethyl-, reaction products with silica - CAS: 68611-44-9

a) Aquatic acute toxicity:

Endpoint: LC50 Fish > 10000 mg/l - Duration h: 96

Endpoint: EC50 Daphnia > 10000 mg/l - Duration h: 24

Endpoint: CI50 Algae > 10000 mg/l - Duration h: 72

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 Daphnia = 6.7 mg/l - Duration h: 48

Endpoint: EC50 Algae = 3.2 mg/l - Duration h: 72

Endpoint: EC50 Fish = 14.6 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

Safety Data Sheet

SURFACER FR4-45 BASE

AkzoNobel

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.
The codes for waste (Decision 2001/573/CE, Directive 2006/12/CEE, Directive 94/31/CEE on hazardous waste) :

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

Additional disposal information:

Do not discharge into drains, water, nature.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

The product is transported in conditions that comply with exemption criteria for ADR transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/699 (ATP 11 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

Restriction 28

Volatile Organic compounds - VOCs = 0.00 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

Safety Data Sheet

SURFACER FR4-45 BASE

AkzoNobel

Hazard class and hazard category	Code	Description
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking
 SECTION 2: Hazards identification
 SECTION 3: Composition/information on ingredients
 SECTION 7: Handling and storage
 SECTION 8: Exposure controls/personal protection
 SECTION 11: Toxicological information
 SECTION 12: Ecological information
 SECTION 13: Disposal considerations
 SECTION 15: Regulatory information
 SECTION 16: Other information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
 Commission of the European Communities
 SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
 Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ATE: Acute Toxicity Estimate
 ATEmix: Acute toxicity Estimate (Mixtures)
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CLP: Classification, Labeling, Packaging.
 DNEL: Derived No Effect Level.
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

Safety Data Sheet
SURFACER FR4-45 BASE

AkzoNobel

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.